VM1NNO00TEQ

Ultrasonic sensor - discrete - 18 mm snout dual mount - 12-24 V DC



Main Range of product Hyde Park Sensor type Ultrasonic sensor Virtu VM1 Series name VM1 Device short name Sensor design Flat form + cylindrical M18 [Sn] nominal sensing 20.00 in (508 mm) distance Type of sensing window Adjustable Material Plastic Enclosure material Valox Front material Glass epoxy Type of output signal Discrete Discrete output function 1 NO Wiring technique 4-wire 12...24 V DC overload and short-circuit protection [Us] rated supply voltage Supply voltage limits 10...28 V DC NPN Discrete output type

1 male connector M12 4 pins

Complementary

[Sd] sensing range	2.0020.00 in (50.8508 mm)
Blind zone	2.01 in (51 mm)
Transmission frequency	300 kHz
Repeat accuracy	1.27 %
Beam angle	5°
Minimum size of detected object	Cylinder diameter 2.5 mm - up to 200 mm sensing distance
Current consumption	40 mA
Maximum switching current	100 mA reverse polarity protection
Height	1.72 in (43.7 mm)
Width	0.71 in (18 mm)
Maximum Depth	1.72 in (43.7 mm)
Length	2.35 in (59.69 mm)
Net Weight	0.07 lb(US) (0.033 kg)

Electrical connection

Product specific application

Environment

Product certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X indoor use only)	
IP degree of protection	IP67	
Ambient air temperature for operation	-22158 °F (-3070 °C)	
Ambient air temperature for storage	-40185 °F (-4085 °C)	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm 1055 Hz)IEC 60068-2-6	
Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27	

Resistance to electromagnetic fields	9.14 V/m (10 V/m) level 3 IEC 61000-4-3
Resistance to fast transients	1 kV level 3 IEC 61000-4-4
Ordering and shipping details	
Category	22490 - SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	03389119063968
Nbr. of units in pkg.	1
Package weight(Lbs)	0.13 lb(US) (0.06 kg)
Returnability	No
Country of origin	US
Offer Sustainability California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Contractual warranty	
Warranty	18 months

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schneider manufacturer:

Other Similar products are found below:

ATV312H037M2 LU9M1 7D 7S 7XA1 FNQR2 8501RS44V24 8501RSD14P14V51 8501XO20V03Y414 9001KR9RH13 9001KXRK
9001SKR9P35RH25 9001SKT35L31 9003K2C003GA 9007AA1 9007BA1 9007C54D 9007C62A2 9007CA11 9007FA3 9007HA4
9007HA6 9007KA1 9007KB11 9007MS01S0206 9012GAR4 9012GAW2 9012GBW1 9012GDW5E3 9012GFW1 9012GNG1 9012GNG3
9012GNG6 9013FHG39J69 9013FSG52J33M4 9013GHG2J30 9050JCK2F30V14 GZ1E02 ABL8MEM24003 ABL8RPS24030
ATS01N206QN RSL1PRJU 9001KA35 9001KA3G 9001KA4 9001KR16H13 9001KR1GH5 9001KR1U 9001KXSDC 9007C52A2