



Schneider Electric Relays


200 N. Martingale Rd., Suite 1000

Schaumburg, IL 60173

Phone: 847-441-2540 • Fax: 847-881-0741

E-Mail: relays@schneider-electric.com • Web site: www.sere relays.com

ITEM # W9AS5D52-24, 9A MINIATURE POWER RELAYS / SPDT, 30 AMP RATING (DC)



[SPECIFICATIONS](#) | [CONTACT CHARACTERISTICS](#) | [COIL CHARACTERISTICS](#) | [PERFORMANCE CHARACTERISTICS](#) | [ENVIRONMENT](#) | [PRODUCT CERTIFICATIONS](#)

Specifications

Check Inventory [Check Distributor Inventory](#)

Status Standard

Cover Style Flange Cover

Figure B

California Proposition 65 Warning



WARNING: This product can expose you to chemicals including:
Substance 1: Nickel compounds, which is known to the State of California to cause cancer.

Substance 2: DIDP, which is known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov

Contact Characteristics

Contact Rating Normally Closed Contact: 15 A
 Normally Open Contact: 30 A

Contact Configuration SPDT

Contact Materials Silver Alloy

Maximum Switching Voltage (V)	300 V
Switching Current at Voltage (AC, Resistive)	Normally Closed Contact: 10 A at 240 VAC 50/60 Hz Normally Open Contact: 20 A at 240 VAC 50/60 Hz
Switching Current at Voltage (DC, Resistive)	Normally Closed Contact: 10 A at 28 VDC Normally Open Contact: 30 A at 28 VDC
Switching Current at Voltage (Pilot Duty)	Normally Closed Contact: 275 VA Normally Open Contact: 470 VA
Minimum Switching Requirement	1 A at 5 VDC, 12 VAC

Coil Characteristics

Nominal Input Voltage	24 VDC
Coil Resistance (Ohms)	576 Ohm
Operating Range - % of Nominal (AC)	80 to 110 %
Operating Range - % of Nominal (DC)	75 to 110 %
Average Consumption (AC / VA)	2.80 VA
Average Consumption (DC / W)	1 W
Drop-out Voltage Threshold (DC)	10 %
Drop-out Voltage Threshold (AC)	10 %

Performance Characteristics

Electrical Life (UL508), Operations at Rated Current (Resistive)	100000
Mechanical Life, Unpowered	10000000
Operating Time (Response Time)	15 ms
Dielectric Strength - Between Coil and Contact	2500 VAC (rms)
Dielectric Strength - Between Poles	1500 VAC (rms)

Environment

Ambient Air Temperature around the Device - Storage	-40 to +85 °C
Ambient Air Temperature around the Device - Operation	-40 to +55 °C

Shock Resistance

10 g-n

Product Certifications

-

Agency Approvals

UL
RoHs

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [General Purpose Relays](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[PCN-105D3MH,000](#) [59641F200](#) [5JO-1000CD-SIL](#) [LY1SAC110120](#) [5X827E](#) [5X837F](#) [5X840F](#) [5X842F](#) [5X848E](#) [LY2N-AC120](#) [LY2S-AC220/240](#) [LY2-US-AC120](#) [LY3-US-AC120](#) [LY4F-UA-DC12](#) [LY4F-UA-DC24](#) [LY4F-US-AC120](#) [LY4F-US-AC240](#) [LY4F-US-DC24](#) [LY4F-VD-AC110](#) [LYQ20DC12](#) [M115C60](#) [M115N010](#) [M115N0150](#) [6031007G](#) [603-12D](#) [61211T0B4](#) [61212T400](#) [61222Q400](#) [61243B600](#) [61243C500](#) [61243Q400](#) [61311BOA2](#) [61311BOA6](#) [61311BOA8](#) [61311C0A2](#) [61311COA1](#) [61311COA6](#) [61311F0A2](#) [61311QOA1](#) [61311QOA4](#) [61311T0D6](#) [61311TOA6](#) [61311TOA7](#) [61311TOB3](#) [61311TOB4](#) [61311U0A6](#) [61312Q600](#) [61312T400](#) [61312T600](#) [61313U200](#)