Product data sheet Characteristics

XACB9212 booted head for pushbutton XAC-B - black - 16 mm, -25..+70 °C

Product availability: Stock - Normally stocked in distribution facility



Main	
Range of product	Harmony XAC
Product or component type	Head for push-button
Component name	XACB
Marking	Unmarked
Operator additional in- formation	Booted
Operating travel	0.63 in (16 mm)
Cap/operator or lens colour	Black
Product compatibility	XESD1181 XESD1191 XESD1281 XESD1291
Sale per indivisible quantity	10

Complementary

Product weight

0.01 lb(US) (0.005 kg)

Environment		
Standards	EN 60947-5-1 CSA C22.2 No 14 IEC 60947-5-1	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Vibration resistance	15 gn (f = 10500 Hz) conforming to IEC 60068-2-6	
Shock resistance	100 gn conforming to IEC 60068-2-27	
Electrical shock protection class	Class II conforming to IEC 61140	
IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 50102	

Ordering and shipping details

Category	22473 - PUSHBUTTON, PENDANTS
Discount Schedule	CS2
GTIN	00785901640943
Nbr. of units in pkg.	10
Package weight(Lbs)	0.01
Returnability	Y
Country of origin	CZ

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period

18 months

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Cases / Switch Covers category:

Click to view products by Schneider manufacturer:

Other Similar products are found below :

 704.925.2
 AMS-8C
 DPS8L2
 DPS8P2
 DPS8PW2
 AP-DV
 PBBOX1HBY
 PBBOX4HBY
 SA1074
 HE9Z-D5Y
 3107
 A3C-3002
 L188

 EUK-704.927.0
 EUK-704.927.4
 HE9Z-D5N1
 W42
 L180
 M539
 HE9Z-D5B
 08-0-0-01
 905
 08-0-0-02
 M1080
 A165-CTA
 435238-5

 M1080-1
 704.927.6
 51-920
 61-9922.0
 HW9Z-KL1
 9001K7
 A3PJ-5060
 113160
 2202
 113260
 M12
 2201
 L167
 SA1072

 M1080-2
 PBBOX1HBG
 PBBOX4HBG
 1.20.810.302/0000
 3109
 3103
 3206
 3209
 61-9920.0
 61-9924.0
 76P02
 76P02