



### 主要信息

产品系列	Harmony XB2
产品类型	完全不发光的蘑菇头按钮
产品短名	XB2
边框材料	塑料
安装直径	22 mm

### 补充信息

操作位置	任何位置
设备安装	固定孔 - 直径: 22 mm
安装孔距	>= 30 x 40 mm (面板) - 厚度: 1...5 mm
固定模式	固定螺母: 2...2.4 N.m
信号单元头部形状	圆形
操作头类型	旋转复位
复位	旋转复位
操纵杆外形	红色 蘑菇头 Ø 60 mm
触点类型	1NC
触点动作	慢断
强制打开	带NC触头
机械寿命	100000 次
接线能力	螺旋压入式端子, <= 2 x 1.5 mm <sup>2</sup> 螺旋压入式端子, <= 1 x 2.5 mm <sup>2</sup> 螺旋压入式端子, >= 1 x 0.5 mm <sup>2</sup>
紧固扭矩	0.8 N.m
短路保护	10 A gL 熔断器 符合 IEC 60269-1
约定发热电流 [I <sub>th</sub> ]	10 A
额定绝缘电压 [U <sub>i</sub> ]	600 V 符合 IEC 60947-1
额定冲击耐受电压 [U <sub>imp</sub> ]	6 kV 符合 IEC 60947-1
额定工作电流 [I <sub>e</sub> ]	3 A 在...上 240 V, AC-15, A600 0.27 A 在...上 250 V, DC-13, Q600

电气寿命	500000 次, AC-15, 3 A 在...上 230 V, 工作额定值 <60 次/分钟, 负载系数: 0.5 符合 IEC 60947-5-4 500000 次, DC-13, 0.2 A 在...上 110 V, 工作额定值 <60 次/分钟, 负载系数: 0.5 符合 IEC 60947-5-4
电气可靠性	$\Lambda < 10\exp(-8)$ 在...上 24 V
高度	30 mm
宽度	42 mm
深度	74.2 mm
产品重量	0.088 kg

## 环境

保护处理	TC
贮存环境温度	-40...70 °C
运行温度	-25...55 °C
过电压种类	Class I 符合 IEC 536
IP 保护等级	IP65 符合 IEC 60529
IK 保护等级	IK03 符合 IEC 60529
抗振动	10 gn (f= 40...500 Hz) 符合 IEC 60068-2-6
抗冲击	70 gn (持续时间 = 11 ms) 适用 半正弦冲击 符合 IEC 60068-2-27

## 可持续性

产品类型	Green Premium 产品
REACH法规	<a href="#">REACH 声明</a>
REACH (不含 SVHC)	是
欧盟ROHS指令	主动合规性 (超出欧盟 RoHS 法定范围的产品) <a href="#">欧盟ROHS声明</a>
无汞	是
RoHS 豁免信息	是
中国 ROHS 管理办法	<a href="#">中国 ROHS 声明</a>
环境披露	<a href="#">产品环境文件</a>
流通资料	<a href="#">产品使用寿命终期信息</a>

## 合同保修

保修单	18 个月
-----	-------

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [Schneider](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)  
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)  
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)  
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)  
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)  
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)