



主要信息

产品系列	Harmony XB2
产品类型	整套指示灯
产品短名	XB2B
边框材料	塑料
安装直径	22 Mm
每件单独销售数量	1
操作头或镜片颜色	绿色
灯源	LED灯泡
灯座	内置BA 9s底座
额定电源电压 [Us]	110 V 直流
设备简介	产品 (非零部件)

补充信息

高度	30 Mm
宽度	30 Mm
深度	58 Mm
产品净重	0.02 Kg
设备安装	固定孔 - 直径: 22 mm 22.3 +0.4/0
安装孔距	- 厚度: 1...6 mm
固定模式	固定螺母 推荐扭矩: 2.4 N.m
接线能力	螺栓紧固, $\leq 1 \times 2.5 \text{ mm}^2$ 带箍线端子 螺栓紧固, $\leq 2 \times 1.5 \text{ mm}^2$ 不带箍线端子 螺栓紧固, $\geq 1 \times 0.5 \text{ mm}^2$ 快速接线端子, 连接型号: 6.3 mm
紧固扭矩	0.8...1.2 N.M 符合 EN 60947-1
螺丝头形状	交叉 兼容 Philips no 1 螺丝刀 交叉 兼容 pozidriv No 1 螺丝刀 一字槽 兼容 $\varnothing 4 \text{ mm}$ 螺丝刀 一字槽 兼容 $\varnothing 5.5 \text{ mm}$ 螺丝刀
额定绝缘电压 [Ui]	400 V (污染等级 3) 符合 EN/IEC 60947-1
额定冲击耐受电压 [Uimp]	6 KV 符合 EN/IEC 60947-1
信号类型	恒定
电源电压范围	0.8...1.1 V 直流
电流消耗	$\leq 20 \text{ mA}$
使用寿命	50000 小时 在25°C、额定电压时
浪涌耐受	1 KV 符合 IEC 61000-4-5
抗电磁域	10 V/M 符合 IEC 61000-4-3

抗静电放电	6 KV 接触(金属部件) 符合 IEC 61000-4-2 8 KV 自由空气中(绝缘部件里) 符合 IEC 61000-4-2
型号	XCE

环境

保护处理	TC/TH
贮存环境温度	-40...80 °C
运行温度	-25...70 °C
过电压种类	Class I 符合 IEC 60356
IP 保护等级	IP65 符合 IEC 60529
IK 保护等级	IK05 符合 IEC 50102
符合标准	GB 14048.5 IEC 60947-5-1 GB 14048.1 IEC 60947-1
产品认证	CCC CE
抗瞬时脉冲能力	2 KV 符合 IEC 61000-4-4
电磁辐射	等级 B 符合 IEC 55011

包装单位

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	15.5 G
Package 1 Height	3.0 Cm
Package 1 Width	3.0 Cm
Package 1 Length	5.8 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	100
Package 2 Weight	1.95 Kg
Package 2 Height	15.0 Cm
Package 2 Width	30.0 Cm
Package 2 Length	40.0 Cm
Unit Type of Package 3	PAL
Number of Units in Package 3	2000
Package 3 Weight	38.2 Kg
Package 3 Height	60.0 Cm
Package 3 Width	80.0 Cm
Package 3 Length	90.0 Cm

可持续性

产品类型	Green Premium 产品
REACH法规	REACH 声明
欧盟ROHS指令	主动合规性 (超出欧盟 RoHS 法定范围的产品) 欧盟ROHS声明
无汞	是
RoHS 豁免信息	是
中国 ROHS 管理办法	中国 ROHS 声明
环境披露	产品环境文件
流通资料	产品使用寿命终期信息

合同保修

保修单	18 个月
-----	-------

Product Life Status : **Commercialised**

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Industrial Panel Mount Indicators / Switch Indicators](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[LW1A-P1-GD](#) [LW1A-P1-W](#) [01-931.3](#) [01-152.025](#) [A0142N5](#) [APD106LN-G](#) [ATN2100](#) [HW1A-L1-GD](#) [HW1A-P2-GL](#) [HW1X-BM411-R](#)
[HW2A-L1-GL](#) [HWAZ1N-OB](#) [PAMR25](#) [LSPD-120A](#) [LSPD-1Y](#) [LSPD-6A](#) [LSPD-6DA](#) [LSPD-6DW](#) [LSPD-6DY](#) [LSPD-6R](#) [LSPD-6W](#)
[AL6H-LK3-A](#) [AL6M-LK1-MG](#) [AP8M155-G](#) [APN106L-O](#) [21-931.9](#) [CPSLED24](#) [AVLN3LD-R](#) [AYLW4L-G](#) [5000211OPAQUELENS](#)
[5.49227.0071301](#) [HW2A-L1-GD](#) [HW2A-P1-GL](#) [LAY-1](#) [LB6P-1T04A](#) [LB6P-1T04G](#) [LSPD-1A](#) [LSPD-1W](#) [LSPD-6DG](#) [LSPD-6DR](#) [LSPD-](#)
[6Y](#) [51-951.5](#) [10-2312.1062](#) [10-2312.1065](#) [10-2312.1069](#) [10-2313.1069](#) [10-4613.3102B](#) [10-4613.3104B](#) [10-5309.3202](#) [10-6412.3162](#)