Product data sheet Characteristics

XB5AD912R470K

head \tilde{A}^2 2 + mounting base + potentiometer 470K

Product availability: Stock - Normally stocked in distribution facility



Main	
Range of product	Harmony XB5
Product or component type	Complete potentiometer
Device short name	XB5
Head type	Standard

Complementary

Complementary	
Bezel material	Dark grey plastic
Mounting diameter	0.87 in (22 mm)
Product compatibility	Ø 6 mm shaft
Sale per indivisible quantity	1
CAD overall width	1.18 in (30 mm)
CAD overall height	1.65 in (42 mm)
CAD overall depth	3.23 in (82 mm)
Product weight	0.11 lb(US) (0.048 kg)
Protective treatment	ТН
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
Electrical shock protection class	Class II IEC 60536
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 13
	NEMA 4X
Resistance to high pressure washer	1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m
IK degree of protection	IK03 IEC 50102
Standards	CSA C22.2 No 14 EN/IEC 60947-1
	UL 508
Product certifications	UL listed
	CSA BV
Shape of signaling unit head	Round
Operator profile	Knurled knob with white
Us] rated supply voltage	<= 30 V AC
	<= 42 V DC
Rated power in W	0.26 W 70 °C
Precision of internal conversion resistor	+-10%
Potentiometer characteristic	Linear
Mechanical durability	50000 cycles
Ohmic value	470000 Ohm
Material	Cermet
Vibration resistance	5 gn 2500 Hz IEC 60068-2-6
Shock resistance	30 gn 18 ms half sine wave acceleration IEC 60068-2-27 50 gn 11 ms half sine wave acceleration IEC 60068-2-27



Main group	Potentiometer	
Group of product	Potentiometer knurled knob	
Colour of marking	White	
Compatibility code	XB5	

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW		
Discount Schedule	CS2		
GTIN	00785901536420		
Nbr. of units in pkg.	1		
Package weight(Lbs)	0.13		
Returnability	Y		
Country of origin	FR		


Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1636 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity Reference not containing SVHC above the threshold		
REACh			
California proposition 65	WARNING: This product can expose you to chemicals including:		
Substance 1	Lead and lead compounds, which is known to the State of California to cause ca cer and birth defects or other reproductive harm.		
More information	For more information go to www.p65warnings.ca.gov		

Product data sheet **Dimensions Drawings**

XB5AD912R470K

Dimensions




Panel thickness: 1 mm to 6 mm / 0.03 in. to 0.24 in. e:


XB5AD912R470K

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

Connection by Screw Terminals or Plug-in Connectors




Connection by Faston Connectors



Connections	a in mm	a in in.	b in mm	b in in.
By screw clamp terminals or plug-in connector	40	1.57	30	1.18
By Faston connectors	45	1.77	32	1.26

Detail of Lug Recess



- Diameter on finished panel or support (1)
- For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended. \emptyset 22.5 mm recommended (\emptyset 22.3 $_0$ ^{+0.4}) / \emptyset 0.89 in. recommended (\emptyset 0.88 in. $_0$ ^{+0.016}) (2)
- (3)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Potentiometers category:

Click to view products by Schneider manufacturer:

Other Similar products are found below :

58C2-2 590SX1N32F103SS 591SXJ48S252SC 591SXP56S252SC 591SXP56S503SC D31409 70B1G048K502X-A 70B1M032S502W 70B1N056S202W 70B8N056F502W 70J8N048S104U 70L1N040P103W 70L1N048P103X 70L1N048S103W GA2L040S102UC GA2L040S103UC GS1G044P103UA GS1N048P103UA GS1T032S103UA A43-1500 A43-20K A47-200K A4720K RA20LASD251A 132-2-0-202 132-0-0-202 RK14K1220-F25-C0-A103 RK14K1220F25C0C104 RK14K1220-F25-C1-B103 14910FAGJSX10102KA 14910FBGLFY00103KA 14910AABHSX10103KA 14910FAGJSX10104KA 152-01031 C0342008 5K P270-109A J97589 23M728 248BBHS0XB25104MA RV170F-10-15R1-B500K-0021 RV8NAYSB104A 917523A A43-40 A43-750 A438-5 A47-15K A4750K SPPG048S103U SPPG056P103U SWE-10