XCSL764F3

Interlock switch 300 VAC 10as XCSL





Main

| Device short name | XCSL |
|-------------------|--|
| Enclosure type | Water resistant enclosure indoor/outdoor Dustproof enclosure indoor/outdoor Ice/sleet proof enclosure indoor/outdoor |

Complementary

| Complementary | | |
|-------------------------------|--|--|
| Line Rated Current | 10 A | |
| [Us] rated supply voltage | 110 V AC | |
| Actuator | Key | |
| Contact operation | Slow-break, break before make | |
| Contacts type and composition | 1 NO staggered 2 NC | |
| Depth | 1.73 in (43.94 mm) | |
| Enclosure material | metal | |
| Height | 7.64 in (194.06 mm) | |
| Installation direction | Electromagnet connection left Actuator supply right | |
| Key locking position | Front | |
| Locking options description | With locking of actuator, unlocking by key operated lock | |
| Number of poles | 3 | |
| Permissible voltage | 300 V AC | |
| Pilot light | LED orange | |
| | | |

Environment

| Ambient Air Temperature for Operation | -13158 °F (-2570 °C) | |
|---------------------------------------|----------------------|--|
| IP Degree of Protection | IP67 | |
| NEMA Degree of Protection | NEMA 1/2/3/4/12 | |

Ordering and shipping details

| Category | 22411-LIMIT SWITCHES,IEC,XCKJ | |
|-----------------------|-------------------------------|--|
| Discount Schedule | Т | |
| GTIN | 3389118074385 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 34.57 oz (980.0 g) | |
| Returnability | Yes | |
| Country of origin | FR | |

Packing Units

| 3 | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 2.05 in (5.2 cm) |
| Package 1 width | 2.44 in (6.2 cm) |
| Package 1 Length | 11.02 in (28 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 22.61 lb(US) (10.255 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| RoHS exemption information | €Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Interlock Switches category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

1338606-1 HS1L-DQ44KMSRP-R HS5L-VF44M-G HS1T-VA44ZLM-G HS1T-VA44ZSM-G HS1T-VA7Y4ZM-G HS1T-VA7Y4ZSM-G HS1T-VA7Y4ZSM-G HS1T-VA7Y4ZSM-G HS1T-VA7Y4ZSM-G HS1T-VA7Y4ZSM-G HS1T-VA7Y4ZSM-G HS1T-VA7Y4ZSM-G HS1T-VA7Y4ZSM-G HS1L-DQ44KMSR-R 44540-0110 HS6B-02B03 HS1L-R44KMSRM-G HS1L-R44KMSRM-R HS5D-03RN HS5D-03ZRNM HS5L-DD44LM-G HS5L-DD44M-G HS5L-VA44M-G HS5L-VA44M-