


Preventa XPS Universal

Safety modules

Catalog

July 2019



Quick access to product information

Get technical information about your product

References

Telefast Pre-wired System
Modicon ABE9 IP 67 passive splitter boxes

References					
Splitter boxes with connection by M23 connector					
Number of channels	Connection by	LED indicator	Reference	Weight (kg)	
4	4 x M12 female connection	Yes	ABE912W1223	0.280	
6	6 x M12 female connection	Yes	ABE912W1226	0.370	
8	8 x M12 female connection	Yes	ABE912W1228	0.500	
12	12 x M12 female connection	Yes	ABE912W1236	0.750	
16	16 x M12 female connection	Yes	ABE912W1248	1.000	
Splitter boxes with connection by cable					
Number of channels	Connection by	Length (m)	LED indicator	Reference	Weight (kg)
4	4 x M12 female connectors	14.4	No	ABE912W1245	0.280
6	6 x M12 female connectors	14.4	No	ABE912W1246	0.400
8	8 x M12 female connectors	14.4	No	ABE912W1247	0.520
12	12 x M12 female connectors	14.4	No	ABE912W1248	0.750
16	16 x M12 female connectors	14.4	No	ABE912W1249	1.000

Schneider Electric

Add to favorites | Help | Historic

XB5AL73415
green flush/red projecting double-headed pushbutton Ø22 with marking

Download your XB5AL73415 datasheet

Change your selection

Discover other products & accessories

Discover your Schneider Electric tools

Characteristics | Dimensions Drawings | Mounting and Clearance | Documents & Downloads

Main

Range of product	Harmony XB5
Product or component type	Complete double-headed push-button
Device short name	XB5
Bezel material	Plastic
Fixing collar material	Plastic
Head type	Standard
Mounting diameter	22 mm
Shape of signaling unit head	Rectangular
Type of operator	Spring return
Operator profile	1 flush - 1 projecting push-buttons
Operators description	Green "I" - red "O"
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break

Each commercial reference presented in a catalog contains a hyperlink. Click on it to obtain the technical information of the product:

- Characteristics, Dimensions and drawings, Mounting and clearance, Connections and schemas, Performance curves
- Product image, Instruction sheet, User guide, Product certifications, End of life manual

Find your catalog



- > With just 3 clicks, you can reach the Industrial Automation and Control catalogs, in both English and French
- > Download Digi-Cat with this [link](#)

Search

General Catalog

Industrial Automation

360°

- Updated quarterly
- Embeds product selectors and configurators, 360° images, training centers
- Optimized search by commercial reference

Select your training



- > Find the right [Training](#) for your needs on our Global website
- > Locate the training center with the selector tool, using this [link](#)

Training and courses

Training by domain of expertise

Electrical Installation and Safety

Start Center

Industrial Automation


General content

Preventa XPS Universal

Safety modules

Selection guide	page 2
■ Type XPSUAB	
- Operating principles, selection.....	page 4
- Main features, references	page 5
■ Type XPSUAF	
- Operating principles.....	page 6
- Main features, references	page 6
■ Type XPSUAK	
- Operating principles.....	page 7
- Main features, references	page 7
■ Type XPSUAT	
- Operating principles.....	page 8
- Main features, references	page 8
■ Type XPSUDN	
- Operating principles.....	page 9
- Main features, references	page 9
■ Type XPSUS	
- Operating principles, selection.....	page 10
- Main features, references	page 11
■ Type XPSUEP	
- Operating principles.....	page 12
- Main features, references	page 12
■ Accessories for Preventa XPS Universal safety modules	page 13
■ Substitution table	page 14
■ Product reference index	page 15


Safety Functions



Safety modules for monitoring	<ul style="list-style-type: none"> - Emergency stop - Antivalent contacts - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain - Two-hand control stations 	<ul style="list-style-type: none"> - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain 	<ul style="list-style-type: none"> - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP & NPN sensor - RFID safety switch - Safety light curtain - Sensing mat/edges
--------------------------------------	--	--	---



Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL e/Category 1 conforming to ISO 13849-1 ■ SILCL 1 conforming to IEC 62061 ■ SIL 1 conforming to IEC 61508 	<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SILCL 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508 		
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard) 			
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV 			
Number of outputs	Safety	1 single changeover output	3 NO	2 NO + 1 NC
	Diagnostic	1 solid state	1 solid state	1 solid state
Display		6 LEDs	6 LEDs	6 LEDs
Supply voltage		24 V AC/DC and 48-240 V AC/DC		
Synchronization time between inputs		Selectable	Selectable	Selectable
Inputs channels	Number	2	2	2
Module type		XPSUAB	XPSUAF	XPSUAK
Page		4	6	7
Accessory type		XPSEC, XPSES	XPSEC, XPSES	XPSEC, XPSES
Page		13	13	13



<ul style="list-style-type: none"> - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP & NPN sensor - RFID safety switch - Safety light curtain - Sensing mat/edges 	<ul style="list-style-type: none"> - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain 	<ul style="list-style-type: none"> - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain - Two-hand control station - Enabling switch 	<ul style="list-style-type: none"> - For extending the number of safety contacts
---	--	---	---



<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SILCL 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508 	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard) 		
<ul style="list-style-type: none"> ■ cULus ■ TÜV 			
3 NO immediate + 3 NO configurable + 1 NC configurable	3 NO + 1 NC	2 NO	4 NO + 2 single NC
2 solid state	1 solid state	1 solid state	1 solid state
8 LEDs	16 LEDs	8 LEDs	3 LEDs
24 V AC/DC and 48-240 V AC/DC			
Selectable	Selectable	Selectable	-
3	12	4	-
XPSUAT	XPSUDN	XPSUS	XPSUEP
8	9	10	12
XPSEC, XPSES	XPSEC, XPSES	XPSEC, XPSES	XPSEC, XPSES
13	13	13	13

Preventa XPS Universal Safety modules

Type **XPSUAB**, for monitoring Emergency stop, Antivalent contacts, Guard switch, Magnetic switch, Proximity safety switch, PNP sensor, RFID safety switch, Safety light curtain or Two-hand control stations

Operating principle

XPSUAB safety modules are designed to monitor two hand control stations IIIA which must comply with International standard ISO 13851. The control stations must be designed and installed so that they cannot be activated involuntarily or easily rendered inoperative. Depending on the application, the requirements of type C standards specific to the machinery involved must be met (additional personal protection methods may have to be considered).

To initiate a dangerous movement, both operators (two-hand control pushbuttons) must be activated within an interval of 0.5 s (synchronous activation). If one of the two pushbuttons is released during a dangerous operation, the control sequence is cancelled. Resuming the dangerous operation is possible only if both pushbuttons are returned to their initial position and reactivated within the required time interval. The safety distance between the control units and the hazardous zone must be enough to ensure that when only one operator is released, the hazardous zone cannot be reached before the dangerous movement has been completed or stopped.


■ With automatic, manual & monitored start, **XPSUAB** safety modules are used for monitoring:

- A single contact Emergency stop conforming to standard ISO 13850
- Switches activated by protection devices conforming to standard ISO 14119:
 - Antivalent contacts pair
 - Mechanical guard switch
 - Magnetic switch with antivalent contacts
 - Proximity safety switch with antivalent contacts
 - PNP sensor
 - RFID safety switch

□ Type 4 light curtains conforming to IEC 61496-1 which have solid-state safety outputs with test function

■ With automatic start only, **XPSUAB** safety modules are used for monitoring two-hand control IIIA.

- These functions are selected and the start function can be configured by selector switches on the front face.
- A solid-state diagnostic output with complete status information facilitates maintenance.
- 6 LEDs on the front face provide information on the monitoring circuit status.



Selection

Requirements of standard ISO 13851		Type I	Type II	Type III		
				A	B	C
Standard ISO 13851 defines the selection of two-hand controls according to its behavior. This table details the 3 types of two-hand control conforming to ISO 13851. For each type, it lists the operating characteristics and minimum requirements.	Use of both hands (simultaneous action)					
	Link between input and output signals					
	Prevention of accidental operation					
	Tamper-proof					
	Output signal reinitialised					
	Synchronous action (specified time limit)					
	Use of proven components (Category 1 conforming to ISO 13849-1)			XPSUAB		
	Redundancy with partial error detection (Category 3 conforming to ISO 13849-1)				XPSUS	
	Redundancy + Self-monitoring (Category 4 conforming to ISO 13849-1)					XPSUS
	Two-hand control station	XY2SB●●	XY2SB●●	XY2SB●●	XY2SB●●	XY2SB●●

Conforming to ISO 13849-1

Conforming to ISO 13851

Preventa XPS Universal Safety modules

Type **XPSUAB**, for monitoring Emergency stop, Antivalent contacts, Guard switch, Magnetic switch, Proximity safety switch, PNP sensor, RFID safety switch, Safety light curtain or Two-hand control stations

Main features

Start input	Automatic, manual & monitored start
Safety input	1
Control outputs	2 ON/OFF configurable pulsed outputs
Safety outputs	1 single changeover output
Diagnostic outputs	1 solid state diagnostic output with complete status information
Connection type	Removable terminal blocks
Safe expansion connection	No
Module width	22.5 mm/0.886 in.
Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL c/Category 1 conforming to ISO 13849-1 ■ SILCL 1 conforming to IEC 62061 ■ SIL 1 conforming to IEC 61508
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard)

References

Description	Voltage	Terminals mm/in.	References	Weight kg/lb
Type XPSUAB for monitoring: - Emergency stop - Antivalent contacts - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain - Two-hand control stations	24 V ~/—	Spring 5.08/0.20	XPSUAB11CC	0.200/0.440
		Screw 5.08/0.20	XPSUAB11CP	0.200/0.440
	48-240 V ~/—	Spring 5.08/0.20	XPSUAB31CC	0.200/0.440
		Screw 5.08/0.20	XPSUAB31CP	0.200/0.440




XPSUAB11CC



XPSUAB11CP

Preventa XPS Universal Safety modules

Type **XPSUAF**, for monitoring Emergency stop, Guard switch, Magnetic switch, Proximity safety switch, PNP sensor, RFID safety switch or Safety light curtain



Operating principle

XPSUAF safety modules are used for providing protection for both the machine operator and the machine by immediately stopping the dangerous movement on receipt of a stop instruction from the operator or on detection of an issue in the safety circuit itself.

XPSUAF safety modules are used for monitoring:

- Emergency stop circuits conforming to standard ISO 13850
- Switches activated by protection devices conforming to standard ISO 14119:
 - Mechanical guard switches
 - Magnetic switch with antivalent or 2 NC contacts
 - Proximity safety switch with antivalent contacts
 - PNP sensor
 - RFID safety switch
- Type 4 light curtains conforming to IEC 61496-1 having solid-state safety outputs with test function
 - These functions are selected and the start function can be configured by selector switches on the front face.
 - A solid-state diagnostic output with complete status information facilitates maintenance.
 - To monitor a higher number of antivalent contacts using this safety module, the antivalent contacts can be connected with a NC in series and NO in parallel.
 - 6 LEDs on the front face provide information on the monitoring circuit status.

Main features

Start input	Automatic, manual & monitored start
Safety inputs	2
Control outputs	3 ON/OFF configurable pulsed outputs
Safety outputs	3 NO
Diagnostic outputs	1 solid state diagnostic output with complete status information
Connection type	Removable terminal blocks
Safe expansion connection	Yes
Terminals	16
Module width	22.5 mm/0.886 in.
Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SILC L 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard)

References

Description	Voltage	Terminals mm/in.	References	Weight kg/lb
Type XPSUAF for monitoring: - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain	24 V ~/∩	Spring 5.08/0.20	XPSUAF13AC	0.200/0.440
		Screw 5.08/0.20	XPSUAF13AP	0.200/0.440
	48-240 V ~/∩	Spring 5.08/0.20	XPSUAF33AC	0.200/0.440
		Screw 5.08/0.20	XPSUAF33AP	0.200/0.440



XPSUAF-3AC




XPSUAF-3AP

Operating principle, main features, references

Preventa XPS Universal Safety modules

Type **XPSUAK**, for monitoring Emergency stop, Guard switch, Magnetic switch, Proximity safety switch, PNP & NPN sensors, RFID safety switch, Safety light curtain or Sensing mat/edges



Operating principle

XPSUAK safety modules provide protection for both the machine operator and the machine by immediately stopping the dangerous movement on receipt of a stop instruction from the operator or on detection of an issue in the safety circuit itself.

XPSUAK safety modules are used for monitoring:

- Emergency stop circuits conforming to standard ISO 13850
 - Switches activated by protection devices conforming to standard ISO 14119:
 - Mechanical guard switches
 - Magnetic switch with antivalent or 2 NC contacts
 - Proximity safety switch with antivalent contacts
 - Sensor pair
 - 1 PNP + 1 NPN sensor
 - RFID safety switch
 - Type 4 light curtains conforming to IEC 61496-1 having solid-state safety outputs with test function
 - 4-wire sensing mats or edges conforming to ISO 13856
- These functions are selected and the start function can be configured by selector switches on the front face.
 - A solid-state diagnostic output with complete status information facilitates maintenance.
 - To monitor a higher number of antivalent contacts using this safety module, the antivalent contacts can be connected with a NC in series and NO in parallel.
 - 6 LEDs on the front face provide information on the monitoring circuit status.

Main features

Start input	Automatic, manual & monitored start
Safety inputs	2
Control outputs	3 ON/OFF configurable pulsed outputs
Safety outputs	2 NO + 1 NC
Diagnostic outputs	1 solid state diagnostic output with complete status information
Connection type	Removable terminal blocks
Safe expansion connection	Yes
Terminals	20
Module width	22.5 mm/0.886 in.
Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SIL C L 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard)

References

Description	Voltage	Terminals mm/in.	References	Weight kg/lb
Type XPSUAK for monitoring: - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch	24 V ~/∞	Spring 5.08/0.20	XPSUAK12AC	0.200/0.440
		Screw 5.08/0.20	XPSUAK12AP	0.200/0.440
- PNP & NPN sensor - RFID safety switch - Safety light curtain - Sensing mat/edges	48-240 V ~/∞	Spring 5.08/0.20	XPSUAK32AC	0.200/0.440
		Screw 5.08/0.20	XPSUAK32AP	0.200/0.440




XPSUAK•2AC



XPSUAK•2AP

Preventa XPS Universal Safety modules

Type **XPSUAT**, for monitoring Emergency stop, Guard switch, Magnetic switch, Proximity safety switch, PNP & NPN sensor, RFID safety switch, Safety light curtain or Sensing mat/edges



Operating principle

XPSUAT safety modules provide protection for both the operator and the machine by immediately stopping the dangerous movement on receipt of a stop instruction from the operator, or on detection of an issue in the safety circuit itself.

XPSUAT safety modules are used for monitoring:

- Emergency stop circuits conforming to standard ISO 13850
- Switches activated by protection devices conforming to standard ISO 14119:
 - Mechanical guard switches
 - Magnetic switch with antivalent or 2 NC contacts
 - Proximity safety switch with antivalent contacts
 - PNP Sensor
 - 1 PNP + 1 NPN Sensor
 - RFID safety switch
- Type 4 light curtains conforming to IEC 61496-1 having solid-state safety outputs with test function
- 4-wire sensing mats or edges conforming to ISO 13856
- In addition to the stop category 0 instantaneous opening safety outputs, the **XPSUAT** safety modules incorporate stop category 1 time delay outputs which allow controlled deceleration of the motor to a complete stop (for example, motor braking by variable speed drive). At the end of the preset delay, the supply is disconnected by opening the time delayed output circuits. Also the time delay from 0.1 s to 15 min can be selected by selector switches on the front face.

- These functions are selected and the start function can be configured by selector switches on the front face.
- A solid-state diagnostic output with complete status information facilitates maintenance.
- To monitor a higher number of antivalent contacts using this safety module, the antivalent contacts can be connected with a NC in series and NO in parallel.
- 8 LEDs on the front face provide information on the monitoring circuit status.

Main features

Start input	Automatic, manual & monitored start
Safety inputs	2 positive safety inputs 24 VDC, 1 negative safety input
Control outputs	4 ON/OFF configurable pulsed outputs
Safety outputs	3 NO immediate + 3 NO configurable + 1 NC configurable
Diagnostic outputs	<ul style="list-style-type: none"> ■ 1 solid state diagnostic output for time delay ending ■ 1 solid state diagnostic output with complete status information
Connection type	Removable terminal blocks
Safe expansion connection	Yes
Terminals	27
Module width	45 mm/1.77 in.
Time delay setting	0.1 s to 15 min by 10 steps of 0.1 s which can be multiplied by 1, 10, 100 and 1000
Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SILCL 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard)

References

Description	Voltage	Terminals mm/in.	References	Weight kg/lb
Type XPSUAT for monitoring	24 V ~/∞	Spring 5.08/0.20	XPSUAT13A3AC	0.350/0.770
		Screw 5.08/0.20	XPSUAT13A3AP	0.350/0.770
- Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP & NPN sensor - RFID safety switch - Safety light curtain - Sensing mat/edges	48-240 V ~/∞	Spring 5.08/0.20	XPSUAT33A3AC	0.350/0.770
		Screw 5.08/0.20	XPSUAT33A3AP	0.350/0.770



XPSUAT3A3AC




XPSUAT3A3AP

Operating principle, main features, references

Preventa XPS Universal Safety modules

Type **XPSUDN**, for monitoring Emergency stop, Guard switch, Magnetic switch, Proximity safety switch, PNP sensor, RFID safety switch or safety light curtain



Operating principle

XPSUDN safety modules are used for monitoring:

- Emergency stop circuits conforming to standard ISO 13850
- Switches activated by protection devices conforming to standard ISO 14119:
 - Mechanical guard switches
 - Magnetic switch with antivalent or 2 NC contacts
 - Proximity safety switch with antivalent contacts
 - PNP Sensor
 - RFID safety switch
- Type 4 light curtains conforming to IEC 61496-1 having solid-state safety outputs with test function

- These functions are selected and the start function can be configured by selector switches on the front face.
- A solid-state diagnostic output with complete status information facilitates maintenance.
- To monitor a higher number of antivalent contacts using this safety module, the antivalent contacts can be connected with a NC in series and NO in parallel.
- 16 LEDs on the front face provide information on the monitoring circuit status.

Main features

Start input	Automatic, manual & monitored start
Safety inputs	6
Control outputs	7 ON/OFF configurable pulsed outputs
Safety outputs	3 NO + 1 NC
Diagnostic outputs	1 solid-state diagnostic output with complete status information
Connection type	Removable terminal blocks
Safe expansion connection	Yes
Terminals	32
Module width	45 mm / 1.77 in.
Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SILCL 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard)

References

Description	Voltage	Terminals mm/in.	References	Weight kg/lb
Type XPSUDN for monitoring	24 V ~/∞	Spring	XPSUDN13AC	0.350/0.770
		Screw	XPSUDN13AP	0.350/0.770
<ul style="list-style-type: none"> - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain 	48-240 V ~/∞	Spring	XPSUDN33AC	0.350/0.770
		Screw	XPSUDN33AP	0.350/0.770



XPSUDN3AC



XPSUDN3AP

Preventa XPS Universal

Safety modules

Type XPSUS, for monitoring Emergency stop, Guard switch, Magnetic switch, Proximity safety switch, PNP sensor, RFID safety switch, Safety light curtain, Two-hand control station or Enabling switch

Operating principle

XPSUS safety modules are designed to monitor two hand control stations IIIA or IIIC which must comply with International standard ISO 13851. The control stations must be designed and installed so that they cannot be activated involuntarily or easily rendered inoperative. Depending on the application, the requirements of type C standards specific to the machinery involved must be met (additional personal protection methods may have to be considered).

To initiate a dangerous movement, both operators (two-hand control pushbuttons) must be activated within an interval of 0.5 s (synchronous activation). If one of the two pushbuttons is released during a dangerous operation, the control sequence is cancelled. Resuming the dangerous operation is possible only if both pushbuttons are returned to their initial position and reactivated within the required time interval. The safety distance between the control units and the hazardous zone must be enough to ensure that when only one operator is released, the hazardous zone cannot be reached before the dangerous movement has been completed or stopped.


■ With automatic, manual & monitored start, **XPSUS** safety modules are used for monitoring:

- 2 Emergency stop circuits conforming to standard ISO 13850
- Switches activated by protection devices conforming to standard ISO 14119:
 - 2 mechanical guard switches
 - 2 magnetic switches with antivalent or 2 NC contacts
 - 2 proximity safety switches with antivalent contacts
 - 2 independent PNP sensors
 - 2 RFID safety switches

□ Type 4 light curtains conforming to IEC 61496-1 having solid-state safety outputs with test function

■ With automatic start only, **XPSUS** safety modules are used for monitoring one two-hand control IIIA, IIIC or enabling switch.

- These functions are selected and the start function can be configured by selector switches on the front face.
- A solid-state diagnostic output with complete status information facilitates maintenance.
- To monitor a higher number of antivalent contacts using these safety modules, the antivalent contacts can be connected with a NC in series and NO in parallel.
- 8 LEDs on the front face provide information on the monitoring circuit status.



Selection

Requirements of standard ISO 13851		Type I	Type II	Type III		
				A	B	C
Standard ISO 13851 defines the selection of two-hand controls according to its behavior. This table details the 3 types of two-hand control conforming to ISO 13851. For each type, it lists the operating characteristics and minimum requirements.	Use of both hands (simultaneous action)					
	Link between input and output signals					
	Prevention of accidental operation					
	Tamper-proof					
	Output signal reinitialised					
	Synchronous action (specified time limit)					
	Use of proven components (Category 1 conforming to ISO 13849-1)			XPSUAB		
	Redundancy with partial error detection (Category 3 conforming to ISO 13849-1)				XPSUS	
	Redundancy + Self-monitoring (Category 4 conforming to ISO 13849-1)					XPSUS
	Two-hand control station	XY2SB●●	XY2SB●●	XY2SB●●	XY2SB●●	XY2SB●●

Conforming to ISO 13849-1

Conforming to ISO 13851

Preventa XPS Universal Safety modules

Type **XPSUS**, for monitoring Emergency stop, Guard switch, Magnetic switch, Proximity safety switch, PNP sensor, RFID safety switch, Safety light curtain, Two-hand control station or Enabling switch

Main features

Start input	Automatic, manual & monitored start
Safety inputs	2
Control outputs	3 ON/OFF configurable pulsed outputs
Safety outputs	2 NO
Diagnostic outputs	1 solid-state diagnostic output with complete status information
Connection type	Removable terminal blocks
Safe expansion connection	Yes
Terminals	16
Module width	22.5 mm/0.886 in.
Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SILCL 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard)

References

Description	Voltage	Terminals mm/in.	References	Weight kg/lb
Type XPSUS for monitoring: - Emergency stop - Guard switch - Magnetic switch - Proximity safety switch - PNP sensor - RFID safety switch - Safety light curtain - Two-hand control station - Enabling switch	24 V ~/∞	Spring 5.08/0.20	XPSUS12AC	0.200/0.440
		Screw 5.08/0.20	XPSUS12AP	0.200/0.440
	48-240 V ~/∞	Spring 5.08/0.20	XPSUS32AC	0.200/0.440
		Screw 5.08/0.20	XPSUS32AP	0.200/0.440




XPSUS•2AC



XPSUS•2AP

Preventa XPS Universal Safety modules

Type **XPSUEP**, for extending the number of safety contacts



Operating principle

XPSUEP safety modules are used for extending the number of safety output contacts of XPS Universal safety modules.

They are available as additions to base modules (Emergency stop, limit switch, two-hand control, etc.). When **XPSUAT** is the base module, its configuration is used to choose whether the XPSUEP's outputs follow XPSUAT's immediate or time delayed outputs.

- 3 LEDs on the front face provide information on the monitoring circuit status.

Main features

Start input	Follows the host module
Safety inputs	0, Extension bus
Safety outputs	4 NO + 2 single NC
Connection	Connection to base module by connector
Diagnostic outputs	1 solid-state diagnostic output with complete status information
Connection type	Removable terminal blocks
Terminals	16
Module width	22.5 mm/0.886 in.
Maximum achievable safety level	<ul style="list-style-type: none"> ■ PL e/Category 4 conforming to ISO 13849-1 ■ SILCL 3 conforming to IEC 62061 ■ SIL 3 conforming to IEC 61508
Product certifications	<ul style="list-style-type: none"> ■ cULus ■ TÜV
Conformity to standards	<ul style="list-style-type: none"> ■ IEC 60947-5-1 ■ IEC 61508-1 (functional safety standard) ■ IEC 61508-2 (functional safety standard) ■ IEC 61508-3 (functional safety standard) ■ ISO 13849-1 (functional safety standard) ■ IEC 62061 (functional safety standard)

References

Description	Voltage	Terminals mm/in.	References	Weight kg/lb
Type XPSUEP For extending the number of safety contacts	24 V ~/∞	Spring 5.08/0.20	XPSUEP14AC	0.200/0.440
		Screw 5.08/0.20	XPSUEP14AP	0.200/0.440
	48-240 V ~/∞	Spring 5.08/0.20	XPSUEP34AC	0.200/0.440
		Screw 5.08/0.20	XPSUEP34AP	0.200/0.440



XPSUEP-4AC



XPSUEP-4AP



XPSEC

Presentation

XPSEC is a set of plastic coding elements for terminal blocks

References

Description	Use for	Unit reference	Weight kg/lb
Terminal block coding bit	For coding the terminal block	XPSEC Sold in lot of 30	0.010/ 0.020

Presentation

XPSES is a set of uniquely numbered sealing strips used to seal the transparent front cover flap of any XPS Universal module to prevent operator or maintenance to change the configuration.



XPSES

References

Description	Use for	Unit reference	Weight kg/lb
Sealing strips	Preventa XPS Universal safety modules	XPSES Sold in lot of 10	0.030/ 0.066

Preventa XPS Universal

Safety modules

Substitution table

XPS Safety modules (end of commercialization)			XPS Universal safety modules (new)				
Reference	Quantity	Group	Reference	Quantity	Group	Comment	Additional comment
XPSAF5130	1	-	XPSUAF13AP	1	-	Direct replacement	-
XPSAF5130P	1	-	XPSUAF13AP	1	-	Direct replacement	-
XPSAFL5130	1	-	XPSUAF13AP	1	-	Direct replacement	-
XPSAFL5130P	1	-	XPSUAF13AP	1	-	Direct replacement	-
XPSAK311144	1	-	XPSUAK12AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK311144P	1	-	XPSUAK12AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK331144P	1	-	XPSUAK32AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK351144	1	-	XPSUAK32AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK351144P	1	-	XPSUAK32AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK361144	1	-	XPSUAK32AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK361144P	1	-	XPSUAK32AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK371144	1	-	XPSUAK32AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAK371144P	1	-	XPSUAK32AP	1	-	Direct replacement	XPSUAK have 1 NO less than XPSAK
XPSAR311144	1	Global group 1	XPSUAT13A3AP	1	1	OR	If max. 6 NO are used
XPSAR311144	1	Global group 1	XPSUAF13AP	1	1	AND	If all 7 NO are used
XPSAR311144	1	Global group 1	XPSUEP14AP	1	1		
XPSAR311144P	1	Global group 2	XPSUAT13A3AP	1	2	OR	If max. 6 NO are used
XPSAR311144P	1	Global group 2	XPSUAF13AP	1	2	AND	If all 7 NO are used
XPSAR311144P	1	Global group 2	XPSUEP14AP	1	2		
XPSAR351144	1	Global group 3	XPSUAT33A3AP	1	3	OR	If max. 6 NO are used
XPSAR351144	1	Global group 3	XPSUAF33AP	1	3	AND	If all 7 NO are used
XPSAR351144	1	Global group 3	XPSUEP14AP	1	3		
XPSAR351144P	1	Global group 4	XPSUAT33A3AP	1	4	OR	If max. 6 NO are used
XPSAR351144P	1	Global group 4	XPSUAF33AP	1	4	AND	If all 7 NO are used
XPSAR351144P	1	Global group 4	XPSUEP14AP	1	4		
XPSAR371144	1	Global group 5	XPSUAT33A3AP	1	5	OR	If max. 6 NO are used
XPSAR371144	1	Global group 5	XPSUAF33AP	1	5	AND	If all 7 NO are used
XPSAR371144	1	Global group 5	XPSUEP14AP	1	5		
XPSAR371144P	1	Global group 6	XPSUAT33A3AP	1	6	OR	If max. 6 NO are used
XPSAR371144P	1	Global group 6	XPSUAF33AP	1	6	AND	If all 7 NO are used
XPSAR371144P	1	Global group 6	XPSUEP14AP	1	6		
XPSATE3410	1	-	XPSUAT33A3AP	1	-	Direct replacement	-
XPSATE3410P	1	-	XPSUAT33A3AP	1	-	Direct replacement	-
XPSATE3710	1	-	XPSUAT33A3AP	1	-	Direct replacement	-
XPSATE3710P	1	-	XPSUAT33A3AP	1	-	Direct replacement	-
XPSATE5110	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSATE5110P	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSATR11530C	1	-	XPSUAT13A3AC	1	-	Direct replacement	-
XPSATR11530P	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSATR1153C	1	-	XPSUAT13A3AC	1	-	Direct replacement	-
XPSATR1153P	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSATR39530C	1	-	XPSUAT33A3AC	1	-	Direct replacement	-
XPSATR39530P	1	-	XPSUAT33A3AP	1	-	Direct replacement	-
XPSATR3953C	1	-	XPSUAT33A3AC	1	-	Direct replacement	-
XPSATR3953P	1	-	XPSUAT33A3AP	1	-	Direct replacement	-
XPSAV11113	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSAV11113P	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSAV11113T050	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSAV11113Z002	1	-	XPSUAT13A3AP	1	-	Direct replacement	-
XPSBAE3920C	1	-	XPSUAB31CC	1	-	Direct replacement	-
XPSBAE3920P	1	-	XPSUAB31CP	1	-	Direct replacement	-
XPSBAE5120C	1	-	XPSUAB11CC	1	-	Direct replacement	-
XPSBAE5120P	1	-	XPSUAB11CP	1	-	Direct replacement	-
XPSBCE3110C	1	-	XPSUS12AC	1	-	Direct replacement	-
XPSBCE3110P	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSBCE3410C	1	-	XPSUS32AC	1	-	Direct replacement	-
XPSBCE3410P	1	-	XPSUS32AP	1	-	Direct replacement	-
XPSBCE3710C	1	-	XPSUS32AC	1	-	Direct replacement	-
XPSBCE3710P	1	-	XPSUS32AP	1	-	Direct replacement	-
XPSBF1132	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSBF1132P	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSDMB1132	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSDMB1132P	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSDME1132	1	-	XPSUDN13AP	1	-	Direct replacement	-
XPSDME1132P	1	-	XPSUDN13AP	1	-	Direct replacement	-
XPSDME1132TS220	1	-	XPSUDN13AP	1	-	Direct replacement	-
XPSECM5120C	1	-	XPSUEP14AC	1	-	Indirect replacement	Only in combination with XPSU host
XPSECM5120P	1	-	XPSUEP14AP	1	-	Indirect replacement	Only in combination with XPSU host
XPSECM5131C	1	-	XPSUEP14AC	1	-	Indirect replacement	Only in combination with XPSU host
XPSECM5131P	1	-	XPSUEP14AP	1	-	Indirect replacement	Only in combination with XPSU host
XPSFB3411	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSFB3711	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSFB5111	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSVC1132	1	-	XPSUS12AP	1	-	Direct replacement	-
XPSVC1132P	1	-	XPSUS12AP	1	-	Direct replacement	-

X	
XPSUAB11CC	5
XPSUAB11CP	5
XPSUAB31CC	5
XPSUAB31CP	5
XPSUAF13AC	6
XPSUAF13AP	6
XPSUAF33AC	6
XPSUAF33AP	6
XPSUAK12AC	7
XPSUAK12AP	7
XPSUAK32AC	7
XPSUAK32AP	7
XPSUAT13A3AC	8
XPSUAT13A3AP	8
XPSUAT33A3AC	8
XPSUAT33A3AP	8
XPSUDN13AC	9
XPSUDN13AP	9
XPSUDN33AC	9
XPSUDN33AP	9
XPSUS12AC	11
XPSUS12AP	11
XPSUS32AC	11
XPSUS32AP	11
XPSUEP14AC	12
XPSUEP14AP	12
XPSUEP34AC	12
XPSUEP34AP	12
XPSEC	13
XPSES	13



<http://www.schneider-electric.com/machinesafety>

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier
F-92500 Rueil-Malmaison
France

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Modules](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[70L-OAC-L](#) [G34960002700](#) [G88104401](#) [IDC-5B](#) [OACU](#) [C4SWOUT](#) [FC6A-T32K3](#) [SNAP-OAC5MA](#) [FC6A-N16B3](#) [FC6A-N32B3](#) [FC6A-T16P3](#) [PB32HQ](#) [PB16T](#) [PB8](#) [PB8H](#) [C200H-OD211](#) [GT1-AD04CST](#) [GT1-DA04](#) [70GRCQ24-HS](#) [M-OAC5](#) [G4OAC24AMA](#) [6202](#) [6402](#)
[IL MOD BK DI8 DO4-PAC](#) [FC6A-J2C1](#) [FC6A-KC1C](#) [FC6A-N08A11](#) [FC6A-M24BR1](#) [FC6A-K4A1](#) [FC6A-T32P3](#) [9-1393028-2](#)
[GP32900003700](#) [641-480-5022](#) [PB16H](#) [WISE-4050/LAN-B](#) [WISE-S614T-A](#) [ADAM-4068-C](#) [56475](#) [ADAM-4017+-F](#) [ADAM-4118-C](#)
[WISE-4050-B](#) [ADAM-4051-C](#) [ADAM-4053-F](#) [GT1-AD08MX](#) [TM5SDO6TBFS](#) [70Q3446](#) [TM3BCCO](#) [ADAM-4069-B](#) [2512840000](#)
[6ES71346JD000CA1](#)