Product data sheet Characteristics

XVC4B4K

40mm Tower ROGB Base Mount



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range of product	Harmony XVC4
Product or component type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	4 illuminated units
Sound signalling	Without
Mounting diameter	1.57 in (40 mm)
Device short name	XVC
Component name	XVC
Light source	Blue LED steady Green LED steady Orange LED steady Red LED steady
Supply circuit type	AC/DC

Complementary

Material	Polycarbonate (illuminated unit) ABS (acrylonitrile butadiene-styrene) (base unit)
	PBT + ABS (UL94HB) (top cover)
Mounting location	On base
Product mounting	On base
[Us] rated supply voltage	24 V
[Us] rated supply voltage	24 V
Cable cross section	0 in² (0.33 mm²)
AWG gauge	AWG 22
Cable length	19.69 in (500 mm)
Marking	CE
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	100 mA
Flashing frequency	1 Hz
Product weight	0.35 lb(US) (0.16 kg)
Height	8.09 in (205.5 mm)

Environment

EN/IEC 61000-6-2 EN/IEC 61000-6-3	
UL	
TC	
-31158 °F (-3570 °C)	
14122 °F (-1050 °C)	
Class II conforming to EN/IEC 61140	
Class II EN/IEC 61140	
IP54 in flat surface installation conforming to EN/IEC 60529	
	EN/IEC 61000-6-3 UL TC -31158 °F (-3570 °C) 14122 °F (-1050 °C) Class II conforming to EN/IEC 61140 Class II EN/IEC 61140

Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	00785901558071
Nbr. of units in pkg.	1
Package weight(Lbs)	0.70999999999999
Returnability	N
Country of origin	ID

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0808 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	


Contractual warranty


Warranty period	18 months	

Pre-assembled and Pre-wired Tower Light

Dimensions

Below drawing shows the maximum configuration of the product. Select the number of stages according to the product characteristics in order to get b dimension.






No. of illuminated units	b Without buzzer (mm)	b Without buzzer (in)
1 stage	100.50	3.96
2 stages	135.50	5.33
3 stages	170.50	6.71
4 stages	205.50	8.09
5 stages	240.50	9.47

Product data sheet Mounting and Clearance

XVC4B4K

Pre-assembled and Pre-wired Tower Light

Direct Mounting on Horizontal Support Panel cut-out



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Lighting Fixtures category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

1301080067 XVEC21P XVEC2B7 2576960000 113163000-00662717 113472000-00691461 XVBC2B3 XVBC2B7 XVBC4B4 XVBC4B5 XVBC4B6 XVBC4B4 XVBC4M5 XVBC4M8 XVBZ01 XVBZ03A XVBZ04 E35600 NB-RLAMP01-LED FLK7LED XVBZ04A XVBC4M7 XVBC4M6 XVBC4B3 XVBC2B8 2700127 2702933 2702477 2403122 2403121 2402991 89406068 148-00076 113261000-00641180 190007019-00014904 226108019-00610754 4823 4824 4868 112887037-00076065 113021000-00564565 113473000-00704968 NB-RLAMP01 112577000-00539774 113458000-00668976 E35500 408001403-00671626 SL7/4-FW LML-6TER-CAB