XVLA143

LED pilot light with black bezel, Harmony XVL, Ø 8, IP40, green, protruding included, 48 V, faston





Main

Range of product	Harmony XVL
Product or Component Type	LED pilot light with black bezel
Component name	XVL
Mounting diameter	0.31 in (8 mm)
Light source	Protruding LED
Light block colour	Green
Protection Type	Built-in by diode Integral ballast resistor
[Us] rated supply voltage	48 V
IP degree of protection	IP40 IEC 60529 IP40 NF C 20-010

Complementary

Supply circuit type	DC		
Connections - terminals	Tag for Faston connectors 2.8 x 0.5 mm Tag for soldering connectors		
Current Consumption	10 mA		
[Ui] rated insulation voltage	50 V IEC 60947-1		
Bulb lifespan	100000 h		
Nominal voltage limit	0.81.1 Un		
Terminals description ISO n°1	(X1-X2)PL		
Height	0.47 in (12 mm)		
Width	0.47 in (12 mm)		
Depth	1.34 in (34 mm)		
Product Weight	0.01 lb(US) (0.003 kg)		

Environment

LIMIONNER		
Product Certifications	CSA UL	
Protective treatment	TC	
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Overvoltage category	Class 3 IEC 60536 Class 3 NF C 20-030	

Ordering and shipping details

Category	22460 - PUSHBUTTONS 22MM (PLASTIC)			
Discount Schedule	CS2			
GTIN	3389110651126			
Nbr. of units in pkg.	1			
Package weight(Lbs)	0.07 oz (2 g)			
Returnability	No			
Country of origin	FR			

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	0.63 in (1.6 cm)	
Package 1 width	1.61 in (4.1 cm)	
Package 1 Length	2.56 in (6.5 cm)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Weight	1.09 oz (31 g)	
Package 2 Height	1.18 in (3 cm)	
Package 2 width	3.94 in (10 cm)	
Package 2 Length	5.12 in (13 cm)	
Unit Type of Package 3	S01	
Number of Units in Package 3	100	
Package 3 Weight	18.45 oz (523 g)	
Package 3 Height	5.91 in (15 cm)	
Package 3 width	5.91 in (15 cm)	
Package 3 Length	15.75 in (40 cm)	

Offer Sustainability

Green Premium product		
WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
☑ REACh Declaration		
Yes		
Pro-active compliance (Product out of EU RoHS legal scope) [☑] EU RoHS Declaration		
Yes		
₽		
China RoHS Declaration		
Product Environmental Profile		
The product must be disposed on European Union markets following sp waste collection and never end up in rubbish bins.		

Contractual warranty


Warranty	18 months
vvarianty	10 monars

Product data sheet Dimensions Drawings

XVLA143

LED Pilot Light

Dimensions



(1) Tags for Faston connectors or soldered connections

e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

С		Ø	
mm	in.	mm	in.
32	1.26	12	0.47

Product data sheet Mounting and Clearance

XVLA143

LED Pilot Light

Panel Drilling



Ø min		G min		H min	
mm	in.	mm	in.	mm	in.
8.2	0.32	12.5	0.49	12.5	0.49

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

LW1A-P1-GD LW1A-P1-W 01-931.3 01-152.025 73.362.4028.0 750-1520 9001OA120 A0142N5 A3DT-500Y AL6M-LK3-R AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-G APD106LN-S APN1126-G APS122DN-W ASLWLD-G ASLWLD-R ATN2100 AYLW4L-A 18-237.035 18-945 HW1A-L1-GD HW1A-P2-GL HW1X-BM411-R HW2A-L1-GL HWAZ1N-OB PA2100/2 PA2200/1 PA2SHIELD PAMR25 LA3P-1C03V-Y 96-923.5 A0244J2 LSPD-120A LSPD-1Y LSPD-6A LSPD-6DA LSPD-6DW LSPD-6DY LSPD-6R LSPD-6W 18-946 AL6H-LK3-A AL6H-P4-JW AL6M-LK1-MG AP8M155-G APD106LN-W APN106L-O