



Main

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------------|
| Range of Product | Harmony XVL |
| Product or Component Type | LED pilot light with integral lens cap |
| Component name | XVL |
| Mounting diameter | 0.31 in (8 mm) |
| Light source | Covered LED |
| Light block colour | Yellow |
| Protection Type | Built-in by diode Integral ballast resistor |
| [Us] rated supply voltage | 24 V |
| IP degree of protection | IP65 IEC 60529 with seal XVLZ911) IP65 NF C 20-010 with seal XVLZ911) IP40 IEC 60529 IP40 NF C 20-010 |

Complementary

| | |
|-------------------------------|------------------------------------------------------------------------|
| Supply circuit type | DC |
| Connections - terminals | Tag for Faston connectors 2.8 x 0.5 mm Tag for soldering connectors |
| Current Consumption | 18 mA |
| [Ui] rated insulation voltage | 50 V IEC 60947-1 |
| Bulb lifespan | 100000 h |
| Nominal voltage limit | 0.8...1.1 Un |
| Terminals description ISO n°1 | (X1-X2)PL |
| Height | 0.39 in (10 mm) |
| Width | 0.39 in (10 mm) |
| Depth | 1.42 in (36 mm) |
| Net Weight | 0.01 lb(US) (0.003 kg) |

Environment

| | |
|---------------------------------------|------------------------------------------|
| Product Certifications | CSA UL |
| Protective treatment | TC |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Overvoltage category | Class 3 IEC 60536 Class 3 NF C 20-030 |

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 22460 - PUSHBUTTONS 22MM (PLASTIC) |
| Discount Schedule | CS2 |
| GTIN | 3389110651409 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.11 oz (3 g) |
| Returnability | Yes |
| Country of origin | ES |

Packing Units

| | |
|------------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 0.39 in (1 cm) |
| Package 1 width | 0.39 in (1 cm) |
| Package 1 Length | 1.65 in (4.2 cm) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 1.20 oz (34 g) |
| Package 2 Height | 1.18 in (3 cm) |
| Package 2 width | 5.12 in (13 cm) |
| Package 2 Length | 5.51 in (14 cm) |
| Unit Type of Package 3 | S01 |
| Number of Units in Package 3 | 100 |
| Package 3 Weight | 17.07 oz (484 g) |
| Package 3 Height | 5.91 in (15 cm) |
| Package 3 width | 5.91 in (15 cm) |
| Package 3 Length | 15.75 in (40 cm) |

Offer Sustainability


| | |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

LED Pilot Light

Dimensions



- (1) Tags for Faston connectors or soldered connections
e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

| C | | Ø | | |
|----|------|----|------|-----|
| mm | in. | mm | in. | in. |
| 34 | 1.34 | 10 | 0.39 | |

LED Pilot Light

Panel Drilling



| Ø min | | G min | | H min | |
|-------|------|-------|------|-------|------|
| mm | in. | mm | in. | mm | in. |
| 8.2 | 0.32 | 10.5 | 0.41 | 10.5 | 0.41 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Industrial Panel Mount Indicators / Switch Indicators](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[LW1A-P1-GD](#) [LW1A-P1-W](#) [01-931.3](#) [01-152.025](#) [73.362.4028.0](#) [750-1520](#) [9001OA120](#) [A0142N5](#) [A3DT-500Y](#) [AL6M-LK3-R](#) [AL6M-P7P-A](#) [AOLQW-2B0600](#) [AP1M255-A](#) [APD106LN-G](#) [APD106LN-S](#) [APN1126-G](#) [APS122DN-W](#) [ASLWLD-G](#) [ASLWLD-R](#) [ATN2100](#) [AYLW4L-A](#) [18-237.035](#) [18-945](#) [HW1A-L1-GD](#) [HW1A-P2-GL](#) [HW1X-BM411-R](#) [HW2A-L1-GL](#) [HWAZ1N-OB](#) [PA2100/2](#) [PA2200/1](#) [PA2SHIELD](#) [PAMR25](#) [LA3P-1C03V-Y](#) [96-923.5](#) [A0244J2](#) [LSPD-120A](#) [LSPD-1Y](#) [LSPD-6A](#) [LSPD-6DA](#) [LSPD-6DW](#) [LSPD-6DY](#) [LSPD-6R](#) [LSPD-6W](#) [18-946](#) [AL6H-LK3-A](#) [AL6H-P4-JW](#) [AL6M-LK1-MG](#) [AP8M155-G](#) [APD106LN-W](#) [APN106L-O](#)