



## Main

|                           |                                                                                                                |
|---------------------------|----------------------------------------------------------------------------------------------------------------|
| Range of Product          | Harmony XVL                                                                                                    |
| Product or Component Type | LED pilot light with integral lens cap                                                                         |
| Component name            | XVL                                                                                                            |
| Mounting diameter         | 0.47 in (12 mm)                                                                                                |
| Light source              | Covered LED                                                                                                    |
| Light block colour        | Yellow                                                                                                         |
| Protection Type           | Integral ballast resistor<br>Built-in by diode                                                                 |
| [Us] rated supply voltage | 24 V                                                                                                           |
| IP degree of protection   | IP65 IEC 60529 with seal XVLZ912)<br>IP65 NF C 20-010 with seal XVLZ912)<br>IP40 IEC 60529<br>IP40 NF C 20-010 |

## Complementary

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| Supply circuit type           | DC                                                   |
| Connections - terminals       | Threaded connector 1 x 0.2...1 x 1.5 mm <sup>2</sup> |
| Current Consumption           | 18 mA                                                |
| [Ui] rated insulation voltage | 50 V IEC 60947-1                                     |
| Bulb lifespan                 | 100000 h                                             |
| Nominal voltage limit         | 0.8...1.1 Un                                         |
| Terminals description ISO n°1 | (X1-X2)PL                                            |
| Height                        | 0.63 in (16 mm)                                      |
| Width                         | 0.63 in (16 mm)                                      |
| Depth                         | 2.01 in (51 mm)                                      |
| Net Weight                    | 0.02 lb(US) (0.007 kg)                               |

## Environment

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Product Certifications                | CSA<br>UL                                |
| Protective treatment                  | TC                                       |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)               |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)               |
| Overvoltage category                  | Class 3 IEC 60536<br>Class 3 NF C 20-030 |

## Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22460 - PUSHBUTTONS 22MM (PLASTIC) |
| Discount Schedule     | CS2                                |
| GTIN                  | 3389110651706                      |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 0.25 oz (7 g)                      |
| Returnability         | Yes                                |
| Country of origin     | ES                                 |

## Packing Units

|                              |                  |
|------------------------------|------------------|
| Unit Type of Package 1       | PCE              |
| Package 1 Height             | 0.63 in (1.6 cm) |
| Package 1 width              | 0.63 in (1.6 cm) |
| Package 1 Length             | 1.93 in (4.9 cm) |
| Unit Type of Package 2       | BB1              |
| Number of Units in Package 2 | 10               |
| Package 2 Weight             | 2.61 oz (74 g)   |
| Package 2 Height             | 1.18 in (3 cm)   |
| Package 2 width              | 4.72 in (12 cm)  |
| Package 2 Length             | 5.12 in (13 cm)  |
| Unit Type of Package 3       | S01              |
| Number of Units in Package 3 | 100              |
| Package 3 Weight             | 34.29 oz (972 g) |
| Package 3 Height             | 5.91 in (15 cm)  |
| Package 3 width              | 5.91 in (15 cm)  |
| Package 3 Length             | 15.75 in (40 cm) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                                                                                                  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                                                      |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                                                         |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                                                    |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                                                                                    |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                                                                                                 |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                                                                                                          |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                                                                                                                           |

## Contractual warranty


|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

LED Pilot Light

---


Dimensions



- (1) Threaded connector  
e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

LED Pilot Light

Panel Drilling



| Ø min |      | G min |      | H min |      |
|-------|------|-------|------|-------|------|
| mm    | in.  | mm    | in.  | mm    | in.  |
| 12.2  | 0.48 | 16.5  | 0.65 | 16.5  | 0.65 |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Switch Fixings](#) category:*

*Click to view products by [Schneider](#) manufacturer:*

Other Similar products are found below :

[893102000](#) [00-5150](#) [LZZ1A](#) [0098.9234](#) [M2PA-5011](#) [630155](#) [635401](#) [6PA113](#) [6PA147-E6](#) [6PA148-E6](#) [6PA32](#) [6PA9](#) [700109](#) [700303A56](#)  
[700C1GRY](#) [700C2GRN](#) [704-6001](#) [704.960.4](#) [704.960.9](#) [704.965.2](#) [704.965.6](#) [704.966.0](#) [7089-3](#) [710082-B11](#) [71M1048](#) [757200264](#)  
[764300000](#) [MHU35](#) [MHU37](#) [807039-1](#) [825.003.011](#) [825.005.011](#) [825.053.011](#) [825.055.011](#) [826.000.071](#) [827.020.011](#) [827.400.021](#)  
[835.900.023](#) [MML52C10C](#) [MML52E10C](#) [MML92HGH](#) [MML93K](#) [84211M02CNNS](#) [84212M02CNNS](#) [84217A8.0LNOS](#) [842.500.011](#)  
[843.000.011](#) [843187-000](#) [843487-000](#) [84-901](#)