Product data sheet Characteristics

XVUC47

Illuminated LED unit for modular tower lights, white, Ø60, blinking, IP65, 24 V AC/DC

Product availability: Non-Stock - Not normally stocked in distribution facility



Price* : 44.00 USD



Main

7

Complementary

Signalling type	Blinking	و ا
Assembly style	Up to 4 units with buzzer Customer assembly, up to 5 units	is to a
Material	PC (polycarbonate) V-2 UL 94 PC (polycarbonate) V-0 UL 94	for an
[Us] rated supply voltage	24 V AC/DC	
Maximum power dissipation in W	1.2 W	
Signalling type	Blinking	
Length	1.97 in (50 mm)	et appending
Net Weight	0.14 lb(US) (0.064 kg)	

Environment

Product certifications	CSA
	CE
	UL

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

RoHS

Ambient air temperature for storage	-40158 °F (-4070 °C)
IP degree of protection	IP65
Ambient air temperature for operation	-13122 °F (-2550 °C)
Vibration resistance	2 gn

Ordering and shipping details

Category	22618 - XVU TOWER LIGHTS
Discount Schedule	XV
GTIN	00785901469582
Nbr. of units in pkg.	1
Package weight(Lbs)	0.3 lb(US) (0.14 kg)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.54 in (9 cm)
Package 1 width	3.58 in (9.1 cm)
Package 1 Length	5.24 in (13.3 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Weight	8.94 lb(US) (4.057 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information


Life Is On Schneider

Product data sheet Dimensions Drawings

XVUC47

Illuminated LED Unit


Dimensions



Product data sheet Mounting and Clearance

XVUC47

Modular Tower Lights Mounting




Drawing	Part number	Part name
A1	-	Top cover
	-	Top cover (Silver)
A2	XVUC9S	Buzzer unit
	XVUC9SQ	Buzzer unit (Silver)
A3	XVUC23	Green LED unit
	XVUC24	Red LED unit
	XVUC25	Orange LED unit
	XVUC26	Blue LED unit
	XVUC27	White LED unit
	XVUC28	Yellow LED unit
A4	XVUC29	Multi-LED unit
A5	XVUC29P	Multi-LED unit, Pulse signal
A6	XVUC9V	Sound unit
A7	XVUC9VP	Sound unit, Pulse signal

Drawing	Part number	Part name
A8	XVUC020	Extender
	XVUC020Q	Extender (Silver)
A9	XVUC21B	DC body
	XVUC21BQ	DC body (Silver)
A10	XVUC21M	AC body NPN
	XVUC21MP	AC body PNP
	XVUC21MQP	AC body PNP (Silver)
A11	XVUZ06	Flexible option
A12	XVUZ01	Fixing Unit - Direct mounting (3 pins)
	XVUZ01Q	Fixing Unit - Direct mounting (Silver,3 pins)
	XVUZ03	Fixing Unit - Direct mounting (2 pins)
	XVUZ04	Fixing Unit - Direct mounting (4 pins)
A13	XVUZ02	Fixing Unit - Plate with Pole (100 mm)
	XVUZ02Q	Fixing Unit - Plate with Pole (100 mm, Silver)
	XVUZ400	Fixing Unit - Plate with Pole (400 mm)
	XVUZ800	Fixing Unit - Plate with Pole (800 mm)
A14	XVUZ05	Fixing Unit - Plate with adjustment pole (100-385 mm)
A15	XVUC43	Green LED unit, Flash
	XVUC44	Red LED unit, Flash
	XVUC45	Orange LED unit, Flash
	XVUC46	Blue LED unit, Flash
	XVUC47	White LED unit, Flash
	XVUC48	Yellow LED unit, Flash
A16	XVUZ100T	Fixing Unit - Metal bracket with pole (100 mm)
	XVUZ250T	Fixing Unit - Metal bracket with pole(250 mm)
	XVUZ400T	Fixing Unit - Metal bracket with pole (400 mm)
A17	XVUZ12	Fixing plate for use on vertical support - black

Product data sheet Connections and Schema

XVUC47

Illuminated Units, Multi-LED and Audible Units Wiring



- Fixing Unit
- Dimensions of Wiring size
- Push-in Wire Connectors
- (A) (1) (2) (3) (4) (5) (6) Fuse: 2A,250V Fuse: 0.5A,125V
- Modular Tower Lights 24V AC/DC Modular Tower Lights 100...240V AC
- L1 to L5 : Illuminated LED Units

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

01-121.022 LW1A-P1-W LW1B-A0L 01-952.0 01-152.025 D38999/20FJ29PB L/C 704-6012 704-6020 704-6023 704-6026 73.362.4028.0 EUS-704.000.7 750-1520 9001OA120 99-450.837 99-455.837 99-458.837 99-486.837 99-901.9 99-902.9 99-908.0 99-909.4 99-909.5 A0244J1 A3DT-500Y AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-A APD106LN-G APN1126-G APS122DN-W ATN2100 AYLW4L-A 18-237.035 C0180AANAH HW1A-L1-GD HW1A-P2-GL HW1F-3G HW1R-2DF20-R HW1X-BM411-R HW2A-L1-GL HW2A-P1-GD HW4S-31L HWAZ1N-OB PA2200/1 PA2SHIELD PAMR25 21-931.0 21-931.2