



### Main

Product or Component Type	Accessory kit
Accessory / separate part destination	Ultrasonic sensor
Product compatibility	XXA - ultrasonic sensor XXS - ultrasonic sensor
Accessory / separate part category	Configuration accessories
Accessory / Separate Part Type	Configuration software

### Complementary

Material	Plastic and metal
----------	-------------------

### Environment

Ambient Air Temperature for Storage	-4...113 °F (-20...45 °C)
Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	95 % without condensation

### Ordering and shipping details

Category	22489-SENSORS XX ULTRASONIC GEN PURPOSE
Discount Schedule	DS2
GTIN	3389119631990
Nbr. of units in pkg.	1
Package weight(Lbs)	2.65 lb(US) (1.2 kg)
Returnability	Yes
Country of origin	FR

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.12 in (13 cm)
Package 1 width	11.81 in (30 cm)
Package 1 Length	15.75 in (40 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Sensor Fixings & Accessories](#) category:*

*Click to view products by [Schneider](#) manufacturer:*

Other Similar products are found below :

[8000-5130](#) [R4](#) [PBT420-100R](#) [SS-12143](#) [STA12](#) [AP4-T](#) [R6](#) [D01051301](#) [43912557-020](#) [D01070602](#) [606072](#) [606075](#) [28810-2](#) [ZX-SW11E](#)  
[V3](#) [T63353](#) [32043-625](#) [SS-12225](#) [PH-2-60M](#) [ZS-SW11V3E](#) [STE-1042609RFRC](#) [STE-1186763RFM4](#) [76002066](#) [C115](#) [E02](#) [041](#) [G1](#) [C115](#)  
[E05](#) [041](#) [G1](#) [SA9Z-S07PN02](#) [ECT18-WELL](#) [79450811](#) [P2435.3](#) [AS7030B\\_WRISTBAND](#) [AS7038GB\\_WRISTBAND](#) [51001R](#) [11027667-00](#)  
[XUZD15](#) [ROTATEKNOB3D2GOKITTOBO1](#) [XUVF60M8](#) [1410RFT 6-12V AC/DC](#) [1411RFT-24V DC](#) [1420RFW 12-24V AC/DC](#)  
[1420RFW 6-12V AC/DC](#) [1428 24-48V AC/DC](#) [1428RF 12-24V AC/DC](#) [1428RF 24-48V AC/DC](#) [1448RF 12-24V AC/DC](#) [1448RF 24-48V](#)  
[AC/DC](#) [1448RFT 12-24V AC/DC](#) [1510 12-24V AC/DC](#) [1743 6-12V AC/DC](#) [1743BB 12-24V DC](#) [1748 12-24V AC/DC](#) [1748 24-48V](#)  
[AC/DC](#)