Product data sheet Characteristics

XZCC12FCM50B

female, M12, 5-pin, elbowed connector - cable gland Pg 7

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed female connector M12, 5 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <= 0.75 mm ² / clamping capacity 0.120.24 in (36 mm)

Complementary

Cable gland type	Pg 7
Cable connector fixing	Screw-on
System Voltage	30 V AC 36 V DC
Line Rated Current	3 A
Enclosure material	Plastic
Insulating resistance	> 1000 GΩ
Contact resistance	<= 8000 μOhm
Product weight	0.04 lb(US) (0.02 kg)

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-40185 °F (-4085 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389110806267
Nbr. of units in pkg.	1
Package weight(Lbs)	7.0000000000007E-2
Returnability	Ν
Country of origin	HU

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0726 - Schneider Electric declaration of conformity Schnei- der Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov



Contractual warranty


Warranty period

18 months

Product data sheet **Dimensions Drawings**

XZCC12FCM50B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

XZCC12FCM50B

Connections and Schemes



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Fixings & Accessories category:

Click to view products by Schneider manufacturer:

Other Similar products are found below :

 F03-01 SUS304 BINIL
 8000-5130
 FH-AP1
 PH-1-10M
 PH-1-20M
 PH-2-30M
 AC201
 R4
 ADI-LC3S
 EC18-WELL
 PC-15015
 K35-4
 A

 1923
 SS-12143
 STA12
 AP4-T
 PH-1-50M
 R6
 D01051301
 43912557-020
 MF-1
 D=3.2
 BGN-035
 E39-L7
 ZX-SB11
 D01070602
 606072

 606075
 Y92ES12PVC4A10ML
 Y92ES12PVC4S5ML
 SA9Z-F11
 Z49-SF1
 ZFV-XMF2
 E4R-R12A-CS3M010
 28810-2
 ZX-SW11E
 V3

 CCS-PL-LDR2-70
 E4R-R12A-CS3M020
 BS-1T CHITAN
 F03-01 CHITAN
 CCS-PD2-1012
 PH-2-5M
 XMLZL008
 AC244

 28810-1
 PH-1-40M
 SS-12225
 32043-500
 81532111
 PH-2-60M