XZCC8FDM30S

female, M8, 3-pin, straight connector - cable gland M9.5 x 1

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Straight female connector M8, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Solder terminal / wire size <= 0.25 mm² / clamping capacity <= 0.2 in (5 mm)

Complementary

Complementary		
Cable gland type	M9.5	
Cable connector fixing	Screw-on	
System Voltage	60 V AC 75 V DC	
Line Rated Current	4 A	
Enclosure material	Plastic	
Insulating resistance	> 1 GΩ	
Contact resistance	<= 5000 μOhm	
Product weight	0.02 lb(US) (0.01 kg)	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-40185 °F (-4085 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES	
Discount Schedule	DS3	
GTIN	003389110834703	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.02	
Returnability	N	
Country of origin	DE	

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0545 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	


Warranty period

18 months

Product data sheet Dimensions Drawings

XZCC8FDM30S

Dimensions



Product data sheet Connections and Schema

XZCC8FDM30S

Connections and Schemes



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sensor Fixings & Accessories category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

F03-01 SUS304 BINIL 8000-5130 FH-AP1 PH-1-10M PH-1-20M PH-2-30M AC201 R4 ADI-LC3S EC18-WELL PC-15015 K35-4 A-1923 SS-12143 STA12 AP4-T PH-1-50M R6 D01051301 43912557-020 MF-1 D=3.2 BGN-035 E39-L7 ZX-SB11 D01070602 606072 606075 Y92ES12PVC4A10ML Y92ES12PVC4S5ML SA9Z-F11 Z49-SF1 ZFV-XMF2 E4R-R12A-CS3M010 28810-2 ZX-SW11E V3 CCS-PL-LDR2-70 E4R-R12A-CS3M020 BS-1T CHITAN F03-01 CHITAN CCS-PD2-1012 PH-2-90M PH-2-5M XMLZL008 AC244 28810-1 PH-1-40M SS-12225 32043-500 81532111 PH-2-60M