ZB4BC480

pushbutton head for harsh environment - red - without marking



Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Range of product	Harmony XB4
Product or component type	Head for push-button
Device short name	ZB4
Bezel material	Chromium plated metal
Head type	Standard
Mounting diameter	0.87 in (22 mm)
Sale per indivisible quantity	1

\sim				
CiO	mn	lem	ıen	tarv

CAD overall width	1.46 in (37 mm)
CAD overall height	0.73 in (18.5 mm)
CAD overall depth	1.46 in (37 mm)
Product weight	0.08 lb(US) (0.036 kg)
Electrical shock protection class	Class I conforming to IEC 61140
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Flush red unmarked
Operator additional information	Vertical mounting Horizontal mounting
Mechanical durability	10000000 cycles
Vibration resistance	5 gn (f=2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27
Main group	Harsh environment
Group of product	Flush unmarked
Cap/operator or lens colour	Red
Marking	Unmarked
Electrical composition code	C15 1 contacts using single blocks in front mounting C11 3 contacts using single blocks in front mounting C1 9 contacts using single blocks in front mounting C2 9 contacts using single and double blocks in front mounting

Environment

Ambient air temperature for storage	-40185 °F (-4085 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529 IP69K	
NEMA degree of protection	NEMA 12 NEMA 13 NEMA 4 conforming to UL 508	
Resistance to high pressure washer	0.01 psi (90 Pa) at 181 °F (82.5 °C)	
IK degree of protection	IK06 conforming to IEC 62262	

Standards	CSA C22.2 IEC 60947-1 IEC 60947-5-1 UL 508	
Product certifications	UL CE CSA	

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	00785901829645
Nbr. of units in pkg.	1
Package weight(Lbs)	7.000000000000007E-2
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov


Contractual warranty

Warranty period	1	18 months

Product data sheet Dimensions Drawings


ZB4BC480

Dimensions




Installation on Flat Surface

Without Protective Guard



(1) Ø22.5 mm recommended (Ø22.3 $_0$ $^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 $_0$ $^{+0.016}$)

With Protective Guard



(1) Ø22.5 mm recommended (Ø22.3 $_0$ $^{+0.4}$) / Ø0.89 in. recommended (Ø0.88 $_0$ $^{+0.016}$)

Legend

Electrical Composition Corresponding to Code C1
Electrical Composition Corresponding to Code C2
Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1
Electrical Composition Corresponding to Code C15
1 N/C 1 N/C or 1 N/O + N/O or 1 N/C + N/C

Single contact



Double contact



Light block



Possible location



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Bezels / Switch Caps category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

896809000 LW1A-B2-R LW2A-B1-G 704.604.4 704.955.3 F1403 7527 760203000 760503000 766601000 785105000 785106000

79211759 MG12KB MH11 MH13 MHU31 MJ1216 MJ1226 MJ33 MJ612 MJ626 MJ627 9001T8BK 908-1634 92-343.200 92-343.400

95804.920 95CAP-011 95CAP-112 11-932.7 99-901.9 99-902.9 99-909.4 99-909.5 99-920.8 A0261A 11-931.2 11-932.5 11-936

AKTSC22B AT496H AW-RF8 161006 1825068-6 184-1872 187-1872 188-1471 1DFBLK 1D-GRY