# **ZBE1025**

# single contact block for head Ø22 1NC silver alloy spring clamp terminals

Product availability: Stock - Normally stocked in distribution facility



Main	
Range of product	Harmony XB4 Harmony XB5
Product or component type	Contact block
Device short name	ZBE
Sale per indivisible quantity	4
IP degree of protection	IP20 IEC 60529
Contacts type and composition	1 NC
Contact operation	Slow-break
Contact block type	Single
Contacts usage	Standard contacts
Connections - terminals	Spring clamp terminals

#### Complementary

Product weight	0.02 lb(US) (0.011 kg)	
Positive opening	With EN/IEC 60947-5-1 appendix K	
Operating travel	0.06 in (1.5 mm) NC changing electrical state 0.17 in (4.3 mm) total travel	
Operating force	2 N NC changing electrical state	
Mechanical durability	10000000 cycles	
Contacts material	Silver alloy (Ag/Ni)	
Electrical reliability	$\Lambda$ < 10exp(-7) 1 mA in clean environment EN/IEC 60947-5-4 $\Lambda$ < 10exp(-8) 5 mA in clean environment EN/IEC 60947-5-4	
Mounting of block	Front mounting	
Condition of use	Mounting on push-button collar	
Electrical composition code	C11 <= 3 C14 <= 2 M10 <= 2	
Compatibility code	ZBE	

#### Environment

Protective treatment	TH	
Ambient air temperature for storage	mperature for storage -40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Standards  EN/IEC 60947-5-1  UL 508  JIS C 4520  EN/IEC 60947-5-4  CSA C22.2 No 14  EN/IEC 60947-1		
Product certifications	LROS (Lloyds register of shipping) DNV CCC UL CSA RINA GOST GL BV	

Vibration resistance	5 gn 2500 Hz IEC 60068-2-6
Shock resistance	30 gn 18 ms half sine wave acceleration IEC 60068-2-27 50 gn 11 ms half sine wave acceleration IEC 60068-2-27

#### Ordering and shipping details

0 11 0		
Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW	
Discount Schedule	CS2	
GTIN	00785901707752	
Nbr. of units in pkg.	4	
Package weight(Lbs)	0.02	
Returnability	Υ	
Country of origin	FR	

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1 Nickel compounds, which is known to the State of California to ca		
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

## Contractual warranty

Warranty period	18 months	

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8515.8640 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505001 190-17508-001 190-17508-002 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-005 GLZ304

51401 BS010 BST-D HW-S01 XESP2021 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 A3CA7121 84-8511.6320 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17500-002 190-17500-006 190-17510-001

1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added GLZ336