### Product data sheet Characteristics

## ZBVB37 green light block for head Ø22 integral LED 24V pins

Product availability: Stock - Normally stocked in distribution facility



Main	
Range of product	Harmony XB5 Harmony XB4
Product or component type	Light block
Device short name	ZBV
Sale per indivisible quantity	5
Connections - terminals	Pins for printed circuit board
Signalling type	Steady
Light source	Protected LED
Bulb base	Integral LED
Light block supply	Direct
Light source colour	Green
[Us] rated supply volt- age	24 V AC/DC, 50/60 Hz

#### Complementary

Product weight	0.01 lb(US) (0.004 kg)
Supply voltage limits	19.230 V DC
	21.626.4 V AC
Current consumption	18 mA
Service life	100000 h at rated voltage and 25 °C
Surge withstand	1 kV conforming to IEC 61000-4-5
Mounting of block	Front mounting
Electrical composition code	M1
	M2
	M3
	M4
	M5
	M6
	M10
	MF1
	P1
	P2
	PF1
Compatibility code	ZBV
Environment	
Protective treatment	ТН
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-40158 °F (-4070 °C)
IP degree of protection	IP20 conforming to IEC 60529
Standards	EN/IEC 60947-1
	EN/IEC 60947-5-4
	UL 508
	JIS C 4520
	EN/IEC 60947-5-1
	CSA C22.2 No 14
	EN/IEC 60947-5-5
Resistance to fast transients	2 kV conforming to IEC 61000-4-4
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) conforming to IEC 61000-4-3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products for submined herein. This documentation is not intended as a substitute for and is not to be used for determining substitity or reliability of these products for specific use applications. It is the ducty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products for specific user applications. Neither Schneider Electric Inductive SSA nor any of its affiliates or substitiantes shall be responsible or liable for misues of the information contrained herein.



Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2
Electromagnetic emission	Class B conforming to IEC 55011

#### Ordering and shipping details

22469 - PUSHBUTTON,22MM ACCESSORIES-NEW	
CS2	
00785901383291	
5	
0.01	
Υ	
FR	
	CS2 00785901383291 5 0.01 Y

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause can- cer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

Warranty period

18 months

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by Schneider manufacturer:

Other Similar products are found below :

LW1A-P1-GD LW1A-P1-W 01-931.3 01-152.025 73.362.4028.0 750-1520 9001OA120 A0142N5 A3DT-500Y AL6M-LK3-R AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-G APD106LN-S APN1126-G APS122DN-W ASLWLD-G ASLWLD-R ATN2100 AYLW4L-A 18-237.035 18-945 HW1A-L1-GD HW1A-P2-GL HW1X-BM411-R HW2A-L1-GL HWAZ1N-OB PA2100/2 PA2200/1 PA2SHIELD PAMR25 LA3P-1C03V-Y 96-923.5 A0244J2 LSPD-120A LSPD-1Y LSPD-6A LSPD-6DA LSPD-6DW LSPD-6DY LSPD-6R LSPD-6W 18-946 AL6H-LK3-A AL6H-P4-JW AL6M-LK1-MG AP8M155-G APD106LN-W APN106L-O