Product data sheet Characteristics

ZC2JC1

limit switch body ZC2J - fixed - without display - 1C/O



Product availability: Stock - Normally stocked in distribution facility



Main Range of product OsiSense XC Series name Standard format Product or component Limit switch body type Device short name ZC2J Body type Fixed XC2J Product compatibility Associated head ZC2JE01 ZC2JE63 ZC2JE62 ZC2JE66 ZC2JE02 ZC2JE61 ZC2JE65 ZC2JE09 ZC2JE70 ZC2JE05 ZC2JE03 ZC2JE64 Body material Cable entry 1 tapped entry for Pg 13.5 cable gland (included) Number of poles

1 C/O

Snap action

1 1 position

Silver plated contacts

Complementary

Local display	Without
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.52 x 2.5 mm²
Positive opening	Without
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	300 V conforming to CSA C22.2 No 14 contact block 500 V conforming to IEC 60947-1 contact block
Resistance across terminals	0.25 mOhm conforming to IEC 60255-7 category 3
Short-circuit protection	10 A by gG cartridge fuse
Electrical durability	5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Width	1.57 in (40 mm)
Height	3.19 in (81 mm)
Depth	1.61 in (41 mm)
Product weight	0.78 lb(US) (0.355 kg)
Terminals description ISO n°1	(11-12)NC (13-14)NO

Contacts type and com-

Contact operation

Number of steps

Contacts material

position

Environment

IP degree of protection	IP65
IK degree of protection	IK08
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment
Ambient air temperature for storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22449 - LIMIT SWITCHES,ACCESSORIES
Discount Schedule	Т
GTIN	00785901266365
Nbr. of units in pkg.	1
Package weight(Lbs)	0.810000000000005
Returnability	Υ
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1012 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8515.8640 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505001 190-17508-001 190-17508-002 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-005 GLZ304

51401 BS010 BST-D HW-S01 XESP2021 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 A3CA7121 84-8511.6320 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17500-002 190-17500-006 190-17510-001

1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added GLZ336