Product data sheet Characteristics

ZCK D10 😔

## ZCKD10 limit switch head ZCKD - metal end plunger



Product availability: Stock - Normally stocked in distribution facility

Range of product	OsiSense XC	
Series name	Standard format	
Product or component type	Limit switch head	
Device short name	ZCKD	
Head type	Plunger head	
Product compatibility	XCKL XCKM	
Associated body	ZCKM6H7 ZCKM7 ZCKM5H7 ZCKLD39 ZCKM8H7	
	ZCKM1H7 ZCKL8H7 ZCKL8	
	ZCKL5H7 ZCKMD39 ZCKL7	
	ZCKM8H29 ZCKL6 ZCKLD35H7 ZCKL5 ZCKM8	he performance of the products contained herein.
	ZCKLD37H7 ZCKM7H29 ZCKM5H29 ZCKMD37H7	cal characteristics of the performance of the products contained herein suitability or reliability of these products for specific user applications.
	ZCKMD39H29 ZCKLD31 ZCKM9 ZCKMD35H29	nce of the prc
	ZCKM1 ZCKL6H7 ZCKL7H7 ZCKL1H7	the performa
	ZCKLD39H7 ZCKM7H7 ZCKLD35	cal characteristics of th suitability or reliability
	ZCKM9H29 ZCKM6H29 ZCKMD37H29 ZCKM5	r technical che mining suitat
	ZCKMD31H7 ZCKMD31 ZCKMD35 ZCKMD39H7 ZCKMD35H7 ZCKMD327	The information provided in this documentation contains general descriptions and/or techni The information provided in this documentation contains general descriptions and/or techni
	ZCKMD37 ZCKLD31H7 ZCKLD37 ZCKL1 ZCKM6	The information provided in this documentation contains general descriptions and/or techni This documentation is not interded as a substitute for and is not to be used for determining
	ZCKMD31H29 ZCKM1H29	itation
Movement of operating head	Linear	documen ded as a s
Type of operator	End plunger spring return metal	n this
Type of approach	Vertical approach 1 direction	ovided ii
		iformation pro locumentation



## Complementary

Switch actuation	On end
Positive opening	With
Head material	Plastic

#### Environment

Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

### Ordering and shipping details

Category	22416 - LIMIT SWITCHES,IEC,XCKL
Discount Schedule	Т
GTIN	00785901646709
Nbr. of units in pkg.	1
Package weight(Lbs)	0.10000000000001
Returnability	γ
Country of origin	ID

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0922 - Schneider Electric declaration of conformity Schnei- der Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

#### Contractual warranty

Warranty period

18 months

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Limit Switches category:

Click to view products by Schneider manufacturer:

Other Similar products are found below :

 5ML1-E1
 5ML31
 LZG1
 LZL1-6C
 622EN114-R
 622EN18-6
 622EN224-6B
 622EN230
 622EN237-R
 622EN69-3
 622EN85-RB
 MA-10019

 6PA109
 7LS51
 83547001
 83725002
 83830001
 83840701
 83841001
 83881140
 8AS42
 8LS10
 8LS125-4PG
 8LS152-4PGN20
 914CE16 

 3A
 914CE3-3L1
 915PA10
 91MCE16-P2O
 924CE16-Y3
 924CE1-S6
 924CE1-T25A
 924CE1-T3
 924CE1-T9A
 924CE2-T9
 924CE31-Y20 

 X5
 924CE31-Y3L1
 GL-10054
 GLAB26J2B
 GLDB03C-6
 GLDC05C
 GLZ324
 H3141CAKAA
 RDI-G-L5B
 DD-10000
 DT-2R3-A7

 14CE16-3N28
 14CE18-N15
 151ML3-E1
 E3102BAAAA
 BFL1-AW1-S