



Main

| | |
|---------------------------|---|
| Range | TeSys |
| Product name | TeSys VARIO |
| Device short name | VCF |
| Product or component type | Enclosed emergency stop switch disconnecter |
| Performance level | High performance |
| Poles description | 3P |
| Control type | Rotary handle |
| Handle colour | Red |
| Handle front plate colour | Yellow |
| Rotary handle padlocking | 1 to 3 padlocks with 4...8 mm |

Complementary

| | |
|--|--|
| Marking | 0 - 1 |
| [Ue] rated operational voltage | 690 V AC |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ithe] conventional enclosed thermal current | 25 A |
| [Ie] rated operational current | 21.8 A AC-23A 400 V |
| Rated operational power in W | 7.5 kW at 400 V AC-3 11 kW at 400 V AC-23 |
| Intermittent duty class | 30 |
| Making capacity (I rms) | 320 A at 400 V AC-21A 320 A at 400 V AC-22A 320 A at 400 V AC-23A |
| [Icm] rated short-circuit making capacity | 1 kA at 400 V at Ipeak |
| [Icw] rated short-time withstand Rms current | 384 A at 400 V during 1 s |
| Rated conditional short-circuit current | 10 kA at 400 V - associated fuse 35 A aM 10 kA at 400 V - associated fuse 35 A gG |
| Breaking capacity | 250 A at 400 V (AC-21A) |

| | |
|------------------------------|---|
| | 250 A at 400 V (AC-22A) 250 A at 400 V (AC-23A) |
| Mechanical durability | 100000 cycles |
| Electrical durability | 30000 cycles DC-1...5 100000 cycles AC-21 |
| Environmental characteristic | Standard environment |
| Suitability for isolation | Yes |
| Connections - terminals | Screw clamp terminals cable 6 mm ² - cable stiffness: flexible - with cable end cable end Screw clamp terminals cable 10 mm ² - cable stiffness: solid - |
| Tightening torque | 2.1 N.m - on screw clamp terminals |
| Fire resistance | 960 °C conforming to IEC 60595-2-1 |
| Handle front plate dimension | 60 x 60 mm |
| Height | 146 mm |
| Width | 90 mm |
| Depth | 131 mm |
| Product weight | 0.5 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60204 IEC 60947-4-1 |
| Protective treatment | TC |
| IP degree of protection | IP65 conforming to IEC 60529 |
| Mechanical robustness | Vibrations 10...150 Hz 1 gn IEC 60068-2-6 Shocks 11 ms 30 Gn IEC 60068-2-27 |
| Ambient air temperature for operation | -20...50 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0738 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [Schneider Electric](#) manufacturer:

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62149-1](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [66107-4-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#)