Caps to Holder FUL, FUP, FUA



500 VAC · 4W/16A (VDE) · 600 VAC/DC · 30 A (UL/CSA)

Approvals and Compliances

References

Mating Cap to FUA; FUL; FUP

Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product, Microsite

Tec	hnical	Data

Fuse-Link	5 x 20 / 6.3 x 32 mm
Rated Voltage	500 VAC (VDE), 600 VAC/DC (UL/CSA)
Rated current	16A (VDE), 30A (UL/CSA)
Rated Power Acceptance IEC	4W / 16A @ Ta 23°C
Degree of Protection	IP40
Admissible Ambient Air Temp.	-40 °C to 85 °C
Material: Cap	Thermoset, UL 94V-0
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	5 ,

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
<u>IEC</u>	Designed according to	IEC 60127-6	Miniature fuses. Part 6. Fuse-holders for miniature fuse-links
(VL)	Designed according to	UL 4248-1	Industrial Control Equipment
CSA Group	Designed according to	CSA C22.2 no. 4248.1	Industrial Control Equipment

Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements
<u>IEC</u>	Designed for applications acc.	IEC 60335-1	Safety of electrical appliances for household and similar purposes. Meets the requirements for appliances in unattended use. This includes the enhanced requirements of glow wire tests acc. to IEC 60695-2-11 or -12 & -13.


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
5 0	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.
00	White Paper Glow wire test	SCHURTER AG	Meets the requirements of IEC 60335-1 for appliances in unattended use. This includes the enhanced requirements of glow wire tests acc. to IEC 60695-2-11 or -12 &-13.







0031.2323 0031.2321

All Variants

Designation	Order Number
Caps to FUL, FUP, FUA	0031.2321
Caps to FUL, FUP, FUA	0031.2323

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging Unit Plastic Bag (25 pcs.)

product selected for their own applications.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder Accessories category:

Click to view products by Schurter manufacturer:

Other Similar products are found below:

BK/1A1337 1A1853 1A4421 1A5220 903-048 1A1337 1A4544 1A5220-01 CO2-10 CO3-03 348897 B072-7007 BK/1A4421 X30110 09030012H 09050023H 00970021HXNVDL 00BS0232P CO2-04 BK1A1853 BK9834 0880.0001 00970053XP 3566C 00970053H 04450718ZX900 CH10CL BP/FP-3 58600000005 33-012C 880140 00970023S 880150 PDM71009ZXM B109-7091-4 B109-7091-6 B109-7091-5 901-524 CVR-RH-25100 LFH60030FBC 03540514Z 03540526Z 03540531Z 03540541Z 03540525Z 03540537Z 03540539Z 03540540Z FEH CC2/J