

Fuseholder Open Design, 5 x 20 mm, Solder, transparent, Cover



250 VAC · 6.3 A Description - Screw/rivet fastening - Solder terminals		See below: Approvals and Compliances	
		Weblinks pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Accessories, Detailed request for product, Microsite	
Technical Data			
Fuse-Link	5 x 20 mm	Soldering Methods	Iron
Mounting	Screw		Soldering Profile
Attachment	Screw/Rivet	Solderability	350°C / 2 sec acc. to IEC 60068-2-20,
Terminal	Solder		Test Ta, method 2
Rated Voltage	250 VAC	Resistance to Soldering Heat	350°C / 10 sec acc. to IEC 60068-2-20,
Rated current	6.3A		Test Tb, method 2
Admissible Ambient Air Temp.	-40°C to 85°C	Solderability	350°C / 2 sec acc. to IEC 60068-2-20,
Climatic Category	40/085/21 acc. to IEC 60068-1		Test Ta, method 2
Material: Socket	Thermoplastic, Nature, UL 94V-1	Contact Resistance	< 10 mΩ at 100 mA
Material: Cover	Thermoplastic Transparent UL 94V-0	Dielectric Strength	> 3kV
Material: Terminals	Copper alloy, tin-plated		(50 Hz: 1 min)
Unit Weight	1.5 g	Impulse Withstand Voltage	> 4 kV between L-N
Storage Conditions	0°C to 60°C may 70% rh	Insulation Resistance	$> 10 \text{M}\Omega$ between L-N

Approvals and Compliances

Storage Conditions

Product Marking

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

0°C to 60°C, max. 70% r.h.

fication marks

5, Rated Voltage, Rated current, Certi-

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements


Compliances

The product complies with following Guide Lines


Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.


(500 VDC: 1 min)

Dimension [mm]



Derating Curves





The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each

product selected for their own applications.

d 39.2 mm

All Variants

Holder Order Number 0031.5101 Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging Unit

Bulk (1000 pcs.)

Accessories

Description



Cover OG, UHB, UH Cover for Holder OG (Clip) 5x20, OG (Halter) 5x20, UH, UHB

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Schurter manufacturer:

Other Similar products are found below:

570-290-741P40 570-290-751P40 020417G 020418E 6R30A1B F600A3B 80910030 8601.2020 G15A2SPQ 9-3557-GP REV A HDJ-B R6J30A3S HFH-1 RF30A2B RF30A3SP 15600-08-10 BK/FHN19G BK/HHM BK/HKP-CCHH BK/HKP-JJ BK/HTJ-LES-FUSE HMG-241 HTJ-LES-FUSE C4044-1 2086-1 2193 2602 2650 178.000100 FHN31G1 T30A2B G4PB8 2660 2799 CQ-209V HKP-CCHH R6F30A2S 341001A 345621A CVRMCC 4202 4407 4408 4413 4423 4532 4537 TSD1404-12 BK/FHN31G1 BK/HC-5