

Description

- Voltage Selector , 3 stages
- Step switch
- PCB terminals

See below: Approvals and Compliances

References

Alternative: version for panel mounting SWM1 (Frontpl)

Weblinks

pdf data sheet, html datasheet, General Product Information, Approvals, Distributor-Stock-Check, Detailed request for product

Technical Data		
Ratings	IEC: 6.3 A / 250 VAC; 50 Hz	
-	UL: 10 A / 250 VAC; 60 Hz	
	CSA: 10 A / 250 VAC; 60 Hz	
Mounting	PCB	
Terminal	Solder / THT	
Number of Stages	3	
Lifetime	300 operating cycles (without load)	
Degree of Protection	front side IP40	
Protection Class	Suitable for appliances with protection class II acc. to IEC 61140	
Allowable Operation Tempe- rature	-40 °C to 85 °C	
Climatic Category	25/85/21 acc. to IEC 60068-1	
Material: Socket	Thermoplastic, black, UL 94V-0	
Weight	6.5 g	
Degree of Protection Protection Class Allowable Operation Tempe- rature Climatic Category Material: Socket	front side IP40 Suitable for appliances with protection class II acc. to IEC 61140 -40 °C to 85 °C 25/85/21 acc. to IEC 60068-1 Thermoplastic, black, UL 94V-0	

Solderability	235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1
Resistance to Soldering Heat	260 °C / 5 sec acc. to IEC 60068-2-20, Test Tb, method 1A
Insulation Resistance	> 10'000MΩ (500VDC; 1min)
Contact Resistance	< 10 m Ω at 20 mV
Dielectric Strength	> 2kVAC between L-N > 4kVAC between L/N-PE (1min; 50Hz)
Clearance and Creepage Di- stance	> 3mm > 8mm between L/N-PE
Resistance to Vibration	acc. to IEC 60068-2-6, test Fc

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals


The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: SWM

Approval Logo	Certificates	Certification Body	Description
10	VDE Approvals	VDE	Certificate Number:
c FL us	UL Approvals	UL	UL File Number: E72661


SWM2 (Print)

Organization	Design	Standard	Description
(h)	Designed according to	UL 508	Industrial control equipment
GR Group	Designed according to	CSA C22.2 no. 55	Industrial Control Equipment
Application sta	ndards		
Application standa	ards where the product can be used		
Organization	Design	Standard	Description
IEC	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements
I <u>EC</u>	Designed for applications acc.	IEC 60335-1	Safety of electrical appliances for household and similar purposes. Meets the requirements for appliances in unattended use. This includes the enhanced requirements of glow wire tests acc. to IEC 60695-2-11 or -12 & -13.
Compliances			
The product comp	olies with following Guide Lines		
Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
JK JA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.


24



T



Drilling diagram



Diagrams

$$1 = C$$

$$0$$

$$5 \xrightarrow{0} 0 2 = B$$

$$3 = A$$

All Variants

	Letterings		Order Number	
Α	В	С		
100	115	230	0033.4208	
			0033.4214	
115	200	230	0033.4259	
Availability for all products can be searched real-time:https://www. schurter.com/en/Stock-Check/Stock-Check-SCHURTER				

50 Pcs

Packaging Unit

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rotary Switches category:

Click to view products by Schurter manufacturer:

Other Similar products are found below :

57HS22-02-2-06N 57M22-02B16N 57M22-09A16N M3786/4-0881 M3786/4-3267 M3786/4-5568 M3786/4-6029 MC06L1NCGF 84986-26 9003K2C003GA PLR3251 PLR3262 PS3 A0142M2SP A019605 A029303 R2AA4455NNNN R2BB4455NNNN DR75-AMSF-10R-B 14-520.0360 1703.3201 HW1MS-0202-101 24002-03S A029101 ACSNO-129-YB-C1014 ACSNO-134-RR-YB-C1005 ACSNO-353-SB-C3016 1825537-4 T505 T505E 24005-03N H10207RR01Q M3786/4-0002 M3786/4-0630 M3786/4-1028L M3786/4-1233L M3786/4-3044 M3786/4-3129 M3786/4-5008L M3786/4-5256 MC6CX1A502X009 42HS36-01-1-06N 42P36-03B10S 44MBS60-04-2-03N 44MG90-02-1-02N 50KMT90-01-2-02N 51A22-01-1-16S 51CDP30-01PAJN 51KSP30-01D04N 51P30-01B12N