



See below: Approvals and Compliances

Weblinks

Description

- Test Probe

- Diameter 2.0 mm

Technical Data

Diameter	2mm	
Rated current	6.3A	
Admissible switching power	@ 250 Insertions:	
	220 W / max. 5 A or 75 VDC	
	440 W / max. 5 A or 50 VAC	
	@ 1000 Insertions:	
	100 W / max. 2 A or 75 VDC	
	150 W / max. 5 A or 50 VAC	
Contact resistance	$< 7 \mathrm{m}\Omega$ at 20 mV	
Allowable Operation Tempe-	-25 °C to 70 °C	
rature		

Resistance to Soldering Heat	260 °C / 5 sec acc. to IEC 60068-2-	
	20 , Test Tb, method 1A	
Weight	1.1g	
Material: Housing	Thermoplastic (PC), UL 94V-2	
Surface of contacts	gold plated , Thickness 2.0 µm	
Material: Housing	Thermoplastic (PC), UL 94V-2	

pdf data sheet, html datasheet, General Product Information, Approvals,

Distributor-Stock-Check, Accessories, Detailed request for product

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.


Application standards

Application standards where the product can be used

Organization	Design	Standard	Description			
I <u>EC</u>	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements			
Compliances						
The product complies with following Guide Lines						
Identification	Details	Initiator	Description			
COMPLIANT	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863			
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.			
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.			

PS 1161

Dimensions [mm]



Diagrams

All Variants

Product group	Color	Order Number
Test Probe	black	0040.1161
Test Probe	red	0040.1162

Availability for all products can be searched real-time:https://www.schurter. com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit

100 Pcs

Mating Outlets/Connectors

Category / Description



Test Jacks & Probes Overview complete

PB 1151, 6.3 A, Test Jack

PB 1151

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Clips category:

Click to view products by Schurter manufacturer:

Other Similar products are found below :

010000 923743-16 923850-C BU-656-0 923738-28 4140A 4324A TL820 TL822 5116 5450 5216 5252 5454 5694 923700 923698 CR0060 3038 927739-20 923743-14 923743-40 932146101 930318100 930126101 Z-SB3FA3250AAAB04001 Z-S11F0107G1000 Z-S11F0207B1520 Z-S11F0207B2030 Z-S11F0207B15000 Z-SB3FA3226AAAB11001 Z-S11F0207B1010 Z-S11F0207B3000 923706 930317800 930317801 973889100 972405100 972405101 923714 R999720600 949-1 458-3 SK 201200278 020 BU-65-B BU-21CPN-GZZZ PK-HVA-02 BU-25C-DZZZ BU-142-2 SAK 6675 NI/GNGE