Touchkit with capacitive touchscreen



See below:

Approvals and Compliances

Description

- Kit content:
- 1x 10.1" SCHURTER Touchscreen Sensor on 2 mm float glass
- 1x PCAP controller board (EETI chipset)
- 1x Active Touchscreen Stylus
- 1x 1 m mini USB-Cable
- 4x self adhesive Feet
- 1x USB stick with evaluation software
- 1x AAAA battery for the active stylus
- 1x Quick Start Guide

Unique Selling Proposition

- Plug and Play
- Multitouch functionality
- Glove operation

Characteristics

- Capacitive touch sensor
- No external power supply necessaryChoice of 2 sensitivity modes
- Up to 10 fingers at one time
- Hand palm rejection
- Water resistant
- EMC up to 10 Vrms conducted immunity and 10 V/m radiated immunity

Weblinks

pdf data sheet, html datasheet, General Product Information, CAD-Drawings, Product News, Detailed request for product, Microsite

Technical Data

Sensor		
Туре	T1542	
Size	10.1 " active area 139.6 mm x 221 mm	
Electrode Pitch	5.52 mm x 5.37 mm	
Material	PET + ITO + Kapton tail	
Cover	2 mm float glass	
Printing	Black with SCHURTER Logo	
Channel-count	26 x 40 channels	
Operating Temperature	-10°C to +70°C	
Storage Temperature	-20°C to +75°C	
Controller		
Chipset	EETI EX3146	
Size	30 mm x 65 mm	
Channel-count	max. 30 x 42 channels (including shield lines)	
Input voltage	3.5 V ~ 5.5 V typ. 5 V (powered via USB)	
Power consumption	Active mode: < 50 mA	
	Idle mode: < 30 mA	
Operating Temperature	-40 °C to +85 °C	
Storage Temperature	-40°C to +90°C	
Relative humidity	95% at 60 °C RH nicht kondensierend	
Interface	USB 1.1 Full speed (mini-USB)	
	I ² C 100 - 400 kHz (2.54 mm pitch sol-	
	dering interface) *	
Response time	< 25 ms	
Report rate	> 100 Hz (1 - 10 fingers)	
USB-HID	Compatible (Windows / Linux / Mac OS)	

Active Touchscreen stylus				
Size	9.7 mm x 140.7 mm			
Battery	1 x AAAA			
Buttons	2			
Included Software				
Hardware calibration tool	EXC3062RunCalibration.bat			
SCHURTER PCAP Analyzer	AnalyserTool.exe			
SCHURTER Sensitivity Tool	SensitivityTool.exe			

Approvals and Compliances

^{*} only on customer request

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.


Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimension [mm]







Designation	Bestellnummer
PCAP Touch Kit	1400.0402

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 1 Kit



Contents of the Design-In-Kit



Switches

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LCD Touch Panels category:

Click to view products by Schurter manufacturer:

Other Similar products are found below:

98-0003-2669-8 CABLE/RTP/USB 98-0003-2933-8 17-8041-226 17-8041-227 CABLE/RTP/RS232 N010-0557-T002 N010-0557-T011 LCDAL04-0430TL0NCNTBR1.0 TP01106W-4KB FTAS00-15AN-4 FTAS00-12.1AW-4A 17-8021-227 17-8031-205 17-8031-227 17-8091-226 17-8091-205 17-8421-205 17-8421-207 17-8441-205 17-8511-205 17-8541-205 17-8541-226 17-8891-227 17-8901-226 98-0003-2185-5 98-0003-2617-7 98-0003-2919-7 98-0003-2955-1 98-0003-3140-9 98-0003-3155-7 98-0003-3190-4 98-0003-3505-3 98-1100-0606-5 98-1100-0638-8 EA TOUCH240-4 N010-0519-T742 N010-0554-T043 N010-0554-T703 EA TOUCH102-1 EA TOUCH128-1 EA TOUCH128-2 EA TOUCH160-1 EA TOUCH240-3 LCD-OLINUXINO-10CTS TS-320240BRNO TS-TFT3.5Z FTAS00-104A5 FTAS00-104AS4 FTAS00-121A4