IEC Appliance Inlet with protection degree IP67 / IP69K, Screw-on Mounting front side, Solder or Quickconnect Terminal

with Cover (separate accessories)





See below:

Weblinks

Microsite, Video

Approvals and Compliances



Set consisting of appliance inlet and connector

pdf data sheet, html datasheet, General Product Information, Approvals,

Distributor-Stock-Check, Accessories, Detailed request for product,

4761 Connector black



Description

- Panel mount : Screw-on mounting front side
- Appliance Inlet, Pin temperature 120 °C, Protection class I
- Solder / Quick Connect
- Complete set consisting of appliance inlet and outlet
- Mating connector type: 4762

Unique Selling Proposition

- Waterproofed Appliance Inlet IP67 / IP69K
- Suitable for equipments in harsh environment
- Specific shape to ensure IP protection
- Version in Black and White

Technical Data

Technical Data			
Ratings IEC Ratings UL/CSA	10A / 250VAC; 50Hz 15A / 250VAC; 60Hz	Appliance inlet/-outlet	S16 acc. to IEC 60320-1, UL 60320-1, CSA C22.2 no. 60320-1
Dielectric Strength	> 1.5 kVAC between L-N > 1.5 kVAC between L/N-PE (1 min/50 Hz)		(For hot conditions) pin-temperature 120 °C, 10A, Protection Class I Shape of connector S16 is SCHURTER
Allowable Operation Temperature	-25°C to 120°C		specific
IP-Protection	front side IP67 acc. to IEC 60529 / IP69K acc. to ISO 20653		
Protection against electric shock	Suitable for appliances with protection class I acc. to IEC 61140		
Terminal	Solder / Quick Connect		
Panel Thickness S	Screw: max 6mm Mounting screw torque max 3Nm		
Material: Housing	Thermoplastic, black / white, UL 94V-0		

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 4761

Approval Logo	Certificates	Certification Body	Description
10	VDE Approvals	VDE	Certificate Number: 40044311
c FN us	UL Approvals	UL	UL File Number: E96454

GE Group

Product standards

General Use Receptacles, Attachment Plugs, and Similar Wiring Devices

Product standards that are referenced Organization Design Standard Description IEC 60320-1 Appliance couplers for household and similar general purposes Designed according to <u>IEC</u> ሠ Designed according to UL 60320-1 Standard for Attachment Plugs and Receptacles CSA C22.2 no. 60320-1

Application standards

Application standards where the product can be used

Designed according to


Organization	Design	Standard	Description
IEC	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements


Compliances


The product complies with following Guide Lines


	8		
Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
Halogen Free EE	Halogen Free	SCHURTER AG	SCHURTER strives to offer our customers halogen free products.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimensions [mm]









X: Quick-connect terminals 4.8x0.8 mm: 28.5 mm

X: Quick-connect terminals 6.3x0.8 mm: 31.0 mm

X: Solder terminals: 25.5 mm

1) Panel

2) Gasket or protection cover

All Variants

Appliance Inlet	Connector	Kit	Color	Terminals Inlet	Order Number
•		-	black	Quick connect terminals 4.8 x 0.8 mm	4312.0000
•		-	black	Quick connect terminals 6.3 x 0.8 mm	4312.0001
•		-	black	Solder terminals	4312.0002
٠	٠	1)	black	Quick connect terminals 4.8 x 0.8 mm	4312.0004
•	•	1)	black	Quick connect terminals 6.3 x 0.8 mm	4312.0005
•	•	1)	black	Solder terminals	4312.0006
•		-	white	Quick connect terminals 4.8 x 0.8 mm	4312.0007
٠		-	white	Quick connect terminals 6.3 x 0.8 mm	4312.0008
•		-	white	Solder terminals	4312.0009
٠	٠	1)	white	Quick connect terminals 4.8 x 0.8 mm	4312.0011
•	•	1)	white	Quick connect terminals 6.3 x 0.8 mm	4312.0012
•	•	1)	white	Solder terminals	4312.0013

1) complete set consisting of appliance inlet and outlet

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 10 Pcs

Accessories

Description



Protection cover Protection cover for waterproof appliance coupler 4761 / 4762

Mating Outlets/Connectors shuttered

Category / Description



Connector Overview complete

4762 Mounting: Power Cord, 3 x 1 $\,mm^2$ / 3 x 18 AWG, Cable, Connector: S15

4762

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Entry Modules category:

Click to view products by Schurter manufacturer:

Other Similar products are found below :

0098.0050 6167.0002 6609100-2 7-6609955-2 FKI2-50-6/M5 FN361-6-06 FN389-4-22 FN9226B-6-02 FN9233S1-10-06 FN9233S1-8-06 FN9233S1B-8-06 FN9233S1R-1-06 FN9233S1R-12-06 FN9233SB-1-06 FN9233SB-12-06 FN9233SB-8-06 FN9233SR-10-06 FN9244B-15-06HI FN9244EB-3-06 FN9244EB-8-06 FN9244ER-15-06 FN9244ER-8-06 FN9244ES1-8-06 FN9244ESB-8-06 FN9244R-12-06 FN9244S1-12-06 FN9244S1R-3-06 FN9244SB-8-06 FN9244SR-6-06 FN9244U-3-06 FN9244U-8-06 8-6609940-2 PE00SSSXB Fuse-H-EUR-1 Fuse-H-USA-1 PM00XD000 A-0701-HT-H 15EJMS8 1-6609941-2 200JM6-2 CA121003-6 SK-1015(F1-5) 161-R3015-E 1-6609153-2 FN323-1-05 FN9233B-8-06 FN9233EB-1-06 FN9233ES1R-10-06 FN9233R-12-06 FN9233S-10-06