EU Power Cord with IEC Appliance Connector C19, V-Lock





Volex C19

Power plug EU black





See below:

Approvals and Compliances

Description

- Power Cord
- Protection class I , Pin temperature 70 °C
- with V-Lock interlocking system

Weblinks

pdf data sheet, html datasheet, General Product Information, Approvals, CE declaration of conformity, Distributor-Stock-Check, Accessories, Detailed request for product

Technical Data

Ratings IEC	16 A / 250 VAC; 50/60 Hz
Dielectric Strength	> 2 kVDC between L-N
	> 2 kVAC between L/N-PE
	(1 min/50 Hz)
Allowable Operation Tempe-	-25°C to 70°C
rature	
IP-Protection	front side IP20 acc. to IEC 60529
Protection against electric	Suitable for appliances with protection
shock	class I acc. to IEC 61140
Terminal	moulded
Material: Housing	PVC, black

Appliance inlet/-outlet	C19 acc. to IEC 60320-3
	(for cold conditions) pin-temperature 70
	°C, 16A, Protection Class I

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
<u>IEC</u>	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
<u>IEC</u>	Designed according to	IEC 60320-3	Appliance couplers for household and similar general purposes
	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
ĀŞĀ	Designed according to	BS 1363-1	Socket-outlets, adapters and connection units

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
C€	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
5 0	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.
V -Lock		SCHURTER AG	V-Lock system are based on a matching plug-dose combination. The connector is equipped with a notch intended for use with the latching cordset. The cord latching system prevents against accidental removal of the cordset.

All Variants

Connec	tor	Cable				Plug					Order Number
Туре	V-Lock	Cord Type	Conductor cross section	Length [m]	Color	Туре	Country	Standard	Style		
C19	•	H05VV- F3G1.5	3 x 1.5 mm ²	3.0	black	Europlug	EU	CEE 7 / VII	angled	-	6051.2103

Most Popular.

A vailability for all products can be searched real-time: https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit	30 Pcs
----------------	--------

Mating Inlets/Plugs

Category / Description



Appliance Inlet Overview complete

1601, Mounting: Screw, Solder terminal straight, IP20, Appliance Inlet, C20	1601	
IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick Connect Terminal	1624	
IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder, Quick-connect or Screw Terminal	1621	



Power Entry Module Overview complete

IEC Appliance Inlet C20 with Circuit Breaker TA45	EF11
EC11, Mounting: Screw, Rocker switch: non-illuminated or illuminated 2-pole, Appliance Inlet IEC C20, Quick connecterminals 6.3×0.8 mm, prewired	EC11



Power Entry Module with line filter Overview complete

IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed)	EF12
--	------

Mating Inlets/Plugs shuttered



Appliance Inlet Overview complete

GSP4, Mounting: Screw, additional ground terminal IP20, Appliance Inlet, C20	GSP4	
1601, Mounting: Screw, Solder terminal straight, IP20, Appliance Inlet, C20	1601	
4793, Mounting: Snap-in, IP30, Appliance Inlet: IEC C20, Suitable for appliances with protection class I or II	4793	
IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick Connect Terminal	1624	
IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder, Quick-connect or Screw Terminal	1621	



IEC Inlet Filter Overview complete

IEC Appliance Inlet C20 with Filter, ECO design, front or rear side Mounting	5130
C20F, Mounting: Screw Front-/Rear-Side, Filter: Standard and Medical Version, Capacitor: X2, 16 A, Solder / quick connect / wires (strandard), prewired	C20F



Power Entry Module Overview complete

IEC Appliance Inlet C20 with Circuit Breaker TA45	EF11
EC11, Mounting: Screw, Rocker switch: non-illuminated or illuminated 2-pole, Appliance Inlet IEC C20, Quick connect terminals 6.3 x 0.8 mm, prewired	EC11



Power Entry Module with line filter Overview complete

IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed)	EF12	
--	------	--

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Leads category:

Click to view products by Schurter manufacturer:

Other Similar products are found below:

62500-1774 1300000023 312033-01 YP-61+YC12 P28818-M2 YP21A+YC13 FTP-629Y603 1702002600 1700001947 J2014004L001-CC SHELF IL13-EU1-H05-3100-300-S P28976-M45 BB-3271V86 W-98452 W-98453 MWOC-PCA-3-3-2 P29844-M5 P29844-M10 3-100-354 W-99245 W-99246 W-99249 W-99251 W-99252 W-99253 W-99254 W-99257 W-99260 W-99261 W-99262 W-99265 W-99267 W-99269 W-99270 W-99272 W-99280 W-99282 S144720002 S002020062 S007220315 S007220344 S007220303 S007220307 P28818-M6 1019123 387005324 59903000000 VL-0136-14-200 387007040 387006821