#### IEC Appliance Outlet D, insert Mounting, Solder Terminal



-	
D	
Õ	
70° C	

See below: Approvals and Compliances

#### Description

(

- Connector , Pin temperature 70  $^\circ\mathrm{C}$  , Protection class II - Solder terminal

Weblinks			
ndf data abaat	html detechent	Conorol Draduat Info	

pdf data sheet, html datasheet, General Product Information, Approvals, Distributor-Stock-Check, Accessories, Detailed request for product

Technical Data	
Ratings IEC	2.5 A / 250 VAC; 50 Hz
Ratings UL/CSA	2.5 A / 250 VAC; 60 Hz
	7 A / 125 VAC; 60 Hz
Dielectric Strength	> 4 kVAC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz)
Allowable Operation Tempe- rature	-25 °C to 70 °C
IP-Protection	front side IP20 acc. to IEC 60529
Protection against electric shock	Suitable for appliances with protection class II acc. to IEC 61140
Terminal	Solder terminal straight
Material: Housing	PA6, black, UL 94V-0

#### **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

#### Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 5086

Approval Logo	Certificates	Certification Body	Description
	VDE Approvals	VDE	VDE Certificate Number: 40034348
c FLL <sup>®</sup> us	UL Approvals	UL	UL File Number: E103791

#### **Product standards**

Product standards that are referenced

Organization	Design	Standard	Description
IEC	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
IEC.	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
(UL)	Designed according to	UL 60320-1	Standard for Attachment Plugs and Receptacles
CSA Group	Designed according to	CSA C22.2 no. 60320-1	General Use Receptacles, Attachment Plugs, and Similar Wiring Devices

5086

# 5086

### **Application standards**

Application standards where the product can be used


Organization	Design	Standard	Description
IEC	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements

### Compliances

The product complies with following Guide Lines

- [ ]	<b>J</b>		
Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
<b>©</b>	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

# **Dimensions** [mm]





Length of the terminal please find at the order code configuration table

# Config. Code

# 5086 - H - A B C 0- D - E

The characters are placeholders for the correspondingly keys of selections from the key tables.

# 5086 - **H** - A B C 0- D - E = Type

Туре	Configuration key
protection class II	Х

# 5086 - H - A B C 0- D - E = Terminals

Terminal L	Configuration key
solder terminal	1



Terminal N	Configuration key
solder terminal	1
Symbols similar as in table A	
5086 - H - A B <b>C</b> 0- D - E <b>= Terminals</b>	
Towning! Country	Configuration

18.2<sup>+0.2</sup>

#### Terminal Ground Configuration key without terminal 0 Symbols similar as in table A

5086 - H - A B C 0- **D** - E = Color

Color		Configuration key	5086 - H - A B C 0- D - <b>E</b> = St	yle	
Black		A	Style		Configuration key
			insert type		5
All Variants					
Terminals L / N	Color	Style	Config. Code	Order Number	
solder terminal	black	-	5086-X-1100-A-5	6180.0006	
The listed variants should be available	able from stock. Other version	s on request www.schu	rter.com/contact		
Availability for all products can be Packaging unit	searched real-time:https://ww	w.schurter.com/en/Stock	<-Check/Stock-Check-SCHURTER		
Accessories	Description				
C. B. Par In In.	Wire Harness Wire harness for SCHURTER pro	ducts			

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Entry Modules category:

Click to view products by Schurter manufacturer:

Other Similar products are found below :

0098.0050 6167.0002 6609100-2 7-6609955-2 FKI2-50-6/M5 FN361-6-06 FN389-4-22 FN9226B-6-02 FN9233S1-10-06 FN9233S1-8-06 FN9233S1B-8-06 FN9233S1R-1-06 FN9233S1R-12-06 FN9233SB-1-06 FN9233SB-12-06 FN9233SB-8-06 FN9233SR-10-06 FN9244B-15-06HI FN9244EB-3-06 FN9244EB-8-06 FN9244ER-15-06 FN9244ER-8-06 FN9244ES1-8-06 FN9244ESB-8-06 FN9244R-12-06 FN9244S1-12-06 FN9244S1R-3-06 FN9244SB-8-06 FN9244SR-6-06 FN9244U-3-06 FN9244U-8-06 8-6609940-2 PE00SSSXB Fuse-H-EUR-1 Fuse-H-USA-1 PM00XD000 A-0701-HT-H 15EJMS8 1-6609941-2 200JM6-2 CA121003-6 SK-1015(F1-5) 161-R3015-E 1-6609153-2 FN323-1-05 FN9233B-8-06 FN9233EB-1-06 FN9233ES1R-10-06 FN9233R-12-06 FN9233S-10-06