Shock-Safe Fuseholder, 4.7 x 16 mm, Fingergrip, Rear-Side



250 VAC · 1W/5A

See below:

Approvals and Compliances

Description

- Screw type fuse carrier

References

Last order date: 30.04.2021

Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product, Microsite

Tec	hnical	Data

Fuse-Link	4.7 x 16mm	
Mounting	Panel mount, Rear Side	
Attachment	Fixing Nut	
Terminal	Solder	
Rated Voltage	250 VAC	
Rated current	5A	
Rated Power Acceptance IEC	1W / 5A @ Ta 23°C	
Degree of Protection	IP67	
Protection Class	Suitable for appliances with protection class I or II acc. to IEC 61140	
Admissible Ambient Air Temp.	-40 °C to 85 °C	
Climatic Category	40/085/21 acc. to IEC 60068-1	
Material: Socket	Thermoset, black	
Unit Weight	8.2 g	
Storage Conditions	0°C to 60°C, max. 70% r.h.	
Product Marking	Туре	

Soldering Methods	Iron
	Soldering Profile
Contact Resistance	$<$ m Ω at 100 mA
Resistance to Vibration	acc. to NF C 20-706 / IEC 60068-2-6, test Fc
Shocks	acc. to NF C 20-706 / IEC 60068-2-27
Bumps	acc. to NF C 20-729 / IEC 60068-2-29
Salt Mist	acc. to NF C 20-711 / IEC 60068-2-11
Dump Heat	acc. to NF C 20-604
Climatic Composite	acc. to NF C 20-619 Phase D
Admissible Torque on Fixing	max 0.7 Nm
Nut	
Panel Thickness	max 2 mm

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type:

Approval Logo Certificates Certification Body Description

GAM

NNO

Application standards

Application standards where the product can be used

Organization Design Standard Description


Designed for applications acc. IEC/UL 62368-1 Audio/video, information and communication technology equipment - Part 1: Safety requirements


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
C€		SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
50	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimension [mm] 33.5 mm





Mounting holes

All Variants

	Сар	Degree of Pro- tection	Order Number
•	Fingergrip	IP67	7090.6020

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packa	1 uii iu	UHH
	~99	• • • • • •

Bulk (10 pcs.)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Schurter manufacturer:

Other Similar products are found below:

570-290-741P40 570-290-751P40 020417G 020418E 6R30A1B F600A3B 80910030 8601.2020 G15A2SPQ 9-3557-GP REV A HDJ-B R6J30A3S HFH-1 RF30A1S RF30A2B RF30A3SP 15600-08-10 BK/FHN19G BK/HHM BK/HKP-CCHH BK/HKP-JJ BK/HTJ-LES-FUSE HMG-241 HTJ-LES-FUSE C4044-1 2086-1 2193 2602 2650 178.000100 FHN31G1 T30A2B G4PB8 2660 2799 CQ-209V HKP-CCHH R6F30A2S 341001A 345621A CVRMCC 4202 4407 4408 4413 4423 4532 4537 TSD1404-12 BK/FHN31G1