Shock-Safe Fuseholder, 10.3 x 38 mm, Fingergrip



600 VAC · 4.5 W/25 A25 A (UL/CSA)

See below:

Approvals and Compliances

Description

- Screw type fuse carrier

References

Last order date: 30.09.2021

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product, Microsite

Technical Data

Fuse-Link	10.3 x 38 mm			
Mounting	Panel mount, Front Side			
Terminal	Quick-Connect 6.3 x 0.8 mm			
Rated Voltage	600 VAC			
Rated current	25 A (UL/CSA)			
Rated Power Acceptance IEC	4.5W / 25A @ Ta 23°C			
Degree of Protection	IP40 / IP67			
Admissible Ambient Air Temp.	-40 °C to 85 °C			
Climatic Category	40/085/21 acc. to IEC 60068-1			
Material: Socket	Thermoset, black			
Unit Weight	48 g			
Storage Conditions	0°C to 60°C, max. 70% r.h.			
Product Marking	Type, Rated Voltage, Rated current			

Soldering Methods	Iron Soldering Profile
Contact Resistance	$<$ m Ω at 100 mA
Panel Thickness	max 4mm

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

NNO

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 23530P

Approval Logo	Certificates	Certification Body	Description
#	UL Approvals	UL	UL File Number: E41738
®	CSA Approvals	CSA	CSA Certification Record: 23151

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	UL 4248-1	Industrial Control Equipment



Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
C€		SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
5 0	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimension [mm] 63 mm





Mounting holes

All Variants

Holder	Сар	Degree of Pro- tection	71 ° (F	NN() Reference	Order Number
•	Fingergrip	IP40	• •	•	23530P	7093.2510
•	Fingergrip	IP67		•	23530JJP	7093.2540

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging Unit	Bulk (10 pcs.)
----------------	----------------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Schurter manufacturer:

Other Similar products are found below:

570-290-741P40 570-290-751P40 020417G 020418E 6R30A1B F600A3B 80910030 8601.2020 G15A2SPQ 9-3557-GP REV A HDJ-B R6J30A3S HFH-1 RF30A2B RF30A3SP 15600-08-10 BK/FHN19G BK/HHM BK/HKP-CCHH BK/HKP-JJ BK/HTJ-LES-FUSE HMG-241 HTJ-LES-FUSE C4044-1 2086-1 2193 2602 2650 178.000100 FHN31G1 T30A2B G4PB8 2660 2799 CQ-209V HKP-CCHH R6F30A2S 341001A 345621A CVRMCC 4202 4407 4408 4413 4423 4532 4537 TSD1404-12 BK/FHN31G1 BK/HC-5