Clip, 5 x 20 mm, Version 2



250 VAC		See below: Approvals and Compliance	ces	
Description - Through hole mounting		The state of the s	Weblinks pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product, Microsite	
Technical Data				
Fuse-Link	5 x 20 mm	Soldering Methods	Wave	
Mounting	PCB		Soldering Profile	
Terminal	Solder THT	Solderability	235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1	
Rated Voltage	250 VAC			
Rated current	6.3A	Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A	
Degree of Protection	IP00			
Material: Terminals	see variants	Solderability	235°C / 2 sec acc. to IEC 60068-2-20,	
Unit Weight	0.7 g		Test Ta, method 1	
Storage Conditions	0°C to 60°C, max. 70% r.h.	Contact Resistance	$<$ m $\Omega$ at 100 mA	
Product Marking	none			

## **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## **Application standards**

Application standards where the product can be used

Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements


#### Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
C€	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
<b>50</b>	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

# Dimension [mm]







## Drilling diagram

#### **All Variants**

Clip	Terminal	Material: Terminals	Order Number
•	straight	Tin-Plated Bronze	7141.2001

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

**Packaging Unit** 

Bulk (100 pcs.)

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Clips category:

Click to view products by Schurter manufacturer:

Other Similar products are found below:

5960-64 659524 707190 124472H BK/4222 BK/4861-01 1A5600 JN1 1A1310-05 1A5940 4121 4207 4861-01 BK/1A5778 BK/1A5779 BK1A5780 BK/5682-02 4180 3561TR 1A5780 9483 1A3400-12-R 3519 KEYSTONE 01230001Z 01000057H 01020071Z 01250001Z 05200001N 0LCC6 5960-09 BK-1A5601-01 8040.0001 01000058Z 01220087Z 01020079Z 01050002Z 01070002Z 01210002Z BK/1A1119-05 FC -102 bright tin FC -211 bright tin 3511 3515 3517 3520 3522 3529 3532 3533 3534