


R13-205



Rating	
20A 125V AC	1/3HP 125V AC
16A 250V AC	1/2HP 250V AC
Contact resistance	
50mΩ Max	
Insulation resistance	
DC 500V 100MΩ Min	
Dielectric strength	
AC 1500V 1 minute	
Cut-out	

FEATURES

- * MATERIAL: Frame is nylon (UL flame: 94V-2). Terminals are silver plated brass.
- * Illuminated actuators are molded in PC, available with red, amber, green, blue and white colors.
- * Snap-in mounting, easy to install switch into panel.
- * Rocker "Z" is only available for non-illuminated function.

	X	Y
1.75-3.0	27.5-0.1	13.8-0.1
3.0-4.0	27.5-0.1	13.8-0.1
4.0-5.0	28.0-0.1	13.8-0.1

Ordering number instruction

R13-205

FUNCTION

Different button (按鈕不同)



Illuminated / Different button (帶燈/按鈕不同)



Momentary / Illuminated / Different button (彈回/帶燈/按鈕不同)



Different position (動作特性不同)



Momentary (彈回)



Independent circuit (獨立通路)



TERMINAL

0 1		.250" SQ
0 5		SO

ROCKER



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [SCI manufacturer](#):

Other Similar products are found below :

[1038215](#) [A13-106A](#) [A13-122-3](#) [A13-122-3B](#) [A13-123](#) [A13-142-15](#) [A13-142-16](#) [A13-142194BHD-BB3](#) [A13-142194BPD-BB3](#) [A13-142-8](#)
[A13-142A](#) [A13-142AP-BB3](#) [A13-142HS](#) [A13-144DA251BHD-BB3](#) [A13-147](#) [A13-150B](#) [A13-150C](#) [A13-150D](#) [A13-165-1](#) [A13-194A-BB3](#)
[A13-194APS-BB3](#) [A13-194B2-BB3](#) [A13-194B2PS-BB3](#) [A13-194B-BB3](#) [A13-194BPS-BB3](#) [A13-204A-BB3](#) [A13-204B-BB3](#) [A13-208](#)
[A13-216DDP](#) [A13-216DTP](#) [A13-224A142C2-BB3](#) [A13-226194B2](#) [A13-22665A](#) [A13-230AU-BB3](#) [A13-236AU-BB3](#) [A13-23A](#) [A13-26A](#)
[A13-26B](#) [A13-26B23A2-J7Z](#) [A13-39](#) [A13-40A23A1](#) [A13-53](#) [A13-65A](#) [A13-65B](#) [A13-75A24A1-A3Z](#) [A13-75A30A2-A7Z](#) [A2-19-14-A1](#)
[A2-19-14-A2](#) [A25-1B-BB3-R](#) [A25-1BHS-BB3-R](#)