

Grove - Servo

Release date: 9/20/2015

Version: 1.0

Wiki: http://www.seeedstudio.com/wiki/Grove - Servo

Bazaar: http://www.seeedstudio.com/depot/Grove-Servo-p-1241.html



Document Revision History

Revision	Date	Author	Description			
1.0	Sep 21, 2015	Victor.He	Create file			



Contents

Do	cument Revision History·····	2
1.	Introduction ·····	2
2.	Features	3
3.	Specifications ·····	4
4.	Usage·····	5
5.	Support	···· 6



Disclaimer

For physical injuries and possessions loss caused by those reasons which are not related to product quality, such as operating without following manual guide, natural disasters or force majeure, we take no responsibility for that.

Under the supervision of Seeed Technology Inc., this manual has been compiled and published which covered the latest product description and specification. The content of this manual is subject to change without notice.

Copyright

The design of this product (including software) and its accessories is under tutelage of laws. Any action to violate relevant right of our product will be penalized through law. Please consciously observe relevant local laws in the use of this product.



1. Introduction

Grove - Servo is DC motor with gearing and feedback system. It is used in driving mechanism of robots. The module is a bonus product for Grove lovers. We regulated the three-wire servo into a Grove standard connector. You can plug and play it as a typical Grove module now, without jumper wires clutter. But if you feel more like a proto servo, check out EMAX 9g ES08A High Sensitive Mini Servo. They are the same model, both of good quality and burden-free price.





2. Features

- Small module
- Grove Compatible Interface
- Easy to use



3. Specifications

Item	Min	Typical	Max	Unit
Working Voltage	4.8	5.0	6.0	V
Torque	1.5/1.8			Kg.cm
Speed	0.12/0.16			s/60°
Size	32X11.5X24			mm
Weight	8.5			Gram




4. Usage

The Servo has three wires: power, ground, and signal. The power wire is typically red, and should be connected to the 5V pin on the Arduino/Seeeduino board. The ground wire is typically black or brown and should be connected to a ground pin on the Arduino board. The signal pin is typically yellow, orange or white and should be connected to Digital 9 on the Arduino board. You can change to the digital port as you like. But don't forget to change the port number in the definition of the demo code at the same time.

Next sweeps the shaft of a servo back and forth across 180 degrees. This example makes use of the Arduino servo library.

- Connect the Servo to Seeeduino and connect Seeeduino to PC using a USB cable.
- Restart the Arduino IDE, open one demo code you like, for example Sweep directly by the path:File -> Example ->Servo->Sweep.



• Upload the code.Please click <u>here</u> if you do not know how to upload.



5. Support

If you have questions or other better design ideas, you can go to our <u>forum</u> or <u>wish</u> to discuss.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Seeed Studio Accessories category:

Click to view products by Seeed Studio manufacturer:

Other Similar products are found below:

101990565 1019	90564 101020003	101020004	101020025	101020028	101020038	101020058	101020472	101020580	101990029
101990058 1019	90061 101990065	102020143	102070002	102070004	102070007	102070008	102070011	102991175	102991176
103010002 1030	20005 103020007	103020008	103020010	103020012	103020030	103020133	103020135	103020136	103020137
103020252 10302	20272 103030005	103030009	103030075	103030275	103030276	103030335	103100063	103990183	103990445
104020006 10402	20048 104020108	104020109	104030001	104030009					