



Visit our
Web site
<http://www.sefram.fr>

MW 3350, 3355, 3360, 3365, 3380, 3390, 3395

A NEW DESIGN TO PROVIDE MORE SAFETY FOR ALL YOUR NEEDS.

Safety, Accuracy, Easy to use

Thanks to the new design of safety, the new SEFRAM clamp on multimeter will answer to all your problems.

- New Slim design : ergonomically designed slim shape with one hand operated knob and button. Just fit the palm of your hand hand your needs.
- Safety : IEC 1010 cat IV 600 V for the model MW 3380, MW 3390 and MW 3395.
- Full jaw
- Maximum opening jaw up to 53 mm
- Up to 1500 A measurements for MW3390 / MW3395
- TRMS AC measurements for MW 3355, MW3365 and MW 3395



MW 3395
MW 3390
MW 3380

MW 3360
MW 3365

MW 3350
MW 3355

TRMS AC

TRMS AC

TRMS AC

Performances	MW 3350	MW 3355	MW 3360	MW 3365	MW 3380	MW 3390	MW 3395
Opening jaw	37 mm	37 mm	45 mm	45 mm	53 mm	53 mm	53 mm
Display with backlight	4000 Counts	4000 Counts	4000 Counts	4000 Counts	4000 Counts	4000 Counts	4000Counts
I max. AC	600 A	600 A	600 A	600 A	1000 A	1500 A	1500 A
I max. DC	-	-	600 A	600 A	-	1500 A	1500 A
V max. AC	600 V	600 V	600 V	600 V	750 V	750 V	750 V
V max. DC	600 V	600 V	600 V	600 V	1000 V	1000 V	1000 V
Resistance	yes	yes	yes	yes	yes	yes	yes
Buzzer	yes	yes	yes	yes	yes	yes	yes
Frequencemeter	yes	yes	yes	yes	yes	yes	yes
HOLD, MIN, MAX, PEAK HOLD	yes	yes	yes	yes	yes	yes	yes
Auto power off	yes	yes	yes	yes	yes	yes	yes
Safety	CAT III 600 V CAT II 1000 V	CAT III 600 V CAT II 1000 V	CAT III 600 V CAT II 1000 V	CAT III 600 V CAT II 1000 V	CAT IV 600 V CAT III 1000 V	CAT IV 600 V CAT III 1000 V	CAT IV 600 V CAT III 1000 V



Technical specifications	MW 3350 MW 3355	MW 3360 MW 3365	MW 3380	MW 3390 MW 3395
IAC	400 A / 600 A	400 A / 600 A	400 A / 1000 A	400 A / 1500 A
Accuracy	± (1,9% + 5d)	± (1,9% + 5d)	± (1,9% + 5d)	± (1,9% + 5d)
Resolution	100 mA	100 mA	100 mA	100 mA
Overload protection	660 A	660 A	1100 A	1500 A
IDC	-	400 A / 600 A	-	400 A / 1500 A
Accuracy	-	± (1,5% + 5d)	-	± (1,9% + 3d)
Resolution	-	100 mA	-	100 mA
Overload protection	-	660 A	-	1500 A
VAC	400 V/ 600 V	400 V/600 V	400 V/750 V	400 V/750 V
Accuracy	± (1% + 5d)	± (1% + 5d)	± (1% + 5d)	± (1% + 5d)
Resolution	100 mV	100 mV	100 mV	100 mV
Protection				
VDC	400 V/ 600 V	400 V/600 V	400 V/1000 V	400 V/1000 V
Accuracy	± (0,7% + 2d)	± (0,7% + 2d)	± (0,7% + 2d)	± (0,7% + 2d)
Resolution	100 mV	100 mV	100 mV	100 mV
Protection				
Resistance	400 Ω	400 Ω	400 Ω	400 Ω
Accuracy	± (1% + 3d)	± (1% + 3d)	± (1% + 3d)	± (1% + 3d)
Resolution	0,1 Ω	0,1 Ω	0,1 Ω	0,1 Ω
Protection				
Continuity test with buzzer	yes for R≤ 30Ω	yes for R≤ 30Ω	yes for R≤ 30Ω	yes for R≤ 30Ω
True RMS AC reading	yes for 3355	yes for 3365	-	yes for 3395
Frequency counter	4KHz/10KHz	4KHz/10KHz	4KHz/10KHz	4KHz/10KHz
Accuracy	± (0,1% + 2d)	± (0,1% + 2d)	± (0,1% + 2d)	± (0,1% + 2d)
Resolution	1Hz	1Hz	1Hz	1Hz

General specifications	MW 3350 MW 3355	MW 3360 MW 3365	MW 3380	MW 3390 MW 3395
Specification				
Display with backlight	4000 Counts	4000 Counts	4000 Counts	4000 Counts
Curve analogue bargraph	yes	yes	yes	yes
Opening jaw	37 mm	45 mm	53 mm	53 mm
MIN/MAX, HOLD	yes	yes	yes	yes
PEAK HOLD (10ms)	yes	yes	yes	yes
Overload indication	yes, display "OL"	yes, display "OL"	yes, display "OL"	yes, display "OL"
Low battery indication	yes with symbol	yes with symbol	yes with symbol	yes with symbol
Sampling rate	2 mes. / s.	2 mes. / s.	2 mes. / s.	2 mes. / s.
Auto power off	yes	yes	yes	yes
Operating mode				
Security CEI 1010	CAT III 600 V	CAT III 600 V	CAT IV 600 V	CAT IV 600 V
Operating temperature	0° to 50° C	0° to 50° C	0° to 50° C	0° to 50° C
Storage temperature	-20° to 60° C	-20° to 60° C	-20° to 60° C	-20° to 60° C
Temperature coefficient	0,2 x (spec.Acc'y)/° C, < 18°C or> 28° C	0,2 x (spec.Acc'y)/° C, < 18°C or> 28° C	0,2 x (spec.Acc'y)/° C, < 18°C or> 28° C	0,2 x (spec.Acc'y)/° C, < 18°C or> 28° C
Power requirement*	AAA size 1,5 V	AAA size 1,5 V	AAA size 1,5 V	AAA size 1,5 V
Battery life	300 h with alkaline battery	300 h with alkaline battery	300 h with alkaline battery	300 h with alkaline battery
Max. diameter of cable	34 mm	35 mm	51 mm	51 mm
Dimensions, weight				
Dimension	76x220x50mm	72x235x51mm	90x275x51mm	90x275x51mm
Weight (with battery)	360g	380g	420g	420g

Deliver with : One set of test leads (SA 103), carrying pouch, battery and user manual

* Alkaline Battery to be used



Specification subject to change without notice - FTMW3350 A/01



32, rue Edouard Martel - BP55- 42009 - St Etienne - cedex 2
Tél. +33 (0) 4.77.59.01.01
 Fax. +33 (0) 4.77.57.23.23
 Web : www.sefram.fr - e-mail : sales@sefram.fr

Partenaire Distributeur



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Clamp Multimeters & Accessories](#) category:

Click to view products by [Sefram](#) manufacturer:

Other Similar products are found below :

[I800](#) [1000-304](#) [TESTO 770-3 0590 7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM197](#) [UT204](#) [KEW2210R](#) [FLUKE 80I-110S](#) [FLUKE A3002FC](#) [FLUKE I200](#) [FLUKE I200S](#) [FLUKE I310S](#) [FLUKE I400](#) [TESTO 770-2 0590 7702](#) [KEW2433R](#) [KEW8112](#) [FLUKE 772](#) [MA440](#) [MA443](#) [MA445](#) [FLUKE-374 FC](#) [FLUKE-1630-2FC](#) [CM42](#) [FLUKE-376 FC](#) [A193 \(800 MM\)](#) [F201](#) [F205](#) [F65](#) [DIGIFLEX 4000A 350MM](#) [DIGIFLEX 400A 250MM](#) [FLUKE A3001FC](#) [FLUKE I6000SFLEX-24](#) [KEW2010](#) [P1670](#) [UT203](#) [FLK-A3004FC](#) [AMP-330-EUR](#) [APPA SFLEX-18D](#) [UT200A](#) [UT201](#) [UT205](#) [UT205A](#) [UT206](#) [UT206A](#) [UT210A](#) [UT210B](#) [UT213A](#)