

Sefram

NEW

MW3950B

True RMS Leakage Clamp Meter Powerful, Precise and Wireless

Bluetooth

TRMS AC

Specifications :

- LCD 6000 counts with backlight
- Current measurement up to 60A AC
- Minimum resolution : 1 μ A
- Low pass filter
- Maximum Jaw Opening : 42mm
- High Frequency Rejection (selectable : 50Hz, 60Hz & 1kHz)
- True RMS reading
- Manual and Automatic range
- Max, Min and HOLD functions
- Bluetooth® interface to save reading values
- Torch light

A connected device

With its Bluetooth® interface and its application dedicated to tablets or smartphones (Android or ios), you can monitor your measurements and record them in real time. Then export the data via the tablet or the smartphone in .csv file in order to be able to process them in a spreadsheet software.



Follow us on :



Visit our website: www.sefram.com

True RMS Leakage Clamp Meter

Specifications		MW3950B
Electrical Specifications		
AC Current		
Range		6 mA to 60 A
Accuracy		±(2% + 5dgt)
Resolution		1 µA
Minimal measured current		10 µA
Positioning error		±1% of reading
Bandwith		15 Hz to 10 kHz
AC Current with Low Pass Filter (50-60Hz)		
Range		6 mA to 60 A
Accuracy		±(1% + 5dgt)
Resolution		1 µA
Minimal measured current		10 µA
Positioning error		±1% of reading
Bandwith		30 Hz to 60 Hz
Cut-off Frequency		200 Hz
AC Current with Low Pass Filter (1kHz)		
Range		6 mA to 60 A
Accuracy		±(1% + 5dgt)
Resolution		1 µA
Minimal measured current		10 µA
Positioning error		±1% of reading
Bandwith		30 Hz to 200 Hz
Cut-off Frequency		1 kHz
Functions		Min, Max and HOLD
General Specifications		
Display		LCD with backlight
Counts		6000 counts
Overload display		OL
Max conductor size		40 mm
Measuring rate		up to 5 measurement per sec.
Interface		Bluetooth® (Bluetooth® Low Energy 4.0, Effective range: Open air 10m)
Temperature of use		-10°C to 50°C
Humidity		between 45% and 80% (check in manual)
Storage temperature		-20°C to 60°C (without batteries), HR < 80%
Security		600V - CAT III
Standards		IEC/EN 61010-1, EN 61010-2-032
Battery type		2 Batteries, IEC LR6, Alkaline (AA) Battery life: Alkaline 60 hours
Auto Power Off		after 20 minutes
Dimensions		100 x 230 x 24 mm
Weight (without batteries)		500 g

Supplied with : carrying pouch, manual and batteries.

For assistance and ordering



32, rue Edouard Martel - BP55- 42009 - St Etienne - cedex 2
 Tél. +33 (0) 4.77.59.01.01 / Fax. +33 (0) 4.77.57.23.23
 Web : www.sefram.fr - e-mail : sales@sefram.fr



FT-MW3950B A 00 - Specifications can be updated without notice



Visit our website: www.sefram.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Clamp Multimeters & Accessories](#) category:

Click to view products by [Sefram](#) manufacturer:

Other Similar products are found below :

[I800](#) [1000-304](#) [TESTO 770-3](#) [0590 7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM197](#) [UT204](#) [KEW2210R](#) [FLUKE 80I-110S](#) [FLUKE A3002FC](#) [FLUKE I200](#) [FLUKE I200S](#) [FLUKE I310S](#) [FLUKE I400](#) [TESTO 770-2](#) [0590 7702](#) [KEW2433R](#) [KEW8112](#) [FLUKE 772](#) [MA440](#) [MA443](#) [MA445](#) [FLUKE-374 FC](#) [FLUKE-1630-2FC](#) [CM42](#) [FLUKE-376 FC](#) [A193 \(800 MM\)](#) [F201](#) [F205](#) [F65](#) [DIGIFLEX 4000A 350MM](#) [DIGIFLEX 400A 250MM](#) [FLUKE A3001FC](#) [FLUKE I6000SFLEX-24](#) [KEW2010](#) [P1670](#) [UT203](#) [FLK-A3004FC](#) [AMP-330-EUR](#) [APPA SFLEX-18D](#) [UT200A](#) [UT201](#) [UT205](#) [UT205A](#) [UT206](#) [UT206A](#) [UT210A](#) [UT210B](#) [UT213A](#)