SKKD 380



SEMIPACK® 3

Rectifier Diode Modules

SKKD 380

Features


- Heat transfer through aluminium nitride ceramic isolated metal baseplate
- Precisious metal pressure contacts for high reliability
- UL recognized, file no. E 63 532


Typical Applications*


- Uncontrolled rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors


V _{RSM}	V_{RRM}	I _{FRMS} = 600 A (maximum value for continuous operation)		
V	V	I _{FAV} = 380 A (sin. 180; T _c = 100 °C)		
900	800	SKKD 380/08		
1300	1200	SKKD 380/12		
1700	1600	SKKD 380/16		
1900	1800	SKKD 380/18		
2100	2000	SKKD 380/20H4		
2300	2200	SKKD 380/22H4		


Symbol	Conditions	Values	Units
I _{FAV}	sin. 180; T _c = 100 °C	380	Α
I _{FSM}	T _{vi} = 25 °C; 10 ms	11000	Α
	T _{vi} = 150 °C; 10 ms	10000	Α
i²t	T _{vi} = 25 °C; 8,3 10 ms	605000	A²s
	T _{vj} = 150 °C; 8,3 10 ms	500000	A²s
V _F	T _{vi} = 25 °C; I _F = 1000 A	max. 1,25	V
$V_{(TO)}$	T _{vi} = 150 °C	max. 0,8	V
r _T	T _{vj} = 150 °C	max. 0,35	mΩ
I_{RD}	T_{vj} = 150 °C; $V_{RD} = V_{RRM}$	max. 10	mA
R _{th(j-c)}	cont. per diode / per module	0,11 / 0,055	K/W
3 3,	sin. 180 per diode / per module	0,116 / 0,058	K/W
$R_{th(c-s)}$	per diode / per module	0,04 / 0,02	K/W
T _{vi}		- 40 + 150	°C
T _{stg}		- 40 + 130	°C
V _{isol}	a. c. 50 Hz; r.m.s.; 1 s / 1 min.	3600 / 3000	V~
V _{isol}	a. c. 50 Hz; r.m.s.; 1 s / 1 min. for SKKH4	4800 / 4000	V~
M _s	to heatsink	5 ± 15 %	Nm
M _t	to terminals	9 ± 15 %	Nm
a		5 * 9,81	m/s²
m	approx.	600	g
Case		A 78b	





















SKKD 380









^{*} The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our staff.

4 09-03-2011 SEI © by SEMIKRON

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by Semikron manufacturer:

Other Similar products are found below:

CUS06(TE85L,Q,M) D1FH3-5063 MBR0530L-TP MBR10100CT-BP MBR30H100MFST1G MMBD301M3T5G PMAD1103-LF
PMAD1108-LF RB160M-50TR RB520S-30 RB551V-30 DD350N18K DZ435N40K DZ600N16K BAS16E6433HTMA1 BAS 3010S02LRH E6327 BAT 54-02LRH E6327 IDL02G65C5XUMA1 NSR05F40QNXT5G JANS1N6640 SB07-03C-TB-H SB1003M3-TL-W
SBAT54CWT1G SBM30-03-TR-E SK32A-LTP SK33A-TP SK34A-TP SK34B-TP SMD1200PL-TP ACDBN160-HF SS3003CH-TL-E
STPS30S45CW PDS3100Q-7 GA01SHT18 CRS10I30A(TE85L,QM MBR1240MFST1G MBRB30H30CT-1G BAS28E6433HTMA1 BAS
70-02L E6327 HSB123JTR-E JANTX1N5712-1 VS-STPS40L45CW-N3 DD350N12K SB007-03C-TB-E SB10015M-TL-E SB1003M3-TL-E
SK110-LTP SK154-TP SK32A-TP SK33B-TP