


#### **Features**

- 70Watts peak pulse power (tp = 8/20µs)
- Tiny DFN0603 package
- Bidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping voltage
- Low leakage current
- Medium capacitance (CJ=15pF typ.)
- Protection one data/power line to: IEC 61000-4-2 ±30kV contact ±30kV air IEC 61000-4-4 (EFT) 40A (5/50ns) IEC 61000-4-5 (Lightning) 6A (8/20µs)
- RoHS compliant


## **Applications**

- Audio Line, Speaker, Headset, Microphone Protection
- Human Interface Devices (Keyboard, Touchpad, Buttons)

#### SES5VD0603SY-2B



**DFN0603** 



**Schematic Diagram** 

### **Absolute Maximum Ratings**

( $T_A$ =25°C, Unless otherwise specified.)

| Parameter                                 | Symbol           | Value       | Unit       |
|---|------------------|-------------|------------|
| Peak Pulse Power (T <sub>P</sub> =8/20µS) | P <sub>PP</sub>  | 70          | W          |
| ESD contact/air discharge (IEC-61000-4-2) | V <sub>ESD</sub> | 30          | kV         |
| Peak Pulse Current ( t₂ = 8/20µS )        | I <sub>PP</sub>  | 6           | Α          |
| Junction Temperature                      | TJ               | -55 to +125 | $^{\circ}$ |
| Storage temperature                       | T <sub>STG</sub> | -55 to +150 | $^{\circ}$ |

#### **Electrical Characteristics**

 $(T_A=25^{\circ}C, Unless otherwise specified.)$ 

| Parameter                         | Symbol         | Condition                  | Min | Тур  | Max | Unit |
|-----------------------------------|----------------|----------------------------|-----|------|-----|------|
| Reverse stand-off Voltage         | $V_{RWM}$      |                            |     |      | 5.0 | V    |
| Reverse Breakdown Voltage         | $V_{BR}$       | I <sub>T</sub> =1mA        | 5.6 | 6.5  |     | V    |
| Reverse Leakage Current           | I <sub>R</sub> | V <sub>R</sub> =5.0V       |     | 5    | 100 | nA   |
| Clarening Valtage (IEC C1000 4 5) | V <sub>C</sub> | I <sub>PP</sub> =1A        |     | 7.8  |     | V    |
| Clamping Voltage (IEC 61000-4-5)  |                | I <sub>PP</sub> =6A        |     | 10.2 | 12  | V    |
| Trigger Voltage (IEC 61000-4-2)   | V <sub>T</sub> | V <sub>ESD</sub> =8kV      |     | 70   |     | V    |
| Clamping Voltage (IEC 61000-4-2)  | Vc             | V <sub>ESD</sub> =8kV      |     | 10   |     | V    |
| Junction Capacitance              | CJ             | V <sub>R</sub> =0V, f=1MHz |     | 15   |     | pF   |



# **Typical Characteristic Curves**

Fig.1 Peak Pulse Power Rating Curve




Fig.2 Pulse Derating Curve




Fig.3 Pulse Waveform-8/20µs







Fig.4 Pulse Waveform-ESD(IEC61000-4-2)



### **Product Dimensions**





| Cumbal | Dimensions in millimeters |       |       |  |
|--------|---------------------------|-------|-------|--|
| Symbol | Min                       | Nom   | Max   |  |
| Α      | 0.23                      | -     | 0.33  |  |
| A1     | 0.00                      | ı     | 0.05  |  |
| A3     | 0.102 REF                 |       |       |  |
| D      | 0.55                      | 0.60  | 0.65  |  |
| Е      | 0.25                      | 0.30  | 0.35  |  |
| b      | 0.215                     | 0.245 | 0.275 |  |
| L      | 0.13                      | 0.18  | 0.23  |  |
| L1     | 0.13                      | 0.18  | 0.23  |  |
| е      | 0.355 BSC                 |       |       |  |



# Marking



# **Order Information**

| Device          | Package | Carrier     | Quantity        | HSF Status     |
|-----------------|---------|-------------|-----------------|----------------|
| SES5VD0603SY-2B | DFN0603 | Tape & Reel | 15000pcs / Reel | RoHS compliant |

# **Revision history**

| Date            | Revision | Description of changes |
|-----------------|----------|------------------------|
| 20-October-2020 | A2       | Update                 |



#### **CAUTION / WARNING**

- Information in this document is believed to be accurate and reliable. However, SEMITEL does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.
- Users should independently evaluate the suitability of and test each product selected for their own applications, and SEMITEL assumes no liability whatsoever relating to the choice, selection or use of the SEMITEL products and services described herein.
- SEMITEL reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product.
- · Information in this document supersedes and replaces all information previously supplied.
- Products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in
  applications where failure or malfunction of an SEMITEL product can reasonably be expected to result in personal injury, death or severe property or
  environmental damage. SEMITEL accepts no liability for inclusion and/or use of SEMITEL products in such equipment or applications and therefore
  such inclusion and/or use is at the customer's own risk.
- This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.
- Resale of SEMITEL products with provisions different from the statements and/or technical features set forth in this document shall immediately void
  any warranty granted by SEMITEL for the SEMITEL product or service described herein and shall not create or extend in any manner whatsoever, any
  liability of SEMITEL.
- SEMITEL expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. SEMITEL only obligations are those in the SEMITEL Standard Terms and Conditions of Sale and in no case will SEMITEL be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.

Specifications are subject to change without notice
© Copyright 2005, Semitel Electronics
Semitel

. ® is a registered trademark of Semitel Electronics
All rights reserved

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ESD Suppressors / TVS Diodes category:

Click to view products by Semitel manufacturer:

Other Similar products are found below:

60KS200C D18V0L1B2LP-7B D5V0F4U5P5-7 DESD5V0U1BB-7 NTE4902 P4KE27CA P6KE11CA P6KE39CA-TP P6KE8.2A

SA110CA SA60CA SA64CA SMBJ12CATR SMBJ33CATR SMBJ8.0A ESD101-B1-02ELS E6327 ESD105-B1-02EL E6327 ESD112-B1
02EL E6327 ESD119B1W01005E6327XTSA1 ESD5V0L1B02VH6327XTSA1 ESD7451N2T5G 19180-510 CPDT-5V0USP-HF

3.0SMCJ33CA-F 3.0SMCJ36A-F HSPC16701B02TP D3V3Q1B2DLP3-7 D55V0M1B2WS-7 DESD5V0U1BL-7B DRTR5V0U4SL-7

SCM1293A-04SO ESD200-B1-CSP0201 E6327 SM12-7 SMF8.0A-TP SMLJ45CA-TP SMQA1000T1G CEN955 W/DATA 82350120560

VESD12A1A-HD1-GS08 CPDUR5V0R-HF CPDQC5V0U-HF CPDQC5V0USP-HF CPDQC5V0-HF IP4042CX5/LF,135 D1213A-01LP4
7B D1213A-02WL-7 1SMB33CAT3G-XYZ MMAD1108/TR13 5KP100A 5KP15A