

AXIAL LEADED HERMETICALLY SEALED SUPERFAST RECTIFIER DIODE

- Very low reverse recovery time
- Hermetically sealed in Metoxilite fused metal oxide
- Low switching losses
- Low forward voltage drop
- Soft, non-snap off, recovery characteristics


QUICK REFERENCE DATA

- $V_R = 50 - 150V$
- $I_F = 1.8A$
- $t_{rr} = 30nS$
- $V_F = 1.2V$

ABSOLUTE MAXIMUM RATINGS (@ 25°C unless otherwise specified)

	Symbol	1N6073 FF05	1N6074 FF10	1N6075 FF15	Unit
Working reverse voltage	V_{RWM}	50	100	150	V
Repetitive reverse voltage	V_{RRM}	50	100	150	V
Average forward current (@ 55°C, lead length = 0.375")	$I_{F(AV)}$	←	1.8	→	A
Repetitive surge current (@ 55°C, lead length = 0.375")	I_{FRM}	←	14.0	→	A
Non-repetitive surge current ($t_p = 8.3ms$, @ V_R & T_{jmax})	I_{FSM}	←	35.0	→	A
Storage temperature range	T_{STG}	←	-65 to +150	→	°C
Operating temperature range	T_{OP}	←	-65 to +150	→	°C

MECHANICAL



These products are qualified to MIL-S-19500/503.

They can be supplied fully released as JAN, JANTX, and JANTXV versions.

These products are qualified in Europe to DEF STAN 59-61 (PART 80)/029 available to F and FX levels.

January 7, 1998

ELECTRICAL CHARACTERISTICS (@ 25°C unless otherwise specified)

	Symbol	1N6073 FF05	1N6074 FF10	1N6075 FF15	Unit
Average forward current max. (pcb mounted; T _A = 55°C) for sine wave	I _{F(AV)}	← 0.85 →			A
	I _{F(AV)}	← 0.90 →			A
Average forward current max. T _L = 70°C; L = 0". T _L = 55°C; L = 3/8"	I _{F(AV)}	← 3.0 →			A
	I _{F(AV)}	← 1.7 →			A
for sine wave	I _{F(AV)}	← 1.8 →			A
	I _{F(AV)}	← 1.8 →			A
for square wave	I _{F(AV)}	← 1.8 →			A
	I _{F(AV)}	← 1.8 →			A
I ² t for fusing (t = 8.3ms) max.	I ² t	← 5.0 →			A ² S
Forward voltage drop max. @ I _F = 1.5A, T _j = 25°C	V _F	← 1.2 →			V
	V _F	← 1.2 →			V
Reverse current max. @ V _{RWM} , T _j = 25°C	I _R	← 1.0 →			μA
	I _R	← 50 →			μA
@ V _{RWM} , T _j = 100°C	I _R	← 50 →			μA
	I _R	← 50 →			μA
Reverse recovery time 0.5A I _F , 1.0A I _R , 0.25A I _{RR} .	t _{rr}	← 30 →			nS
	t _{rr}	← 30 →			nS
Junction capacitance typ. @ V _R = 5V, f = 1MHz	C _j	← 28 →			pF
	C _j	← 28 →			pF

THERMAL CHARACTERISTICS

	Symbol	1N6073 FF05	1N6074 FF10	1N6075 FF15	Unit
Thermal resistance - junction to lead Lead length = 0.375"	R _{θJL}	← 46 →			°C/W
	R _{θJL}	← 13 →			°C/W
Lead length = 0.0"	R _{θJL}	← 13 →			°C/W
	R _{θJA}	← 95 →			°C/W
Thermal resistance - junction to amb. on 0.06" thick pcb. 1 oz. copper.	R _{θJA}	← 95 →			°C/W

January 7, 1998




Fig 1. Forward voltage drop as a function of forward current.




Fig 2. Maximum power versus lead temperature.




Fig 3. Transient thermal impedance characteristic.




Fig 4. Typical junction capacitance as a function of reverse voltage.

January 7, 1998




Fig 5. Forward power dissipation as a function of forward current, for sinusoidal operation.




Fig 6. Forward power dissipation as a function of forward current, for square wave operation.




Fig 7. Maximum repetitive forward current as a function of pulse width at 55°C; $R_{\theta JL} = 45\text{ }^{\circ}\text{C/W}$; V_{RWM} during $1 - \delta$.




Fig 8. Maximum repetitive forward current as a function of pulse width at 100°C; $R_{\theta JL} = 110\text{ }^{\circ}\text{C/W}$; V_{RWM} during $1 - \delta$.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rectifiers](#) category:

Click to view products by [Semtech](#) manufacturer:

Other Similar products are found below :

[70HFR40](#) [RL252-TP](#) [150KR30A](#) [1N5397](#) [NTE5841](#) [NTE6038](#) [SCF5000](#) [1N4002G](#) [1N4005-TR](#) [JANS1N6640US](#) [VS-80-7161](#) [481235F](#)
[RRE02VS6SGTR](#) [067907F](#) [MS306](#) [70HF40](#) [T85HFL60S02](#) [US2JFL-TP](#) [A1N5404G-G](#) [CRS04\(T5L,TEMQ\)](#) [ACGRA4007-HF](#)
[ACGRB207-HF](#) [CLH03\(TE16L,Q\)](#) [ACGRC307-HF](#) [ACEFC304-HF](#) [NTE6356](#) [NTE6359](#) [NTE6002](#) [NTE6023](#) [NTE6039](#) [NTE6077](#)
[85HFR60](#) [40HFR60](#) [1N1186RA](#) [70HF120](#) [85HFR80](#) [D126A45C](#) [SCF7500](#) [D251N08B](#) [SCHJ22.5K](#) [SM100](#) [SCPA2](#) [SCH10000](#) [SDHD5K](#)
[VS-12FL100S10](#) [ACGRA4001-HF](#) [D1821SH45T PR](#) [D1251S45T](#) [NTE5990](#) [NTE6358](#)