Silicon Epitaxial Planar Switching Diode

Features

- Small package
- Low forward voltage
- Fast reverse recovery time
- Small total capacitance

Applications

Ultra high speed switching application

Absolute Maximum Ratings (T_a = 25 °C)

Parameter		Symbol	Value	Unit
Maximum Peak Reverse Voltage		V_{RM}	100	V
Reverse Voltage		V _R	75	V
Average Forward Current		Ι _Ο	200	mA
Maximum Peak Forward Current		I _{FM}	300	mA
Non-Repetitive Peak Forward Surge Current	att=1s att=1µs	I _{FSM}	1 2	А
Power Dissipation		Pd	350	mW
Junction Temperature		Tj	150	°C
Storage Temperature Range		T _{stg}	- 55 to + 150	°C

Characteristics at T_a = 25 °C

Parameter	Symbol	Min.	Max.	Unit
Forward Voltage at $I_F = 1 \text{ mA}$ at $I_F = 10 \text{ mA}$ at $I_F = 50 \text{ mA}$ at $I_F = 150 \text{ mA}$	V _F V _F V _F V _F	- - -	715 855 1 1.25	mV mV V V
Reverse Current at $V_R = 20 V$ at $V_R = 75 V$ at $V_R = 25 V$, $T_J = 150 °C$ at $V_R = 75 V$, $T_J = 150 °C$	I _R I _R I _R	- - -	25 2.5 30 50	nA μA μA μA
Reverse Breakdown Voltage at I_R = 100 μ A	V _{(BR)R}	75	-	V
Total Capacitance at $V_R = 0$, f = 1 MHz	CT	-	2	pF
Reverse Recovery Time at I _F = 10 mA, V _R = 6 V, I _{RR} = 1 mA, R _L = 100 Ω	t _{rr}	-	4	ns












Marking Code: A4 TO-236 Plastic Package







Dated : 18/06/2016 Rev:02

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by Semtech manufacturer:

Other Similar products are found below :

MMBD3004S-13-F RD0306T-H DSE010-TR-E BAV17-TR BAV19-TR 1N3611 NTE156A NTE574 NTE6244 1SS181-TP 1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1TIG LS4151GS08 FC903-TR-E 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR 1SS226-TP RFUH20TB3S D291S45T BAV300-TR BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G CDSZC01100-HF LL4150-M-08 BAV199E6433HTMA1 BAS28-7 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3 NSVM1MA152WKT1G RGP30D-E3/73 BAV99TQ-13-F BAS21DWA-7 NTE6250 NTE582-4 NTE582-6 MMDB30-E28X