



BZX84C...Series

Silicon Planar Zener Diodes

This series of Zener diodes is offered in the convenient, surface mount plastic TO-236 package. These devices are designed to provide voltage regulation with minimum space requirement. They are well suited for applications such as cellular phones, hand held portables, and high density PC boards.



1. Anode 3. Cathode
TO-236 Plastic Package


Features

- Zener breakdown voltage range - 2.0 V to 75 V
- Package designed for optimal automated board assembly
- Small package size for high density applications

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

| Parameter | Symbol | Value | Unit |
|---|-----------------|---------------|--------------------|
| Power Dissipation | P_D | 350 | mW |
| Thermal Resistance, Junction to Ambient ¹⁾ | $R_{\theta JA}$ | 357 | $^\circ\text{C/W}$ |
| Junction and Storage Temperature Range | T_j, T_{stg} | - 65 to + 150 | $^\circ\text{C}$ |

¹⁾ Alumina = 0.4 X 0.3 X 0.024 in, 99.5% alumina



SEMTECH ELECTRONICS LTD.




Dated: 16/03/2015 Rev: 03

BZX84C...Series

Electrical Characteristics ($T_a = 25^\circ\text{C}$ unless otherwise noted, $V_F < 0.9\text{ V}$ at $I_F = 10\text{ mA}$)

| Type | Marking Code | Zener Voltage Range ¹⁾ | | | | Dynamic Impedance | | Reverse Current | |
|-----------|--------------|-----------------------------------|----------|----------|-------------|-------------------|-------------|------------------------|----------|
| | | V_{ZT} | | | at I_{ZT} | Z_{ZT} | at I_{ZT} | I_R | at V_R |
| | | Nom. (V) | Min. (V) | Max. (V) | (mA) | Max. (Ω) | (mA) | Max. (μA) | (V) |
| BZX84C2V0 | A8 | 2 | 1.8 | 2.15 | 5 | 100 | 5 | 120 | 0.5 |
| BZX84C2V2 | B8 | 2.2 | 2.08 | 2.33 | 5 | 100 | 5 | 120 | 0.7 |
| BZX84C2V4 | C8 | 2.4 | 2.2 | 2.6 | 5 | 100 | 5 | 50 | 1 |
| BZX84C2V7 | D8 | 2.7 | 2.5 | 2.9 | 5 | 100 | 5 | 20 | 1 |
| BZX84C3V0 | E8 | 3 | 2.8 | 3.2 | 5 | 95 | 5 | 10 | 1 |
| BZX84C3V3 | F8 | 3.3 | 3.1 | 3.5 | 5 | 95 | 5 | 5 | 1 |
| BZX84C3V6 | H8 | 3.6 | 3.4 | 3.8 | 5 | 90 | 5 | 5 | 1 |
| BZX84C3V9 | J8 | 3.9 | 3.7 | 4.1 | 5 | 90 | 5 | 3 | 1 |
| BZX84C4V3 | K8 | 4.3 | 4 | 4.6 | 5 | 90 | 5 | 3 | 1 |
| BZX84C4V7 | M8 | 4.7 | 4.4 | 5 | 5 | 80 | 5 | 3 | 2 |
| BZX84C5V1 | N8 | 5.1 | 4.8 | 5.4 | 5 | 60 | 5 | 2 | 2 |
| BZX84C5V6 | P8 | 5.6 | 5.2 | 6 | 5 | 40 | 5 | 1 | 2 |
| BZX84C6V2 | R8 | 6.2 | 5.8 | 6.6 | 5 | 10 | 5 | 3 | 4 |
| BZX84C6V8 | X8 | 6.8 | 6.4 | 7.2 | 5 | 15 | 5 | 2 | 4 |
| BZX84C7V5 | Y8 | 7.5 | 7 | 7.9 | 5 | 15 | 5 | 1 | 5 |
| BZX84C8V2 | Z8 | 8.2 | 7.7 | 8.7 | 5 | 15 | 5 | 0.7 | 5 |
| BZX84C9V1 | A9 | 9.1 | 8.5 | 9.6 | 5 | 15 | 5 | 0.5 | 6 |
| BZX84C10 | B9 | 10 | 9.4 | 10.6 | 5 | 20 | 5 | 0.2 | 7 |
| BZX84C11 | C9 | 11 | 10.4 | 11.6 | 5 | 20 | 5 | 0.1 | 8 |
| BZX84C12 | D9 | 12 | 11.4 | 12.7 | 5 | 25 | 5 | 0.1 | 8 |
| BZX84C13 | E9 | 13 | 12.4 | 14.1 | 5 | 30 | 5 | 0.1 | 8 |
| BZX84C15 | F9 | 15 | 13.8 | 15.6 | 5 | 30 | 5 | 0.05 | 10.5 |
| BZX84C16 | H9 | 16 | 15.3 | 17.1 | 5 | 40 | 5 | 0.05 | 11.2 |
| BZX84C18 | J9 | 18 | 16.8 | 19.1 | 5 | 45 | 5 | 0.05 | 12.6 |
| BZX84C20 | K9 | 20 | 18.8 | 21.2 | 5 | 55 | 5 | 0.05 | 14 |
| BZX84C22 | M9 | 22 | 20.8 | 23.3 | 5 | 55 | 5 | 0.05 | 15.4 |
| BZX84C24 | N9 | 24 | 22.8 | 25.6 | 5 | 70 | 5 | 0.05 | 16.8 |
| BZX84C27 | P9 | 27 | 25.1 | 28.9 | 2 | 80 | 2 | 0.05 | 18.9 |
| BZX84C30 | R9 | 30 | 28 | 32 | 2 | 80 | 2 | 0.05 | 21 |
| BZX84C33 | X9 | 33 | 31 | 35 | 2 | 80 | 2 | 0.05 | 23.1 |
| BZX84C36 | Y9 | 36 | 34 | 38 | 2 | 90 | 2 | 0.05 | 25.2 |
| BZX84C39 | Z9 | 39 | 37 | 41 | 2 | 130 | 2 | 0.05 | 27.3 |
| BZX84C43 | A0 | 43 | 40 | 46 | 2 | 150 | 2 | 0.05 | 30.1 |
| BZX84C47 | B0 | 47 | 44 | 50 | 2 | 170 | 2 | 0.05 | 32.9 |
| BZX84C51 | C0 | 51 | 48 | 54 | 2 | 180 | 2 | 0.05 | 35.7 |
| BZX84C56 | D0 | 56 | 52 | 60 | 2 | 200 | 2 | 0.05 | 39.2 |
| BZX84C62 | E0 | 62 | 58 | 66 | 2 | 215 | 2 | 0.05 | 43.4 |
| BZX84C68 | F0 | 68 | 64 | 72 | 2 | 240 | 2 | 0.05 | 47.6 |
| BZX84C75 | H0 | 75 | 70 | 79 | 2 | 255 | 2 | 0.05 | 52.5 |

¹⁾ Tested with pulses $t_p = 20\text{ ms}$.




SEMTECH ELECTRONICS LTD.




Dated: 16/03/2015 Rev: 03

BZX84C...Series


Temperature Coefficient





Temperature Coefficient



Power Derating Curve



Typical Forward Voltage



SEMTECH ELECTRONICS LTD.



ISO/TS 16949:2009
Certificate No. 160713000

ISO14001:2004
Certificate No. 7116

ISO 9001:2008
Certificate No. 50719410

BS-OHSAS 18001:2007
Certificate No. 7116

IECQ QC 080000
Certificate No. PRC-HSPM-1483

Dated: 16/03/2015 Rev: 03

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Zener Diodes](#) category:

Click to view products by [Semtech](#) manufacturer:

Other Similar products are found below :

[RKZ13B2KG#P1](#) [DL5234B](#) [EDZTE6113B](#) [1N4682](#) [1N4691](#) [1N4693](#) [1N4732A](#) [1N4736A](#) [1N4750A](#) [1N4759ARL](#) [1N5241B](#) [1N5365B](#)
[1N5369B](#) [1N747A](#) [1N959B](#) [1N964B](#) [1N966B](#) [1N968B](#) [1N972B](#) [NTE5121A](#) [NTE5147A](#) [NTE5152A](#) [NTE5155A](#) [NTE5164A](#)
[JANS1N4974US](#) [1N4692](#) [1N4700](#) [1N4702](#) [1N4704](#) [1N4711](#) [1N4714](#) [1N4737A](#) [1N4745ARL](#) [1N4752A](#) [1N4752ARL](#) [1N4760ARL](#)
[1N5221B](#) [1N5236B](#) [1N5241BTR](#) [1N5242BTR](#) [1N5350B](#) [1N5352B](#) [1N961BRR1](#) [1N964BRL](#) [RKZ5.1BKU#P6](#) [3SMAJ5946B-TP](#)
[3SMAJ5950B-TP](#) [3SMBJ5925B-TP](#) [441774C](#) [BZX84C3V9](#)