

POWER DISCRETES
Description

Quick reference data

$$V_R = 200V - 1000V$$

$$I_F = 1.0A$$

$$t_{rr} = 2\mu S$$

$$V_F = 1.2V$$

Features

- ◆ 1 Amp 55°C/no heat sink
- ◆ Monolithic non-cavity construction
- ◆ Fused metal oxide hermetic seal
- ◆ Superior thermal shock resistance
- ◆ Low thermal impedance
- ◆ Low reverse leakage
- ◆ PIV to 1000 volts

These products can be supplied as JAN, JANTX or JANTXV per MIL-S-19500/286

Electrical Specifications

Electrical specifications: All temperatures are local ambient , 25°C unless otherwise specified.

Device Types	Reverse Voltage		Forward Current (1)	Reverse Current (Max)		Instantaneous Forward Voltage	Repetitive Surge Current	1 Cycle Surge Current tp = 8.3ms	Reverse Recovery Time (2)		Typical Thermal Impedance (3)	
	V _{RWM}	V _{RRM}		Free Air 55°C	I _R				V _F @ I _F = 1.0A _{dc}	I _{FRM}	I _{FSM}	T _{rr}
	V	V	A		25°C	100°C	Vdc	A (pk)				A (pk)
1N4245	200	200	1.0	1.0	25	1.2	10	30	2	1	7	38
1N4246	400	400	1.0	1.0	25	1.2	10	30	2	1	7	38
1N4247	600	600	1.0	1.0	25	1.2	10	30	2	1	7	38
1N4248	800	800	1.0	1.0	25	1.2	10	30	2	1	7	38
1N4249	1000	1000	1.0	1.0	25	1.2	10	30	2	1	7	38

Notes:

- (1) The 1.0 amp rating @ 55°C requires no heat sinking, special mounting, or forced air across the body of the device.
- (2) Recovery conditions: 0.5 Amp forward current to -1.0 Amp reverse current. Recovery time measured when rectifier recovers to -.25 Amp.

Storage temperature: -65°C to +175°C.

POWER DISCRETES


Ordering Information

Part Number	Description
1N4245 1N4246 1N4247 1N4248 1N4249	Axial leaded hermetically sealed ⁽¹⁾

Note:

(1) Available in bulk or tape and reel packaging. Please consult factory for quantities.

Outline Drawing



DIM ^N	Dimensions				Note
	Inches		Millimeters		
	MIN	MAX	MIN	MAX	
A	.065	.110	1.65	2.79	-
B	1.00	1.25	25.4	31.7	-
C	.140	.165	3.56	4.19	-
D	.027	.031	.686	.786	-

Note:

1. Lead diameter not controlled in this area.

Contact Information

Semtech Corporation
Power Discrettes Products Division
200 Flynn Road, Camarillo, CA 93012
Phone: (805)498-2111 FAX (805)498-3804

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ESD Suppressors / TVS Diodes](#) category:

Click to view products by [Semtech](#) manufacturer:

Other Similar products are found below :

[NTE4902](#) [P4SMAJ15A](#) [P4SMAJ26A](#) [SMAJ400CA-TP](#) [TGL34-47CA](#) [ESDAULC45-1BF4](#) [SM1605E3/TR13](#) [SMF20A-TP](#) [P4SMAJ12A](#)
[CPDUR24V-HF](#) [CPDQC5V0USP-HF](#) [CPDQC5V0-HF](#) [MPLAD30KP45CAE3](#) [MMBZ27VCLQ-7-F](#) [MMAD1108/TR13](#) [MPLAD30KP24A](#)
[ACPDQC5V0R-HF](#) [DFLT170A-7](#) [NTE4900](#) [NTE4926](#) [NTE4938](#) [SMF22A-TP](#) [SMF12A-TP](#) [SLVU2.8-TP](#) [SMLJ6.5CA-TP](#) [SMAJ6.5CA-](#)
[TP](#) [MMAD1108E3/TR13](#) [D5V0M1U2LP3-7](#) [SMAJ400A-TP](#) [AOZ8811DT-03](#) [AOZ8831DI-05](#) [AOZ8831DT-03](#) [SMAJ188CA](#) [3SMC33CA](#)
[BK](#) [CPDQC3V3C-HF](#) [CPDQC12VE-HF](#) [MPLAD30KP170CA](#) [82357120100](#) [5.0SMLJ15CA-TP](#) [5KP18A-TP](#) [P6KE8.2A-TP](#)
[MPLAD30KP43CAE3](#) [SMAJ43A-TP](#) [D5V0F6U8LP33-7](#) [TVS5501V10MUT5G](#) [5.0SMLJ24CA-TP](#) [SMAJ110CA-TP](#) [MPLAD15KP75CAE3](#)
[MMAD1103e3/TR13](#) [DFLT40AQ-7](#)