

AXIAL LEADED HERMETICALLY SEALED FAST RECTIFIER DIODE

QUICK REFERENCE DATA


- Low reverse recovery time
- Hermetically sealed in Metoxilite fused metal oxide
- Low switching losses
- Low forward voltage drop
- Soft, non-snap off, recovery characteristics

- $V_R = 200 - 1000V$
- $I_F = 2.00A$
- $t_{rr} = 150 - 500nS$
- $I_R = 0.5\mu A$

ABSOLUTE MAXIMUM RATINGS (@ 25°C unless otherwise specified)

	Symbol	1N5615 S2F	1N5617 S4F	1N5619 S6F	1N5621 S8F	1N5623 S0F	Unit
Working reverse voltage	V_{RWM}	200	400	600	800	1000	V
Repetitive reverse voltage	V_{RRM}	200	400	600	800	1000	V
Average forward current (@ 55°C, lead length 0.375")	$I_{F(AV)}$	←————— 2.0 —————→					A
Repetitive surge current (@ 55°C in free air, lead length 0.375")	I_{FRM}	←————— 6.0 —————→					A
Non-repetitive surge current ($t_p = 8.3mS$, @ V_R & T_{jmax})	I_{FSM}	←————— 25 —————→					A
Storage temperature range	T_{STG}	←————— -65 to +175 —————→					°C
Operating temperature range	T_{OP}	←————— -65 to +175 —————→					°C

MECHANICAL



These products are qualified to MIL-PRF-19500/429 and are preferred parts as listed in MIL-STD-701.

They can be supplied fully released as JAN, JANTX, JANTXV and JANS version.

These products are qualified in Europe to DEF STAN 59-61 (PART 80)/029.

ELECTRICAL CHARACTERISTICS (@ 25°C unless otherwise specified)

	Symbol	1N5615 S2F	1N5617 S4F	1N5619 S6F	1N5621 S8F	1N5623 S0F	Unit
Average forward current max. (pcb mounted; T _A = 55°C) for sine wave	I _{F(AV)}	←————— 1.00 —————→					A
	I _{F(AV)}	←————— 1.05 —————→					A
Average forward current max. (T _L = 55°C; L = 3/8") for sine wave	I _{F(AV)}	←————— 1.95 —————→					A
	I _{F(AV)}	←————— 2.00 —————→					A
for square wave	I _{F(AV)}	←————— 2.00 —————→					A
I ² t for fusing (t = 8.3mS) max.	I ² t	←————— 2.5 —————→					A ² S
Forward voltage drop max. @ I _F = 1.0A, T _j = 25°C	V _F	←————— 1.2 —————→					V
Reverse current max. @ V _{RWM} , T _j = 25°C	I _R	←————— 0.5 —————→					μA
	I _R	←————— 25 —————→					μA
@ V _{RWM} , T _j = 100°C	I _R	←————— 25 —————→					μA
Reverse recovery time max. 0.5A I _F to 1.0A I _R . Recovers to 0.25A I _{RR}	t _{rr}	150	150	250	300	500	nS
Junction capacitance typ. @ V _R = 5V, f = 1MHz	C _j	27	27	27	18	18	ρF

THERMAL CHARACTERISTICS

	Symbol	1N5615 S2F	1N5617 S4F	1N5619 S6F	1N5621 S8F	1N5623 S0F	Unit
Thermal resistance - junction to lead Lead length = 0.375"	R _{θJL}	←————— 38 —————→					°C/W
	R _{θJL}	←————— 7 —————→					°C/W
Lead length = 0.0"	R _{θJL}	←————— 7 —————→					°C/W
Thermal resistance - junction to amb. on 0.06" thick pcb. 1 oz. copper.	R _{θJA}	←————— 95 —————→					°C/W




Fig 1. Forward voltage drop as a function of forward current.




Fig 2. Maximum power versus lead temperature.




Fig 3. Transient thermal impedance characteristic.




Fig 4. Typical junction capacitance as a function of reverse voltage.




Fig 5. Forward power dissipation as a function of forward current, for sinusoidal operation.




Fig 6. Forward power dissipation as a function of forward current, for square wave operation.




Fig 7. Typical repetitive forward current as a function of pulse width at 55°C; $R_{\theta JL} = 35 \text{ }^\circ\text{C/W}$; V_{RWM} during $1 - \delta$.




Fig 8. Typical repetitive forward current as a function of pulse width at 100°C; $R_{\theta JL} = 95 \text{ }^\circ\text{C/W}$; V_{RWM} during $1 - \delta$.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Zener Diodes](#) category:

Click to view products by [Semtech](#) manufacturer:

Other Similar products are found below :

[RKZ13B2KG#P1](#) [DL5234B](#) [1N4682](#) [1N4691](#) [1N4693](#) [1N4732A](#) [1N4733A-TR](#) [1N4736A](#) [1N4750A](#) [1N4759ARL](#) [1N5241B](#) [1N5365B](#)
[1N5369B](#) [1N747A](#) [1N959B](#) [1N964B](#) [1N966B](#) [1N968B](#) [1N972B](#) [NTE149A](#) [NTE5116A](#) [NTE5121A](#) [NTE5147A](#) [NTE5152A](#) [NTE5155A](#)
[NTE5164A](#) [JANS1N4974US](#) [1N4692](#) [1N4700](#) [1N4702](#) [1N4704](#) [1N4711](#) [1N4714](#) [1N4737A](#) [1N4745ARL](#) [1N4752A](#) [1N4752ARL](#)
[1N4760ARL](#) [1N5221B](#) [1N5236B](#) [1N5241BTR](#) [1N5242BTR](#) [1N5350B](#) [1N5352B](#) [1N961BRR1](#) [1N964BRL](#) [RKZ5.1BKU#P6](#)
[3SMAJ5950B-TP](#) [3SMBJ5925B-TP](#) [TDZTR24](#)