















RClamp®0554S

KEY FEATURES

- High surge immunity: Ipp=25A, 8x20μs
- 4-line protection array
- · Superior clamping voltage
- Low capacitance: 5pF
- Small package (SOT-23L)

BENEFITS

- Protection for lightning, ESD and Cable Discharge
- Ideal for protecting two differential pairs
- Protects sensitive next generation transceivers
- Provides minimal loading to preserve signal integrity
- Footprint compatible with SRV05-4

APPLICATIONS

- USB 2.0 Power and Data Line Protection
- 10/100/1000 Ethernet
- · Video Graphics Cards
- Monitors and Flat Panel Displays
- Digital Video Interface (DVI)
- Notebook Computers
- IEEE 1394 Firewire Ports


PACKAGING

JEDEC SOT-23 6L



Low Clamping Performance TVS Array for ESD, Cable Discharge & Surge Protection

The RClamp*0554S's unique design incorporates eight surge rated, low capacitance steering diodes and a TVS diode in a single package. During transient conditions, the steering diodes direct the transient to either the positive side of the power supply line or to ground. The internal TVS diode prevents over-voltage on the power line, protecting any downstream components.




RClamp®0554S


RClamp® 0554S - Absolute Maximum Rating						
Maximum Rating	Symbol	Value	Unit			
Peak Pulse Power ($tp = 8/20us$)	P_{pk}	375	Watts			
Peak Pulse Power (tp = $8/20\mu$ s)	Ірр	25	А			
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V _{ESD}	±30 ±25	kV			
Operating Temperature	T _j	-55 to +125	° C			
Storage Temperature	T _{STG}	-55 to +150	° C			

Electrical Characteristics (T=25°C)							
Parameter	Symbol	Condition	Min	Тур	Max	Units	
Reverse Stand-Off Voltage	V_{RWM}				5	V	
Reverse Breakdown Voltage	V_{BR}		6			V	
Reverse Leakage Current	I _R	V_{RWM} = 5V, T = 25 ° C			0.5	μΑ	
Clamping Voltage	Vc	$I_{pp} = 25A$, $tp = 8/20\mu s$			15	V	
Junction Capacitance	C _j	Any I/O to Gnd $VR = 0$, $f = 1MHz$			5	pF	
		I/O to $I/OVR = 0, f = 1MHz$		3		pF	

ESD CLAMPING (8KV CONTACT PER IEC 61000-4-2)



SURGE CLAMPING $(TP = 8/20\mu S)$



ORDERING INFORMATION

RClamp0554S.TCT					
Working Voltage	Qty Per Reel	Reel Size			
5V	3,000	7 inches			



200 Flynn Road, Camarillo, California 93012 • phone: (805) 498-2111 • fax: (805) 498-3804

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ESD Suppressors / TVS Diodes category:

Click to view products by Semtech manufacturer:

Other Similar products are found below:

60KS200C D12V0H1U2WS-7 D18V0L1B2LP-7B 82356050220 D5V0M5U6V-7 NTE4902 P4KE27CA P6KE11CA P6KE39CA-TP
P6KE8.2A SA110CA SA60CA SA64CA SMBJ12CATR SMBJ8.0A SMLJ30CA-TP ESD101-B1-02ELS E6327 ESD112-B1-02EL E6327
ESD119B1W01005E6327XTSA1 ESD5V0L1B02VH6327XTSA1 ESD7451N2T5G 19180-510 CPDT-5V0USP-HF 3.0SMCJ33CA-F
3.0SMCJ36A-F HSPC16701B02TP D3V3Q1B2DLP3-7 D55V0M1B2WS-7 DESD5V0U1BL-7B DRTR5V0U4SL-7 SCM1293A-04SO
ESD200-B1-CSP0201 E6327 ESD203-B1-02EL E6327 SM12-7 SMF8.0A-TP SMLJ45CA-TP CEN955 W/DATA 82350120560
82356240030 VESD12A1A-HD1-GS08 CPDUR5V0R-HF CPDUR24V-HF CPDQC5V0U-HF CPDQC5V0USP-HF CPDQC5V0-HF
D1213A-01LP4-7B D1213A-02WL-7 ESDLIN1524BJ-HQ 5KP100A 5KP15A