### FAST RECOVERY HIGH VOLTAGE RECTIFIER ASSEMBLY

SCF2500 SCF5000 SCF7500 SCF10000 SCF12500

January 8, 1998

TEL:805-498-2111 FAX:805-498-3804 WEB:http://www.semtech.com

# HIGH VOLTAGE, HIGH DENSITY, FAST RECOVERY LEADED SILICON RECTIFIER ASSEMBLY

- · Low reverse recovery time
- Low forward voltage drop
- High thermal shock resistance
- Corona free construction
- Low distributed capacitance


## QUICK REFERENCE DATA

- $V_R = 2500V 12500V$
- $I_F = 0.5A$
- $I_R = 1.0 \,\mu\text{A}$
- $t_{rr} = 150 nS$

#### **ABSOLUTE MAXIMUM RATINGS**

Working Device Reverse Type Voltage		Average Rectified Current I <sub>F(AV)</sub>		Repetitive Surge Current	1 Cycle Surge Current $t_p = 8.3$ mS (sinusoidal)		$I^{2}t$ $t_{p} = 8.3mS$	Case Length Max
177	(V <sub>RWM</sub> )	@ 55 ℃	@ 100 °C	@ 25 °C	@ 25 °C	@ 100 °C	@ 25 °C	dim. C
	Volts	Amps	Amps	Amps	Amps	Amps	A <sup>2</sup> S	inches
SCF2500	2500	1	<b>†</b>	1	<b>†</b>	<b>†</b>	<b>†</b>	1.145
SCF5000	5000							2.020
SCF7500	<i>7</i> 500	0.5	0.3	15	25	12.5	2.6	2.770
SCF10000	10000							3.520
SCF12500	12500	<b> </b>		ļ	↓	ļ	<b> </b>	4.270

#### **MECHANICAL**



January 8, 1998

#### **ELECTRICAL CHARACTERISTICS**

Device Type	Current	eakage @ V <sub>RWM</sub> R	Maximum Forward Voltage drop V <sub>F</sub> @ 0.5A	Maximum Reverse Recovery Time
-71-	@ 25 °C	@ 100 °C	@ 25 °C	t <sub>rr</sub> @ 25 °C
	μΑ	μΑ	Volts	nS
SCF2500	†	†	3.45	<u>†</u>
SCF5000			5.75	
SCF7500	1.0	25	9.20	150
SCF10000			11.5	
SCF12500	ļ.	<b> </b>	15.0	<b>↓</b>

(1) measured on discrete devices prior to assembly

Operating temperature range Storage temperature range

-55 °C to +150 °C -55 °C to +150 °C




Fig 1. Forward voltage drop as a function of forward current.

TABLE 1

DEVICE	X-AXIS		
SCF2500	х3		
SCF5000	x5		
SCF7500	x8		
SCF10000	x10		
SCF12500	x13		

January 8, 1998




Figure 2. Maximum average forward currents against ambient temperature.




Figure 3. Maximum ratings for capacitive loads. Insurge current versus RC time constant




Figure 4. Non repetitive forward current surge curves.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rectifiers category:

Click to view products by Semtech manufacturer:

Other Similar products are found below:

70HFR40 RL252-TP 150KR30A 1N5397 NTE5841 NTE6038 SCF5000 1N4002G 1N4005-TR JANS1N6640US 481235F

RRE02VS6SGTR 067907F MS306 70HF40 T110HF60 T85HFL60S02 US2JFL-TP A1N5404G-G CRS04(T5L,TEMQ) ACGRA4007-HF

ACGRB207-HF CLH03(TE16L,Q) ACGRC307-HF ACEFC304-HF NTE6356 NTE6359 NTE6002 NTE6023 NTE6039 NTE6077

85HFR60 40HFR60 1N1186RA 70HF120 85HFR80 D126A45C SCF7500 D251N08B SCHJ22.5K SM100 SCPA2 SCH10000 SDHD5K

VS-12FL100S10 ACGRA4001-HF D1821SH45T PR D1251S45T NTE5990 NTE6358