





Long reach external mount float switch via 1/2"NPT

- Long reach for thick walled tanks and boss mounting
- Available with flying lead or M12 plug connection
- Float material SS 316, stem material SS 304
- External mount via 1/2"NPT thread, so does not require access to the inside of the tank for fitting.
- N/O or N/C switching action



Technical Specification

Mounting style	External	Cable length - standard	100cm or plug	
Mounting thread	1/2"NPT	Cable size 17/0.10 - AWG22		
Float & Stem material	316/304 grade SS	Cable conductor material Tinned co		
Maximum Temperature	120°C	Cable sheath material Teflon		
Maximum pressure	10 bar	Cable temperature rating 200°C		
Float SG	0.7	Tightening torque should be adequate		
Minimum fluid SG	0.8	to ensure a good seal		

Electrical Specification

Lieuti idai apedilidatidii					
Contact Form		N/O (N/C)			
Switching Power Max	VA	50			
Switching Voltage AC Max	V	300			
Switching Voltage DC Max	V	300			
Switching Current Max	Α	0.5			
All ratings are for resistive	load only.				

Standard Parts	Stem Material	Float Material	Connection
SSF215X100	SS304	SS316	100cm Teflon AWG 22
SSF215XPM12	SS304	SS316	M12 Plug connection
SSF215XPL	SS304	SS316	DIN43650

Custom versions can be made for particular applications. Please contact Cynergy3 with your requirements.

1/2"NPT

The SSF215 series of floatswitches are externally mounted horizontal switches. This series has an extended reach to provide a solution for extra thick tank walls or for mounting in welded on 1/2"NPT bosses.

The 1/2"NPT thread enables the switches to be fitted through the wall of a tank from the outside, so does not require access to the inside of the tank.

The floatswitch can be fitted to achieve either N/O (make on rise) or N/C (make on fall) switching action by simply rotating the switch through 180°.

Mechanical Dimensions Lead Wire 1000 mm 37 Ø17x47 47 62 120 1/2"NPT 24Hex Plug connections 14 Ø17x47 47 62 120 % 2-pole 24Hex Plug/socket 1/2"NPT 15 33.5 37 Ø17x47 47 62 120 % Cable Gland 6mmmax.

www.cynergy3.com

Cynergy3 Components Ltd. 7 Cobham Road Ferndown Industrial Estate Wimborne, Dorset BH21 7PE Telephone +44 (0) 1202 897969

Email:sales@cynergy3.com

ISO9001 CERTIFIED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Liquid Level Sensors category:

Click to view products by Sensata manufacturer:

Other Similar products are found below:

FSH-21 FSH-25 FSH-34 FSH-35 FSV-31 FSV-35 RSF54H100R1/8 LRNH31S41 F03-16SFC-10M F03-16PE-5M F03-16PT-5M SCN-1518SC LL103000 LRNR31N01 F03-16PT-2M MS03-PP F03-16SF-10M KSL-100-1 LS01-1A66-PP-2000W LS01-1B66-PP-500W LS02-1B85-PP-5000W LS03-1A85-PP-500W LS03/DL-1A85-PA-500W EL-10N EL-3N LL01-1AA01 59630-1-T-02-F LS04-1B66-2-500W LFFS 011 PS-3S (Q) T0-SKF-0.5 T0-SKF-10 T0-SKF-5 VNI3 CLE2P VNI1 LBFS 0111 LFFS 014 KSL-35-PP KSL-88-PP KSL-99-1 LS02-1A85-PP-500W LS02-1B85-PP-500W LS03-1A85-PA-500W MIC 1000-20 700670 BAF147B002-00A0 DFT-110 DFT-220