



# APPROVAL SHEET

Approval Specification	Customer's Approval Certificate
<b>TO:</b>	<b>Checked &amp; Approved by:</b>
<b>Part No.:</b>	<b>Date:</b>
<b>Customer's Part No.:</b>	Please return this copy as a certification of your approval

## BEIJING ZHONGXUN SIFANG SCIENCE & TECHNOLOGY CO.,LTD.

Tel: +86-010-58937383  
Fax: +86-010-58937263  
E-mail: zxsf\_sales@163.com  
QQ: 3037058772  
Website: <http://www.bjzxsf.net> <http://www.sfsaw.com>  
Add: No 201, Block A. Building 3. Yongjie Beilu  
Yongfeng high-tech industrial base  
Haidian District Beijing city



Part No.	:	SFR3907
Pages	:	7
Date	:	2017/5/8
Revision	:	1.0

<b>Prepared by:</b>	
<b>Checked by:</b>	
<b>Approved by:</b>	




## Features

- 1-port Resonator
- Metal Case for **SC04-06**
- **RoHS** compatible
- Package Code SC04-06
- **Electrostatic Sensitive Device(ESD)**




## Application


### Typical Low-Power Transmitter Application



### Typical Local Oscillator Application



## Package Dimensions (SC04-06)



## Pin Configuration


<b>1</b>	Input/ Output
<b>4</b>	Output/ Input
<b>2,3</b>	Case Ground

## Marking




SF	Trademark
R	SAW Resonator
303D	Part number

## Test Circuit



## Equivalent LC Model



## Performance

### Maximum Rating

Item		Value	Unit
DC Voltage	$V_{DC}$	$\pm 30$	V
Operation Temperature	T	-40 ~ +85	$^{\circ}\text{C}$
Storage Temperature	$T_{stg}$	-40 ~ +85	$^{\circ}\text{C}$
RF Power Dissipation	P	15	dBm

### Electronic Characteristics


Test Temperature:  $25^{\circ}\text{C} \pm 2^{\circ}\text{C}$

Terminating source impedance:  $50\Omega$

Terminating load impedance:  $50\Omega$

Item			Minimum	Typical	Maximum	Unit
Center Frequency	Absolute Frequency	$f_c$		303.00		MHz
	Tolerance from 303.00MHz	$\Delta f_c$		$\pm 75$		KHz
Insertion Loss(min)		IL		1.3	2.0	dB
Quality Factor	Unloaded Q	$Q_U$		10397		
	50 $\Omega$ Loaded Q	$Q_L$		1288		
Frequency Aging	Absolute Value during the First Year	$ f_A $		$\leq 10$		ppm/yr
DC Insulation Resistance between Any Two Pins			1.0			M $\Omega$
RF Equivalent RLC Model	Motional Resistance	$R_M$		14.1	26.0	$\Omega$
	Motional Inductance	$L_M$		77.2		$\mu\text{H}$
	Motional Capacitance	$C_M$		3.57		fF
	Static Capacitance	$C_0$	4.36	4.66	4.96	pF

### Frequency Response





**Notes**

1. As a result of the particularity of inner structure of SAW products, it easy to be breakdown by electrostatic, so we should pay attention to **ESD protect** in the test.
2. **Static voltage** between signal load and ground may cause deterioration and destruction of the component. Please avoid static voltage.
3. **Ultrasonic cleaning** may cause deterioration and destruction of the component. Please avoid ultrasonic cleaning.
4. Only leads of component may **be soldered**. Please avoid soldering another part of component.
5. There is a close relationship between the device's performance and **matching network**. The specifications of this device are based on the test circuit shown above. L and C values may change depending on board layout. Values shown are intended as a guide only.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Resonators](#) category:*

*Click to view products by [Sf manufacturer](#):*

Other Similar products are found below :

[B39431R820H210](#) [CSAC2.00MGCM-TC](#) [ECS-HFR-40.00-B-TR](#) [CSTLS4M00G53Z-A0](#) [ZTB455E](#) [ECS-CR2-16.00-A-TR](#) [ECS-HFR-20.00-B-TR](#) [ECS-CR2-20.00-A-TR](#) [RO3164E-3](#) [ASR418S2-T](#) [CSTNE10M0G520000R0](#) [CSTLS8M00G53093-A0](#) [CSTNE12M0G52A000R0](#) [CSTLS18M4X54-A0](#) [CSTLS16M9X53Z-B0](#) [CSTLS24M0X51-A0](#) [CSTLS25M0X51-B0](#) [CSTLS18M0X51-B0](#) [CSTLS4M00G53093-A0](#) [CSTLS18M4X53-A0](#) [CSTNE16M0V510000R0](#) [CSTLS30M0X53-B0](#) [CSTLS33M8X53-B0](#) [CSTLS16M9X53-A0](#) [CSTLS6M40G56-B0](#) [CSTLS6M25G56-A0](#) [CSTNE14M7V510000R0](#) [CSTLS18M4X53-B0](#) [CSTLS33M0X51-B0](#) [CSTLS5M50G56-B0](#) [7B008000I01](#) [7D038400I01](#) [TAXM24M2ILDBET2T](#) [TAXM26M2IHDBET2T](#) [146-32.768-12.5-20-20/A](#) [3225-24.00-12-10-10/A](#) [7B009843M01](#) [CF4016M00009T8188042](#) [S32400001B0730D1JB](#) [X252016MLB4SI](#) [Q24FA20H00389](#) [CSTLS16M0X54-B0](#) [CSTLS4M19G56-B0](#) [9AC04194152080D2JB](#) [CST3.58MGW](#) [CSTCR4M91G55B-R0](#) [CSTLS3M68G56-B0](#) [S2100327072090](#) [FC-12M32.768KHZ9PF20PPM](#) [ASR315S2](#)