

# 深圳市胜丰宏电子有限公司

## APPROVAL SHEET

Customer:				
Customer P/N:	<u>E</u>	C 12038B2M220V		
Description:		EC FAN		
Model NO.:		EC 12038B2M220		
Version.:	Α	Issue NO.:	2021MF1129 Issu	ıе
date: 2021-	11-29	Quantity: 20PCS		
Please sign back Thanks!	this spec	ification for our record	d upon your approval	۱.
Company	у	CUSTOMER		
Stamp		APPROVAL		
		Stamp		
制作: 胡超		承认:		
复核: 李厚	 群	核准:		
核准: 温德	忠贵	日期:		

工厂地址: 东莞市凤岗镇竹塘下围村大塘北路6号合泰工业园A栋3楼

免费咨询和订购热线: 400-9920-988 官方网站 http://www.fancool.net/

E-Mail: fancool8@163.com

# 1.0: 一般规格 (General Speci fication)

项目(Item)		规格/条件(Specification/Condition)		
1	型号(Mode1 No.)	EC 12038B2M220		
2	外型尺寸(Outline. Dimension)	120*120*38		
3	工作电压 ( Operating Voltage)	EC85 -240 V		
4	额 定 电 压 (Rated .voltage)	EC 220V		
5	起动电压 Starting Voltage	EC ≤90.0V on/off		
6	额 定 电 流 (Rated current)	0.04A±10%	a. 额定电压(Rated .voltage) b.25℃ 65% RH c.After testing for 5 minutes	
7	消耗功率 (Power consumption)	9W±10%		
8	转 速 (Speed)	3700±10%RPM		
9	最大风量: (Max Airflow)	135.2CFM	a. 额定电压(Rated .voltage) b. AMCA 标准 (Standard) C. 额定电流(Rated current)	
10	最大静压: (Air .Static Pressure)	10.53mmH2O		
11	最大噪音(Max Noise)	45.29Max: Db-A	a. 额定电压(Rated Voltage) b. 18dB无响室(18dB Non-Echo Chamber) c. 标准(Standard): CNS 8753 / ISO 3744 d. Test Condition : ISO 7779 e. 距离(Distance): 1.0 M	
12	极数 (No.of.Pole)	4 极		
13	运转方向 (Rotating Direction)	逆时针/运转方向是从扇叶面看		
14	锁住保护 Lock Protection	□无□有		
15	自动启动保护 Auto Restar Protection	□无□有		
16	极性保护 Polarity Protection	VCC与GND反接时 不导通 Open circuit when Vcc & GND are exchanged		
17	恒速功能 fixed constant speed Function	□无□有		
18	PWM 功能 PWM function	□无□有		

## 2.0:主要材料/零件规格(Main Materials/parts Specification)

材	材料/零件 ( Materials/parts ) 规格(Specification)		rification)	
1	塑料材料/扇叶 外框 (Plastic Material/Blade,Housing)	PBT 黑色方框/7 叶弯叶		
2	轴承 (Bearing Type)	滚珠轴承(ball bear	ing)	
3	引線 (Lead Wire)	22#1007AVG 290MM	黑 (N) 黑 (L)	
4	端子 (Connector)	无		
5	环保要求 (EnvironmentalRequirement)	□ROHS	□ 无卤	□fireproof

# 3.0 電性規格 (Electrical Specifically ) 有 YES 输出 FG 方波 (齿型) 反馈信号。

絕緣阻抗 10MΩ/		0MΩ/裸線与外框間測量,500VDC/min		
1	Insulation	$10M\Omega/between unshackled wire and frame at$		
	Resistance	500VDC/min		
	絕緣耐压	5Ma Max./導線与外框間測量,500VAC/min		
2	Dielectric Strength	5Ma Max./Measured between lead wire(+)and frame at 500VAC/min		
3	防水等级 Waterproof level	IP X0		


## 4.0 环境测试 (Environmental Specification)

1	运转温/湿度范围	温度/Temperature:-10℃ - +70℃	
1	Operating Temp .Range	湿度/Humidity:5% - 95%RH	
2 保存温/湿度范围		温度/Temperature:-40℃ - +75℃	
4	Storage Temperature	湿度/Humidity:5% - 95%RH	
3	耐湿性	电气规格依据 MIL-STD 202F Method 103B	
3	Humidity	湿度: 95%RH 温度: 40±2℃	
4	热冲击	电气规格依据 MIL-STD 202F Method 107D	
4	Thermal Shock	Per MIL-STD 202F Method 107D, Condition D	
5	绝缘阶段	UL: A种	
Э	Insulation Shock	UL: Class A	
6	包装耐振动试验	包装后, XYZ 三方向施 1.1G load vibration test	
O	Packing Vibration Test	for 30min .No serious damage	

	包装耐冲击试验 Packing Shock Proof Test	捆包后,高50公分,1棱角3边6面自然落下,无严重损坏.
7		1comer,3edges, 6faces natural drop from 60cm high packing No serious damage

## 5.0 在无响室额定电压下之噪音测试

#### (NOISE IS MEASURED AT RATED VOLTAGE IN ANECHOIC)




(在背景噪音不超过 18dB (A) 的无响室内,将待测风扇通入额定的工作电压,悬掉入空中,将麦克风放于风扇同一平面且离待测风扇进风口一米处进行测试其 B&K 值) Noise is measured rated voItage in free air in anechoic chamber with B&K sound IeveI meter with microphone at a distance of one meter from the fan intake. The background noise is 18Db(A) max。

## 6.0 平均寿命说明 (Life Expectancy Explanation)

在指定恒温下持续工作后,经检验,90%能正常运转即可估算其平均使用寿命(The continuous duty life at given temperature after which,90% of testing units shall still be running)。

Bearing System	Test Temperature	Test time (H)
Two ball Bearing	25℃	60000

## 7.0 外观图:



### 8. 注意事项 (Nores)

8-1. 使用时请勿超出本规定所规定之极限,否则我们不保证此产品

We, will nor guarantee the products if the application of our products are exceeded the limitation which isspecified on the specification

8-2. 倘若要变更此份文件任何规格,请务必事先提出要求

In case of changes of the specification specified on thid document A WRITTEN NOTICEIS REQUESTED INADVANCE

- 8-3. 请勿触压着叶片以电源线缠绕着风扇或用力拉扯电源线,如此轴心与电源线将会被损坏 please do not touch the impeller with the pressure and never bring the fan with lead wire The bearing and lead wirenay be damaged
- 8-4. 本产品不保证因粉尘、水滴、小虫进入,而影响寿命与不良产生

No guarantee on the products against the safety problem or failure caused by powder dust,drop of water or insect

8-5. 如有任何资料及文件与此份资料不同,将以此份资料为主要参考

If there is any data or related documentation different from this data sheet. This data sheet is the preprinciple reference

8-6. 请勿在可燃性气体与任何有害环境中使用

please do not use the fan in the environment of corrosive gas or liquid or any detrimental gas

8-7. 请于六个月内使用,否则风扇存放在很高温或很低温及湿度很高的室温中,风扇于六个月后将可能会有漏电流产生

piease do not store the fan in the environment of high/low temperarure, high humidity or detrimental gas. Pleasestore within six months, every six months, shall be a leakage of electric current to the fan, even though the fan isstored in room temperature

8-8. 当风扇于运转转中,请勿企图将风扇锁死特别长的时间,如此,会因连续停止不转,产生高 热而烧毁风扇

while the fan is in operarion, please do not lock the fan intentionally for a long period of time, since the continuous stoppage will result in overheat and thus burnt out the fan.

8-9. 组装风扇时,请特别注意,因共振或振动产生的噪音

During the installation of the fan, please pay sudstantial attention to possible notice caused by resonance vibrationand shock

8-10. 当搬运或作业中,风扇如从 60cm 的高底落下,将会对叶片的平衡产生若干影响,特别是滚珠轴承避免掉落

It is very important to notify that avoid to drop fron 60cm height when in any movement or operation, it will impact the balance of blade. Especially ball bearing structure is avoided to drop down

8-11. 锁外壳之螺丝扭力不得超 4.6 kg -5.3 kg

The torque of the screw that locked the frame should not exceed 4.6kg-5.3kg



# CERTIFICATE

# ATTESTATION Certificate of Compliance

Technical file of the company mentioned below has been inspected and audit has been completed successfully

The EMC Directive 2014/30/EU has been taken as references for these processes.

Certificate's Holder

SHENZHEN SHENGFENGHONG ELECTRONICS CO., LTD.

Address

Third floor, building a, Hetai Industrial Park, NO:6, Datang North Road, Xiawei village, Zhutang, Fenggang town, Dongguan City, China

Manufacturer

: SHENGFENGHONG ELECTRONICS CO., LTD.

Address

No.1-2205 Yabao Rd., Bantian , Longgang Distict, Shenzhen, China

Product Name

cooling fan

SF12038, SF1504, SF1805, SF2006, SF2010, SF2507, SF2510, SF3007, SF3010, SF3507, SF3510, SF4007, SF4010, SF4015, SF4020, SF4028, SF4056, SF5010, SF5012, SF5015, SF5020, SF6010, SF6015, SF6020, SF6020, SF6010, SF5012, SF5012, SF5020, SF6010, SF6015, SF6020, SF602

Product Model (S)

SF6025, SF6038, SF7010, SF7015, SF7020, SF7025, SF7030, SF7530, SF8010, SF8015, SF8020, SF8025, SF8038, SF8076, SF9010, SF9015, SF9025, SF9038, SF9215, SF9225, SF9238, SF9733, SF10025, SF11025, SF12025, SF12032, SF14025, SF14038, SF15050, SF16038, SF16050, SF17238, SF17250, SF17251, SF18060, SF20060, SF22060, SF25489

Trade Mark

: N/A

Related Directive

: 2014/30/EU

Related Standards

EN 55032:2015 + A1:2020 + A11:2020

EN 55035:2017 + A11:2020

Certificate Number

HK2109183572E

Report No.

HK2109183572-1ER

Registration Date

Sep. 24, 2021





The information of the certificate can be checked through www.cer-mark.com. The CE mark which is shown on the certificate can only be used under the conditions that the products complete with all of the relevant Directives of EC Declaration of Conformity. The Manufacturer should be responsible for the internal production control so that the products complied with the essential requirements of the above mentioned Directive(s). Certificate holder must notify all changes to the original certification laboratory of HUAK.



#### Shenzhen HUAK Testing Technology Co., Ltd.

Add.:1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China Tel.:+86-755-2302 9901 Http://www.cer-mark.com Postcode:518103 E-mail: service@cer-mark.com



# CERTIFICATE

#### **ATTESTATION Certificate of Compliance**

Technical file of the company mentioned below has been inspected and audit has been completed successfully

The RoHS Directive 2015/863/EU amending Annex II to Directive 2011/65/EU has been taken as references for these processes.

Certificate's Holder : SHENZHEN SHENGFENGHONG ELECTRONICS CO., LTD.

Third floor, building a, Hetai Industrial Park, NO:6,

Address

Datang North Road, Xiawei village, Zhutang,

Fenggang town, Dongguan City, China

Manufacturer

SHENZHEN SHENGFENGHONG ELECTRONICS CO.,LTD.

Address

No.1-2205 Yabao Rd., Bantian, Longgang Distict, Shenzhen China

Product Name

cooling fan

SF12038, SF1504, SF1805, SF2006, SF2010, SF2507, SF2510, SF3007, SF3010, SF3507, SF3510, SF4007, SF4010, SF4015, SF4020, SF4028, SF4056, SF5010, SF5012, SF5015, SF5020, SF6010, SF6015, SF6020, SF6025, SF6038, SF7010, SF7015, SF7020, SF7025, SF7030, SF7530,

Product Model (S)

SF8010, SF8015, SF8020, SF8025, SF8038, SF8076, SF9010, SF9015, SF9025, SF9038, SF9215, SF9225, SF9238, SF9733, SF10025, SF11025, SF12025, SF12032, SF12038, SF14025, SF14038, SF15050, SF16038, SF16050, SF17238, SF17250, SF17251, SF18060, SF20060, SF22060, SF25489

Trade Mark

Related Directive

Directive 2015/863/EU amending Annex II to Directive 2011/65/EU

Certificate Number :

HK2109183877R

Report No.

HK2109183877-1RR

Registration Date

October 09, 2021





The information of the certificate can be checked through www.cer-mark.com. The CE mark which is shown on the certificate can only be used under the conditions that the products complete with all of the relevant Directives of EC Declaration of Conformity. The Manufacturer should be responsible for the internal production control so that the products complied with the essential requirements of the above mentioned Directive(s). Certificate holder must notify all changes to the original certification laboratory of HUAK.



#### Shenzhen HUAK Testing Technology Co., Ltd.

Add.:1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China Tel.:+86-755-2302 9901 Http://www.cer-mark.com Postcode:518103 E-mail: service@cer-mark.com

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Fans category:

Click to view products by SHENG FENG manufacturer:

Other Similar products are found below:

F1238H24B-FHR F1238X24B1-FSR-TTL 8312R G9225S05B2-FSR AUB0612L G4020H05B2-RSR-EM 298DM-2LP11-000 298DS2LP11-000A AUB0912H-F00 6222N USTF501005HW 8412GLV 8412NGL-12 4114N/12HHR-297 6448-384 PMD2408PMB1-A(2).F.GN
RACK0224 3258JH 4114N/17-251 622/2N 4318/2R 4412F/2D OD127AP-28HTB 424JMU EF40101BX-1000U-G99 4414/2HH
AQ0612MB-A70GL(T)#22 9GA0924L4021 9GA0924M4021 9GA0924M4011 9GA0912M4D011 9GA0912F4021 9GA0912H4D011
9GA0824L20021 9GA0824L20011 9GA0812A2002 9GA0812B2D001 9GA0812L20021 9WP1248M1021 9GA0824L2D001
9GA0912W402 9GA0912M402 9GA0824B2D001 9GA0824A20021 9GA0912W4021 9GA0924W402 9GA0812L2D0011
9GA0812A20021 9GA0824L2001 9GA0824L2002