

## Dual Common Anode Zener TVS

 Lead(Pb)-Free

### Features:

- \*Allows Either Two Separate Unidirectional Configurations or a Single Bidirectional Configurations.
- \*Low Leakage Current.
- \*24-40 Watts Peak Power Protection.
- \*Excellent Clamping Capability.
- \*ESD Rating of Class N(exceeding 16KV)per the Human Body Model.
- \*Transient Voltage Suppressors Encapsulated in a SOT-23 Package.


### Mechanical Data:

- \*Case: Molded Epoxy
- \*Marking: Marking Code
- \*Maximum Case Temperature for Soldering Purpose: 260 C for 10 sec.
- \*Weight: 0.008grams(approx.)

SMALL SIGNAL  
ZENER DIODES  
300m WATTS  
3-26 VOLTS



## SOT-23 Outline Dimensions



## Maximum Ratings (TA=25°C Unless otherwise Noted)

| Characteristics  | Symbol                            | Value       |             |
|--|-----------------------------------|-------------|-------------|
| Peak Power Dissipation @ 1.0 ms @ $T_L \leq 25^\circ\text{C}$ <sup>(1)</sup><br>MMBZ5V6A thru MMBZ10VA<br>MMBZ12VA thru MMBZ33VA | P <sub>PK</sub>                   | 24<br>40    | W           |
| Total Power Dissipation on FR-5 Board <sup>(2)</sup> @ TA=25°C<br>Derate above 25°C  | P <sub>D</sub>                    | 225<br>1.8  | mW<br>mW/°C |
| Thermal Resistance Junction-to-Ambient   | R <sub>θJA</sub>                  | 556         | °C/W        |
| Total Power Dissipation on Alumina Substrate <sup>(3)</sup> @ TA =25°C<br>Derate above 25°C                                      | P <sub>D</sub>                    | 300<br>2.4  | mW<br>mW/°C |
| Thermal Resistance Junction-to-Ambient   | R <sub>θJA</sub>                  | 417         | °C/W        |
| Junction and Storage Temperature Range   | T <sub>J</sub> , T <sub>STG</sub> | -55 to +150 | °C          |
| Lead Solder Temperature-Maximum(10 Second Duration)  | T <sub>L</sub>                    | 260         | °C          |

NOTE: 1. Non-Repetitive Current Pulse, per FIG 5 and Derated above TA=25°C per FIG 6.

2. FR-5=1.0×0.75×0.62 in.


3. Alumina=0.4×0.3×0.024m, 99.5% alumina

## Electrical Characteristics


(TA=25°C unless otherwise noted)

**UNIDIRECTIONAL** (Circuit tied to Pins 1 and 3 or 2 and 3)

| Symbol           | Parameter  |
|------------------|--|
| I <sub>PP</sub>  | Maximum Reverse Peak Pulse Current                 |
| V <sub>C</sub>   | Clamping Voltage @ I <sub>PP</sub>                 |
| V <sub>RWM</sub> | Working Peak Reverse Voltage                       |
| I <sub>R</sub>   | Maximum Reverse Leakage Current @ V <sub>RWM</sub> |
| θV <sub>BR</sub> | Breakdown Voltage @ I <sub>T</sub>                 |
| I <sub>T</sub>   | Test Current                                       |
| V <sub>BR</sub>  | Maximum Temperature Coefficient of V <sub>BR</sub> |
| I <sub>F</sub>   | Forward Current                                    |
| V <sub>F</sub>   | Forward Voltage @ I <sub>F</sub>                   |
| Z <sub>ZT</sub>  | Maximum Zener Impedance @ I <sub>ZT</sub>          |
| I <sub>ZK</sub>  | Reverse Current                                    |
| Z <sub>ZK</sub>  | Maximum Zener Impedance @ I <sub>ZK</sub>          |



## Device Marking

| Item            | Marking  | Equivalent Circuit diagram  |
|-----------------|--|---|
| MMBZ5V6A Series | XX=Specific Device Code<br>(See Table on Page 3) |  |



**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

**UNIDIRECTIONAL** (Circuit tied to Pins 1 and 3 or Pins 2 and 3)

( $V_F = 0.9\text{ V Max @ } I_F = 10\text{ mA}$ )

**24 WATTS**

| Device   | Device Marking | $V_{RWM}$<br>Volts | $I_R @ V_{RWM}$<br>uA | Breakdown Voltage  |     |      | @ $I_T$<br>mA | Max Zener Impedance <sup>(5)</sup> |                        |       | $V_C @ I_{PP}$ <sup>(6)</sup> |      | $\theta V_{BR}$<br>mV/°C |
|----------|----------------|--------------------|-----------------------|--------------------|-----|------|---------------|------------------------------------|------------------------|-------|-------------------------------|------|--------------------------|
|          |                |                    |                       | $V_{BR}^{(4)}$ (V) |     |      |               | $Z_{ZT}$<br>@ $I_{ZT}$             | $Z_{ZK}$<br>@ $I_{ZK}$ | $V_C$ | $I_{PP}$                      |      |                          |
|          |                |                    |                       | Min                | Nom | Max  |               | $\Omega$                           | $\Omega$               | V     | A                             |      |                          |
| MMBZ5V6A | 5A6            | 3.0                | 5.0                   | 5.32               | 5.6 | 5.88 | 20            | 11                                 | 1600                   | 0.25  | 8.0                           | 3.0  | 1.26                     |
| MMBZ6V2A | 6A2            | 3.0                | 0.5                   | 5.89               | 6.2 | 6.51 | 1.0           | -                                  | -                      | -     | 8.7                           | 2.76 | 2.80                     |
| MMBZ6V8A | 6A8            | 4.5                | 0.5                   | 6.46               | 6.8 | 7.14 | 1.0           | -                                  | -                      | -     | 9.6                           | 2.5  | 3.4                      |
| MMBZ9V1A | 9A1            | 6.0                | 0.3                   | 8.65               | 9.1 | 9.56 | 1.0           | -                                  | -                      | -     | 14                            | 1.7  | 7.5                      |
| MMBZ10VA | 10A            | 6.5                | 0.3                   | 9.50               | 10  | 10.5 | 1.0           | -                                  | -                      | -     | 14.2                          | 1.7  | 7.5                      |

( $V_F = 0.9\text{ V Max @ } I_F = 10\text{ mA}$ )


**40 WATTS**

| Device   | Device Marking | $V_{RWM}$<br>Volts | $I_R @ V_{RWM}$<br>nA | Breakdown Voltage  |     |       | @ $I_T$<br>mA | $V_C @ I_{PP}^{(6)}$ |          | $\theta V_{BR}$<br>mV/°C |
|----------|----------------|--------------------|-----------------------|--------------------|-----|-------|---------------|----------------------|----------|--------------------------|
|          |                |                    |                       | $V_{BR}^{(4)}$ (V) |     |       |               | $V_C$                | $I_{PP}$ |                          |
|          |                |                    |                       | Min                | Nom | Max   |               | V                    | A        |                          |
| MMBZ12VA | 12A            | 8.5                | 200                   | 11.40              | 12  | 12.60 | 1.0           | 17                   | 2.35     | 7.5                      |
| MMBZ15VA | 15A            | 12                 | 50                    | 14.25              | 15  | 15.75 | 1.0           | 21                   | 1.9      | 12.3                     |
| MMBZ18VA | 18A            | 14.5               | 50                    | 17.10              | 18  | 18.90 | 1.0           | 25                   | 1.6      | 15.3                     |
| MMBZ20VA | 20A            | 17                 | 50                    | 19.00              | 20  | 21.00 | 1.0           | 28                   | 1.4      | 17.2                     |
| MMBZ27VA | 27A            | 22                 | 50                    | 25.65              | 27  | 28.35 | 1.0           | 40                   | 1.0      | 24.3                     |
| MMBZ33VA | 33A            | 26                 | 50                    | 31.35              | 33  | 34.65 | 1.0           | 46                   | 0.87     | 30.4                     |

4.  $V_{BR}$  measured at pulse test current  $I_T$  at an ambient temperature of  $25^\circ\text{C}$ .


5.  $Z_{ZT}$  and  $Z_{ZK}$  are measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for  $I_{Z(AC)} = 0.1 I_{Z(DC)}$ , with the AC frequency = 1.0 kHz.

6. Surge current waveform per Fig 5 and derate per Fig 6



**FIG.7 Maximum Non-repetitive Surge Power,  $P_{PK}$  Versus PW**

Power is defined as  $V_{RSM} \times I_{Z(pk)}$  where  $V_{RSM}$  is the clamping voltage at  $I_{Z(pk)}$ .




**FIG.8 Maximum Non-repetitive Surge Power,  $P_{PK(NOM)}$  Versus PW**

Power is defined as  $V_Z(NOM) \times I_{Z(pk)}$  where  $V_Z(NOM)$  is the nominal Zener voltage measured at the low test current used for voltage classification









**FIG.1 Typical Breakdown Voltage Versus Temperature**

(Upper curve for each voltage is bidirectional mode,  
lower curve is unidirectional mode)




**FIG.2 Typical Leakage Current Versus Temperature**




**FIG.3 Typical Capacitance Versus Bias Voltage**


(Upper curve for each voltage is bidirectional mode,  
lower curve is unidirectional mode)



**FIG.4 Steady State Power Derating Curve**



**FIG.5 Pulse Waveform**



**FIG.6 Pulse Derating Curve**



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [ESD Suppressors / TVS Diodes](#) category:*

*Click to view products by [Shikues](#) manufacturer:*

Other Similar products are found below :

[60KS200C](#) [D18V0L1B2LP-7B](#) [D5V0F4U5P5-7](#) [DESD5V0U1BB-7](#) [NTE4902](#) [P4KE27CA](#) [P6KE11CA](#) [P6KE39CA-TP](#) [P6KE8.2A](#)  
[SA110CA](#) [SA60CA](#) [SA64CA](#) [SMBJ12CATR](#) [SMBJ33CATR](#) [SMBJ8.0A](#) [ESD101-B1-02ELS E6327](#) [ESD105-B1-02EL E6327](#) [ESD112-B1-02EL E6327](#) [ESD119B1W01005E6327XTSA1](#) [ESD5V0L1B02VH6327XTSA1](#) [ESD7451N2T5G](#) [19180-510](#) [CPDT-5V0USP-HF](#)  
[3.0SMCJ33CA-F](#) [3.0SMCJ36A-F](#) [HSPC16701B02TP](#) [D3V3Q1B2DLP3-7](#) [D55V0M1B2WS-7](#) [DESD5V0U1BL-7B](#) [DRTR5V0U4SL-7](#)  
[SCM1293A-04SO](#) [ESD200-B1-CSP0201 E6327](#) [SM12-7](#) [SMF8.0A-TP](#) [SMLJ45CA-TP](#) [CEN955 W/DATA](#) [82350120560](#) [VESD12A1A-](#)  
[HD1-GS08](#) [CPDUR5V0R-HF](#) [CPDQC5V0U-HF](#) [CPDQC5V0USP-HF](#) [CPDQC5V0-HF](#) [D1213A-01LP4-7B](#) [D1213A-02WL-7](#)  
[MMAD1108/TR13](#) [5KP100A](#) [5KP15A](#) [5KP18A](#) [5KP48A](#) [5KP90A](#)